Milwaukee

HEAVY-DUTY TOOLS

for Contractors and Industry





UNITED ELECTRIC CORPORATION
DE MINNEAPOLIS, INC. - AURORA BRANCH
212 East Fourth Avenue North
AURORA, MINNESOTA 55705

CATALOG 473

Authorized Sales

MILWAUKEE Electric Tools are sold only through Authorized Distributors with experienced personnel to assist you in selecting the proper tools for your specific requirements. You derive a real advantage in buying from your MILWAUKEE Distributor. He not only maintains well balanced inventories of tools for immediate shipment, but places at your disposal the services of his trained and experienced personnel to advise you on special product applications.

TESTED-LISTED

MILWAUKEE Heavy-Duty Tools bearing monograms of Underwriters Laboratories, Inc., or Canadian Standards Association are listed by their laboratories for industrial use.

SAFETY SEAL

The Milwaukee Electric Tool Corporation is a member of the Power Tool Institute and is authorized to display that organizations safety seal. MILWAUKEE assures its users of its concern for their safety as well as the safe application of its products by supporting and adhering to the principles for which the Safety Seal stands: 1. That the manufacturer's power tools including the particular tool associated with the Seal, are produced in accordance with applicable Standards for Safety of Underwriters' Laboratories and American National Standards (ANSI). 2. That compliance with applicable safety standards is assured by independent inspection and testing conducted by Underwriters' Laboratories (UL). 3. That every motorized tool is inspected under power. 4. That every tool has with it adequate instructions and a list of safety rules for the protection of the user. 5. That the tool manufacturer is a member of the Power Tool Institute and is a sponsor of the Institute's Consumer Safety Education Program.

Milwaukee

HEAVY DUTY TOOLS

Feature Highest Quality Materials and Workmanship

Guarantee

Every MILWAUKEE Tool is thoroughly inspected and tested before leaving the factory. It is guaranteed against defective workmanship and materials. Should any trouble develop, return the COMPLETE tool prepaid to the Factory, Branch, or nearest Authorized MILWAUKEE Service Station. If inspection shows trouble is caused by defective workmanship or material, all repairs will be made without charge and the tool returned, transportation prepaid. The guarantee does not apply where: Repairs or attempted repairs have been made by persons other than Factory, Branch or Authorized Service Station personnel; repairs are due to normal wear; the tool has been abused or in an accident; misuse is evident — caused by overloading the tool beyond its rated capacity, use of the tool after partial failure or use with improper accessories. No other guarantee, written or verbal, is authorized.

INDEX

ALTERNATORS 50,51
BATTERY POWERED TOOLS 7
CARBIDE-TIP BITS 10,22,23,25
DIAMOND DRILLING EQUIPMENT
- Dymodrills, Dymorig, Vac-U-Rig® 14,15
- Dymobits and Accessories 16

DRAIN CLEANER 13
DRILLS, "HOLE-SHOOTERS" 4,5,6,7,9
DRILL ACCESSORIES 4,5,6,7,9,10,11,12
DRILL BITS 10,11
DRILL KITS – Right Angle 6
DRILL STANDS 9
EXTENSION CORDS 3,7,10
GRINDERS
- Bench Grinders and Accessories 47
- Die Grinder 43
- Disc Grinders and Accessories 44,45
- Portable Grinders and Accessories 46
- Straight Grinder 43
- Tuck Point Grinders and Accessories 46

HAMMERS – Accessories
- ¾" Electric Hammer 21
- Hammer-Drill 22
- Pittsburgh Lock 49
- Rotary Hammers and Accessories . . 23,24,25,26

HOLE HAWGS 8
HOLE SAWS 12
IMPACT WRENCHES and Accessories 42
MAGNETIC DRILL PRESSES 17
NIBBLER 49
NUT RUNNERS and Accessories 39
PARTS – Quick Reference 52,53
POLISHERS and Accessories 34
RIGHT ANGLE AND 33° DRIVES 4,7
ROUTERS – Bits – Accessories 35,36,37
SANDERS
- Disc and Accessories 44,45
- Orbital 34

SANDER-GRINDERS 44,45
SAWS
- Band Saw and Blades 28
- Chain and Accessories 27
- Circular and Accessories 32,33
- Jig-Saw and Accessories 29

SAWZALL® and Blades 30,31
SCREW-SHOOTERS
- and Accessories 10,38,39,40,41
- Drywall 40
- Mobile Home Kit 40
- No-Hub 40
- For Self-Drilling Fasteners 38

SHEARS 48
TAPPER 43
VACUUM CLEANERS 18,19,20

AMPS . . . HORSEPOWER . . . EFFICIENCY

An Electric Tool is only as good as its motor. No matter what other desirable features any tool may have, the motor is the most vital part . . . the heart of the tool.

All motors draw more or less amperes depending upon the various loads applied. The motor converts electrical energy to mechanical energy. If the amount of loss is small in conversion, the motor's efficiency becomes greater, resulting in more output at the working end of the tool. The ampere rating of the motor on the MILWAUKEE nameplate is based upon continuous heavy-duty operation to provide maximum efficiency at full rated load. MILWAUKEE motors are conservatively rated and have the reserve horsepower for extra heavy-duty jobs.

GENERAL INFORMATION

Unless otherwise indicated, the tools listed in this catalog have universal motors operating on single-phase current (25-60 Hz) of the specified voltage. All tools (except double insulated and 12 volt models), have 3 wire conductor cords with 3 prong rubber plugs for use in grounded receptacles. Double insulated tools listed in the catalog feature an extra layer of insulation which provides extra protection against electrical shock and eliminates the need for grounding. These tools are equipped with a rubber, 2 prong plug and can be used in all standard receptacles, offering an advantage where proper grounding is not available. The Milwaukee Electric Tool Corporation reserves the right to make any changes in or improvements on its products without incurring any liability or obligation whatever and without being required to make any corresponding changes or improvements in products previously manufactured or sold.

INSTRUCTIONS

An instruction booklet is furnished with each MILWAUKEE Electric Tool. Please read it carefully for best care and performance. IMPORTANT — Pay particular attention to all safety precautionary measures before operating any power tool.

EXTENSION CABLE CHART

When an extension cord is used, it should always be a 3 wire cord to permit proper grounding. If using extension cord out of doors, be sure it is rated for outdoor use. As the distance from the supply outlet increases, heavier gauge extensions are required. The use of extension cords of inadequate size wire causes a serious drop in voltage, loss of power and possible motor damage. This table is based on limiting line voltage drop to 5 volts at 150% of rated amperes. Always inspect cords before using and make any necessary repairs or replacements.

Ampere rating (on Nameplate)	0-2.00	2.10-3.4	3.5-5.00	5.10-7.0	7.10-12.0	12.1-16.0	
Ext. Cable Length	Wire Size						
25 Ft.	18	18	18	18	16	14*	
50 Ft.	18	18	18	16*	14*	12	
75 Ft.	18	18	16	14	12	10	
100 Ft.	18	16	14	12	10	8	Not normally available as flexible extension cord.
150 Ft.	16	14	12	12	8	8	
200 Ft.	16	14	12	10	8	6	
300 Ft.	14	12	10	8	6	4	
400 Ft.	12	10	8	6	4	4	
500 Ft.	12	10	8	6	4	2	
600 Ft.	10	8	6	4	2	2	
800 Ft.	10	8	6	4	2	1	
1000 Ft.	8	6	4	2	1	0	

*See page 10 for Extension Cords.

HEAVY-DUTY Milwaukee HOLE-SHOOTERS

With Powerful, Milwaukee Built Motors For Continuous Industrial Use

MILWAUKEE heavy-duty pistol grip Hole-Shooters are available in a wide variety of capacities, speeds and designs to meet your specific drilling and handling requirements. Available with In-Line design handles or pistol grips, they are all engineered to give dependable performance and long life, even under the most severe operating conditions. In addition to constant speed models, three models are also available to provide complete speed control from zero to the tool's maximum RPM. Only the highest quality materials are used in the manufacture of these drills. All have heat-treated nickel alloy steel gears and hardened shafts, heavy-duty MILWAUKEE-built motors, lockable trigger switches and Jacobs industrial, geared, key-type chucks with rubber-flex key holders.

A

1/4" HOLE-SHOOTER
PISTOL GRIP

Best 1/4" heavy-duty drill value. Lightweight, compact. Lifetime lubricated ball bearings — single gear reduction. Especially designed for general maintenance. Comfortable pistol grip handle of durable glass reinforced nylon designed to withstand the roughest service use.

B

1/4" HOLE-SHOOTER
TRIGGER SPEED CONTROL WITH REVERSING SWITCH

A Trigger Speed Control unit, with the same features as above, provides speeds from 0 to 2500 RPM. No center punching . . . no drill bit walking . . . drills almost everything including ceramics and glass. Reversing switch is located above trigger switch.

C

1/4" and 3/8" HOLE-SHOOTERS
IN-LINE GRIP

Most powerful Drills of this type made for production drilling . . . deliver top horse power at maximum efficiency. Built for continuous use on the toughest jobs. All have double gearing for greater torque.

D

1/4" and 3/8" HOLE-SHOOTERS
PISTOL GRIP

These drills have the same power and performance features as the In-Line grip models above but with a durable glass reinforced nylon pistol grip handle.

E

1/4" and 3/8" HOLE-SHOOTERS
TRIGGER SPEED CONTROL WITH REVERSING SWITCH

The Trigger Speed Control models give speeds of 0 to 2000 RPM on the 1/4" Drill and 0 to 1000 on the 3/8" model. Other specifications are similar to those for the Drills above. Reversing switch is located above trigger switch.

SPECIFICATIONS

Group	Catalog No.	Cap. (In.) in Steel	Volts	Spindle Dia. and Thread	Speed rpm No Load	Gear Train	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
A	0101	1/4	115	3/8-24	2000	Sngl.	8 3/8	3 1/2	6	Yes
B	0102-1	1/4	115 AC Only	#1 J.T.*	0 To 2500	Sngl.	8 3/8	3 1/2	6	Yes
C	0120	1/4	115	3/8-24	2000	Dbl.	9 1/2	3 3/4	6	Yes
	0140	1/4			3500					
	0160 ★	1/4			5000					
	0180	1/4			2500					
	0190	1/4			1700					
	0200	5/16			1000		10			
	0220	3/8			650		10 1/4	4	7	
D	0121	1/4	115	3/8-24	2000	Dbl.	8 3/4	3 3/4	6	Yes
	0141	1/4			3500					
	0161 ★	1/4			5000					
	0181	1/4			2500					
	0191	1/4			1700					
	0221	3/8			650		9 1/2	4	7	
E	0122-1	1/4	115 AC Only	#1 J.T.*	0 To 2000	Dbl.	8 3/4	3 3/4	6	Yes
	0222-1	3/8		#2 J.T.*	0 To 1000		9 1/2	4	7	

★ Recommended only for drilling skin aluminum and other non-ferrous metals.
* Jacobs Taper Spindle.

AUXILIARY SIDE HANDLE
For Drills Listed Above Only.



Catalog No. 49-15-0100

Type "A" Grease

1/2 lb. can **Catalog No. 49-08-0500**
1 lb. can **Catalog No. 49-08-0800**

RIGHT ANGLE DRIVE UNIT
One to One Gear Ratio

Compact and closely coupled, the Right Angle Unit is available only for Drills in groups C and D except Catalog Nos. 0140, 0141, 0160, and 0161. It is ideal for drilling in tight spots in cabinet making, carpentry, automotive, heating, ventilating and many other industries.

Catalog No. 48-06-2890
chuck not included
Net Wt. 1 lb.



Chuck, removed from Drill, is threaded on spindle of angle unit which couples to Drill. It can be locked in any position within 360°.

STEEL CARRYING CASE
For drills in group A through E above
Catalog No. 48-55-0710

TRIGGER SPEED CONTROL REVERSING SWITCH

Milwaukee Trigger Speed Control-Reversing switches let you drill through wood, steel, masonry, ceramic tile and practically any other material at the exact speed required for the job. The further the trigger is depressed, the faster the tool operates. Reversing Lever is conveniently located above trigger for maximum drilling versatility. Mechanical interlock prevents accidental reversing while motor is running.

HEAVY-DUTY Milwaukee HOLE-SHOOTERS

BALL AND ROLLER BEARINGS

1/4", 3/8", 1/2" CAPACITIES
GEARED FOR CONTINUOUS PRODUCTION DRILLING

These D-Handle Drills with powerful MILWAUKEE motors are built for rugged performance and many years of useful service. They are known for their ability to stand up under full load at their maximum rating and for handling a wide variety of applications. Models with multiple gear reduction have greater torque output . . . gears transmit smooth, efficient power. The switch for models with reversible motors is conveniently located below the trigger switch. All have heat-treated, helical-cut alloy steel gears and hardened shafts, Jacobs industrial, geared key-type chuck, rubber flex key holder, and a 360° adjustable side handle.

NEW 1/4", 3/8", 1/2" HOLE SHOOTERS

All models designed with comfortable, durable glass reinforced nylon handles. Powerful Milwaukee built motors deliver maximum power for the toughest jobs . . . with speeds and capacities to meet almost any production requirement.

SPECIFICATIONS

Catalog No.	Cap. (In.) in Steel	Volts	Spindle Dia. and Thread	Speed No Load (RPM)	Gear Train	Lgth. (Ins.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
0801	1/4	115	1/2"-20	1800	DBL.	13 1/4	5 3/4	9	Yes
0871	3/8	115	1/2"-20	1350	DBL.	13 7/8	6 1/2	10	Yes
1001	1/2	115	1/2"-20	600	DBL.	13 7/8	6 1/4	10	Yes
1001-1 Rev.	1/2	115	1/2"-20	600	DBL.	14 1/8	6 1/4	10	Yes
1101	1/2	115	1/2"-20	500	TRPL.	14 1/4	6 1/2	10	Yes
1101-1 Rev.	1/2	115	1/2"-20	500	TRPL.	14 1/8	6 3/4	10 1/2	Yes
1105-1 Rev.	1/2	115	1/2"-20	550	TRPL.	14 1/8	6 3/4	10 1/2	Yes
1201	1/2	115	1/2"-20	350	TRPL.	14 1/4	6 1/2	10	Yes
1201-1 Rev.	1/2	115	1/2"-20	350	TRPL.	14 1/8	6 3/4	10 1/2	Yes
1250-1 Rev.	★	115	1/2"-20	950	DBL.	14 1/8	6 1/2	10	Yes

NEW 1/4", 3/8", 1/2" DOUBLE INSULATED HOLE SHOOTERS

New armature construction provides extra layer of insulation between the electrical windings and the spindle. Double insulated against internal and external electrical hazards. Two prong plug fits any 110 volt receptacle. Ideal for carpenters, electricians and plumbers who don't have grounded receptacles to use.

0805†	1/4	115	1/2"-20	1800	DBL.	13 1/4	5 3/4	9	Yes
0875†	3/8	115	1/2"-20	1350	DBL.	13 7/8	6 1/2	10	Yes
1106-1 Rev.†	1/2	115	1/2"-20	500	TRPL.	14 1/8	6 3/4	10 1/2	Yes
1251-1 Rev.†	★	115	1/2"-20	950	DBL.	14 1/8	6 1/2	10	Yes

1/4", 5/16", 3/8", 1/2" HOLE SHOOTERS

All models designed with all aluminum housings and standard 3 prong plug. Speeds and capacities to meet most production requirements.

0800	1/4	115	1/2"-20	2000	DBL.	12 1/2	5 1/2	9	Yes
0850	5/16	115	1/2"-20	1400	DBL.	12 1/2	5 1/2	9	Yes
0870	3/8	115	1/2"-20	1000	DBL.	13	6 1/4	10	Yes
0890	3/8	115	1/2"-20	850	DBL.	13	6 1/4	10	Yes
1000	1/2	115	1/2"-20	560	DBL.	13	6 1/2	10	Yes
1000-1 Rev.	1/2	115	1/2"-20	560	DBL.	13 1/4	6 1/2	10	Yes
1100	1/2	115	1/2"-20	450	TRPL.	13 1/4	6 3/4	10	Yes
1100-1 Rev.	1/2	115	1/2"-20	450	TRPL.	13 1/4	6 3/4	10	Yes
1200	1/2	115	1/2"-20	320	TRPL.	13 1/4	6 3/4	10	Yes
1200-1 Rev.	1/2	115	1/2"-20	320	TRPL.	13 1/4	6 3/4	10	Yes

NOTE: Abbreviation "Rev." following Catalog No. indicates reversing motor. ★ 3/8" capacity with 1/2" chuck for fast wood boring. † Double Insulated.

TYPE "A" GREASE
1/2 LB. CAN CAT. NO. 49-08-0500
1 LB. CAN CAT. NO. 49-08-0800

AUXILIARY SIDE HANDLE
CAT. NO. 49-15-0200
Same as furnished with above drills.
For D-Handle drills only.

SEE PAGE 6 FOR RIGHT ANGLE DRIVE KITS AND PAGE 7 FOR RIGHT ANGLE DRIVE UNITS

HEAVY-DUTY Milwaukee RIGHT ANGLE DRILL KITS

FOR ELECTRICIANS • PLUMBERS • MAINTENANCE MEN

CATALOG NOS. 3001-1, 3101, 3101-1, 3106-1, 3201-1, 3251-1
WITH GLASS REINFORCED NYLON HANDLES

CATALOG NOS. 3000, 3100, 3100-1, 3200, 3200-1

PLUMBERS KITS

CATALOG NO. 3100
Kit contains No. 1100, 450 R.P.M. Heavy-Duty ½" drill, No. 48-06-2870 Right Angle Drive, 1⅛" Auger Bit, 2⁹⁄₁₆" Selfeed Bit, wrench, chuck remover bar, side handle and steel carrying case.

CATALOG NO. 3100-1
Same as above except with No. 1100-1, 450 R.P.M. Heavy-Duty ½" reversing drill and No. 48-06-2871 reversing Right Angle Drive.

CATALOG NO. 3101
NEW Same as 3100 except with No. 1101, 500 R.P.M. Heavy-Duty ½" drill with glass reinforced nylon handle.

CATALOG NO. 3101-1
NEW Same as above except with No. 1101-1, 500 R.P.M. Heavy-Duty ½" reversing drill with glass reinforced nylon handle, and No. 48-06-2871 reversing Right Angle Drive.

CATALOG NO. 3105-1
Kit contains No. 1105-1, 550 R.P.M. Heavy-Duty ½" reversing drill with glass reinforced nylon handle, No. 48-06-2871 reversing Right Angle Drive, 1⅛" Auger Bit, 2⁹⁄₁₆" Selfeed Bit, chuck remover bar, side handle, wrench and steel carrying case.

CATALOG NO. 3106-1
NEW Kit contains *New Double Insulated* No. 1106-1, 500 R.P.M. Heavy-Duty ½" reversing drill with glass reinforced nylon handle, No. 48-06-2871 reversing Right Angle Drive, 1⅛" Auger Bit, 2⁹⁄₁₆" Selfeed Bit, wrench, side handle, chuck remover bar, and steel carrying case.

CATALOG NO. 3200
Kit contains No. 1200, 320 R.P.M. Heavy-Duty ½" drill, No. 48-06-2870 Right Angle Drive, 1⅛" Auger Bit, 2⁹⁄₁₆" Selfeed Bit, wrench, side handle, chuck remover bar, and steel carrying case.

CATALOG NO. 3200-1
Same accessories as above except with 1200-1, 320 R.P.M. Heavy-Duty ½" reversing drill and No. 48-06-2871 reversing Right Angle Drive.

CATALOG NO. 3201-1
NEW Same accessories as above except 1201-1, 350 R.P.M. Heavy-Duty ½" reversing drill with glass filled nylon handle and No. 48-06-2871 reversing Right Angle Drive.

ELECTRICIANS KITS

CATALOG NO. 3000
Kit contains No. 1000, 560 R.P.M. Heavy-Duty ½" drill, No. 48-06-2870 Right Angle Drill, ¾" bit, wrench, chuck remover bar, side handle and steel carrying case.

CATALOG NO. 3000-1
Same as above except with No. 1000-1, 560 R.P.M. Heavy-Duty reversing ½" drill and No. 48-06-2871 reversing Right Angle Drive.

CATALOG NO. 3001-1
NEW Kit contains No. 1001-1, 600 R.P.M. Heavy-Duty ½" reversing drill with glass reinforced nylon handle, No. 48-06-2871 reversing Right Angle Drive, ¾" bit, wrench, chuck remover bar, side handle and steel carrying case.

CATALOG NO. 3251-1
NEW Same as above kit, except with *New Double Insulated* No. 1251-1, 950 R.P.M. Heavy-Duty reversing drill with glass reinforced nylon handle and ¾" ship auger bit. Has ⅜" capacity with ½" chuck for fast wood boring.

SPECIFICATIONS

Kit Catalog No.	With Drill	RAD UNIT SPEEDS RPM Low Side	RPM High Side	Ship Wt. Lbs.	O.S.H.A. Compliance
3000	1000	375	840	21	Yes
3000-1 Rev.	1000-1	375	840	21	Yes
3001-1 Rev.	1001-1	400	900	21	Yes
3100	1100	300	675	25	Yes
3100-1 Rev.	1100-1	300	675	25	Yes
3101	1101	335	750	25	Yes
3101-1 Rev.	1101-1	335	750	25	Yes
3105-1 Rev.	1105-1	365	825	25	Yes
3106-1 Rev.†	1106-1†	335	750	25	Yes
3200	1200	215	480	25	Yes
3200-1 Rev.	1200-1	215	480	25	Yes
3201-1 Rev.	1201-1	230	525	25	Yes
3251-1 Rev.†	1251-1†	630	1425	25	Yes

NOTE: Abbreviation "Rev." following Catalog No. indicates reversing motor. †Double Insulated Tool

NOTE

See preceding page for specifications on ½" Hole-Shooters included in these kits.

STEEL CARRYING CASE
(when ordered separately)
For D-Handle Right Angle Drills
Catalog No. 48-55-0085

Type "A" Grease

½ lb. can **Catalog No. 49-08-0500**
1 lb. can **Catalog No. 49-08-0800**

HEAVY-DUTY Milwaukee RIGHT ANGLE DRILLS

FOR CLOSE QUARTER DRILLING

Catalog No. 48-06-2870

½" DRILL WITH RIGHT ANGLE DRIVE
Head and handle swivel 360° and can be locked tight in any position.

Used with D-Handle Drills Described on Preceding Page

The MILWAUKEE Right Angle Drive Unit is used extensively for drilling between joists, studding, in tight corners or in close quarters on machinery equipment. It provides two additional drilling speeds. Chuck transferred from drill to LOW spindle of right angle unit reduces drills normal speed by ⅓ and increases drilling torque by 50%. Chuck transferred to opposite spindle of right angle unit increases speed by 50% for small hole drilling giving it versatility for a number of applications.

RIGHT ANGLE DRIVE UNIT

Catalog No. 48-06-2870 For drills with non-reversing motors. Drill or chuck not included. Net Wgt. 2 lbs. Shp. Wgt. 3 lbs.

REVERSING RIGHT ANGLE DRIVE

Catalog No. 48-06-2871 For drills with reversing motors.

CHOICE OF THREE DRILLING SPEEDS

Catalog No.	RPM Drill Only	Drill With RAD Unit RPM Low Side	RPM High Side	O.S.H.A. Compliance
0800	2000	1330	3000	Yes
0801	1800	1200	2700	Yes
0805†	1800	1200	2700	
0850	1400	930	2100	Yes
0870	1000	665	1500	Yes
0871	1350	900	2025	Yes
0875†	1350	900	2025	
0890	850	570	1275	Yes
1000	560	375	840	Yes
1000-1 Rev.*	560	375	840	
1001	600	400	900	Yes
1001-1 Rev.*	600	400	900	
1100*	450	300	675	Yes
1100-1 Rev.*	450	300	675	
1101*	500	335	750	Yes
1101-1 Rev.*	500	335	750	
1105-1 Rev.*	550	365	825	Yes
1106-1 Rev.†*	500	335	750	Yes
1200*	320	215	480	Yes
1200-1 Rev.*	320	215	480	
1201*	350	230	525	Yes
1201-1 Rev.*	350	230	525	
1250-1 Rev.*	950	630	1425	Yes
1251-1 Rev.†*	950	630	1425	

†Double Insulated Tool

*Catalog No. 48-95-0400 Extension and Catalog No. 48-06-2860 33° Angle Drive is adaptable to these reversing and non-reversing drills.

Note: "Rev." following catalog no. indicates reversing motor.

NEW 33° ANGLE DRIVE KIT

Catalog No. 48-06-2860 Electricians and Plumbing Contractors can now stretch drilling reach up to 30 inches, plus adding 33° with Milwaukees new 33° Angle Drive Kit. This kit permits easy drilling of up to 2 9/16" dia. holes in ceiling joists for running conduit or pipe — eliminating need for ladders or scaffolding. Kit consists of an extension tube, side handle, drive shaft with hex sockets on both ends, two clamping collars and a 33° Angle Drive unit. See chart at right for proper drills to use with this kit. Use 33° Angle Drive with the 30" extension only. 33° angle units operate at the same speed as the drill powering them.



Catalog No. 48-95-0400 30" extension available separately for use with Milwaukee RAD units 48-06-2870 and 48-06-2871. Unit comes complete with 30" extension tube, drive shaft with hex socket on both ends and two clamping collars. Purchase RAD unit separately. See chart at right for proper drills to use with the extension.

HEAVY-DUTY Milwaukee 12 VOLT BATTERY POWERED TOOLS

V12 LINE

UNLIMITED 12 VOLT SOURCES

¼" and ⅜" PISTOL DRILLS

FOR 12 VOLT OPERATION ONLY

Designed for 12 volt operation and continuous heavy-duty use, these two In-Line Pistol Drills deliver top horsepower at maximum efficiency. The ¼" Drill has a no load speed of 1750 RPM and the ⅜" Drill, 600 RPM. Standard equipment includes Jacobs industrial, geared, key-type chuck and rubber-flex key holder. New weight 3¾ lbs. Shipping weight 6 lbs.

CAT. No. 0125 1/4" DRILL
CAT. No. 0225 3/8" DRILL

½" HOLE-SHOOTER

FOR 12 VOLT OPERATION ONLY

This 12 volt, 1/2" D-Handle Drill is ruggedly built for heavy-duty performance and for a wide variety of applications. The no load speed is 360 RPM. Standard equipment includes Jacobs industrial, geared, key-type chuck, rubber-flex key holder and adjustable side handle. Net weight 6¾ lbs. Shipping weight 10 lbs.

CAT. No. 1120

Type "A" Grease

½ lb. can **CAT. No. 49-08-0500**
1 lb. can **CAT. No. 49-08-0800**

6 FT. CORD with BATTERY CLIPS

Cat. No. 48-76-0060

For connecting V-12 tools to 12 volt batteries in motor vehicles, boats, mowers, etc. Two wire—10 gauge, oil resistant, yellow flexible cord with 2 battery clips and female connection.

25 FT. EXTENSION CORD

Cat. No. 48-76-0050

Can be used with these MILWAUKEE accessories: battery case, cord with battery clips or direct to transformer. Two wire—10 gauge, oil resistant, yellow flexible cord with male and female connections.

BELT BATTERY and CORD

For use with Pistol Drills only.

10 Volt Nickel-Cadmium Battery (less cord). **Catalog No. 48-11-0060**

12" Adapter Cord furnished separately. **Catalog No. 48-76-0090**

TRANSFORMER and BATTERY CHARGER

Cat. No. 48-55-0035



Converts 115V AC line voltage for Battery Powered Tools. Also recharges 12-volt batteries. Includes 6 foot cord for 115 line voltage and 2 foot 12 volt cord used between battery charger and outlet on battery carrying case. For charging other 12 volt batteries the 6 foot cord with battery clips is required.

CORDS FOR ABOVE when ordered separately
NO. 48-76-0080 6' for 115 v.
NO. 48-76-0070 2' for 12 v.

CADMIUM BATTERY CHARGER

For 10 Volt Battery. 14 hour fast charge and 30 hour slow charge. Plug into 115 Volt outlet and connect to battery. **Cat. No. 48-59-0050**

Accessories for Battery Powered Tools, such as Right Angle Unit, Selfeed Bits, Auger Bits, Flat Boring Bits, are the same as for 115 Volt tools.

BATTERY and CARRYING CASE

BATTERY
Cat. No. 48-11-0050

CARRYING CASE
Cat. No. 48-55-0040

The 12 volt storage battery has a rated capacity of 32 amp. hours. Can be recharged over 400 times. Battery carrying case is wired with outlet for plug-in connection and is used with MILWAUKEE or any 12 volt battery up to 5¼" wide, 7¾" high and 9" long.

When ordering tools without the MILWAUKEE Battery carrying case, the 6 foot cord with battery clips is required. Cat. No. 48-76-0060.

HEAVY-DUTY Milwaukee HOLE HAWGS

- **COMPACT DESIGN FOR DRILLING BETWEEN STUDS AND JOISTS**
- **POWER AND TORQUE TO HANDLE UP TO 4 5/8" SELFEED BITS**

The most advanced compact design for drilling between studs and joists with power and torque to handle up to 4 5/8" Selfeed bits in wood and 1/2" in steel. Only 6 3/8" from tip of chuck to back of gear case . . . 13 1/2" high and 4 5/8" wide. Two-speed delivers 1200 rpm for small holes and 300 rpm for larger holes. Single speed model operates at 900 rpm . . . moderate speed and high torque for small and medium holes . . . Ideal for electricians . . . Three position spade handle and two position pipe handle for good leverage in any position. A tough, glass-reinforced nylon handle offers high impact strength.

NEW SINGLE SPEED HOLE HAWG 900 RPM WITH REVERSING MOTOR

Capacities: Auger or Ship Auger Bit to 1 1/2" in wood. Selfeed Bits to 2 9/16" in wood. Up to 7/16" in steel.

TWO SPEED HOLE HAWG 1200 AND 300 RPM WITH REVERSING MOTOR

Capacities: Auger or Ship Auger Bit to 1 3/8" in wood. Selfeed Bits to 4 5/8" in wood. Up to 1/2" in steel.

ALL MODELS HAVE

3/4 H.P.

BALL AND ROLLER BEARINGS

WEIGH ONLY 10 1/2 LBS.



2-SPEED GEAR SHIFT
(Models 1675-1 Rev. and 1676-1 Rev.)
Extends the range of practical applications . . . 1200 rpm for smaller holes . . . 300 rpm for tough, big-hole boring.

3-POSITION SPADE HANDLE
For good leverage in any position.



EXTERNAL BRUSH CAPS
Brushes easily accessible from outside of tool for inspection or replacement.

TRIGGER SWITCH LOCK
For continuous operation.

TRIPLE REDUCTION GEARING
Hardened alloy steel gears provide powerful torque for toughest boring and drilling jobs.

2-POSITION PIPE HANDLE
Can be used on either side of motor housing for better control.

HEAVY-DUTY 3-JAW INDUSTRIAL GEARED CHUCK

KEYED ALUMINUM HOUSINGS
For perfect shaft alignment and true running.

HEAVY-DUTY 3/4 H.P. MOTOR
Rugged, dependable drilling power unmatched in any compact drill.

CYCLONIC AIR COOLING
Large fan directs air around every vital part for cool, efficient operation. Air exhausted through front vents and away from operator.

REVERSING SWITCH
Conveniently located beneath trigger switch for easy removal of cocked or jammed bits from work.

STEEL CARRYING CASE
(When ordered separately)
CATALOG NO. 48-55-0110

TYPE "C" GREASE
1 Pound Can
CATALOG NO. 49-08-1000

SINGLE AND TWO SPEED HOLE HAWG SPECIFICATIONS

Catalog Number	Speed	No Load RPM	Capacity in Wood	Capacity in Steel	Spindle Diameter and Thread	Gear Train	Net Wgt. Lbs.	Shp. Wgt. Lbs.	O.S.H.A. Compliance
1670-1 Rev.	High	900	1 1/2 Ⓐ & Ⓑ 2 9/16 Ⓒ	7/16"	5/8" — 16	Trpl.	10 1/2	16	Yes
1671-1 Rev.	Same as above but with steel carrying case							24	Yes
1675-1 Rev.	High	1200	1 1/8 Ⓐ 1 1/4 Ⓑ 1 3/8 Ⓒ	5/16"	5/8" — 16	Trpl.	10 1/2	16	Yes
	Low	300	1 1/2 Ⓐ & Ⓑ 4 5/8 Ⓒ	1/2"					
1676-1 Rev.	Same as above but with steel carrying case							24	Yes

Ⓐ Auger Ⓑ Ship Auger Ⓒ Selfeed Bit.

HEAVY-DUTY Milwaukee SUPER HOLE-SHOOTERS

Large Capacity Drills with Maximum Power for Continuous Performance

Ruggedly built and of simple functional design, these Milwaukee Hole-Shooters have the reserve power for the toughest drilling jobs. Gear drives are special helical-cut, chrome-nickel steel, heat treated to assure quiet performance and high torque with minimum wear. Drive shafts run smoothly on self-lubricating ball and roller bearings.

Ball and Roller Bearings

A

1/2" COMPACT HOLE-SHOOTERS

Compact, well balanced ½" production Drills deliver ⅔ horsepower at the chuck and are designed for constant use . . . ideal for hole saw drilling. Available in double or triple gear reduction. Pipe and spade handles removable. All ball bearings . . . Jacobs industrial key chucks . . . lockable trigger-switch.

SPECIFICATIONS

Unless otherwise specified all drills have Jacobs Industrial, geared, key-type chucks.

Group	Catalog No.	Cap. (In.) in Steel	Volts	Spindle Dia. and Thread	Speed rpm No Load	Gear Train	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
A	1600 1600-1 Rev.	½	115 115	½"-20 ⅝"-16	600	Dbl.	12¼	9½	13	Yes
	1620-1 Rev.	⅜ w/ ½ Chuck	115	⅝"-16	† 900	Dbl.	12¼	9½	13	Yes
	1650 1650-1 Rev.	½	115 115	½"-20 ⅝"-16	450	Trpl.	12¼	9½	13	Yes
B	1700 1700-1 Rev.	½	115 115	⅝"-16 #6J.T.*	600	Dbl.	16	14¾	19 21	Yes
	1750 1750-1 Rev.	⅝	115 115	⅝"-16 #3J.T.*	525	Trpl.	16½	15¾	20 22	Yes
	1850 1850-1 Rev.	¾	115 115	⅝"-16 #3J.T.*	400	Trpl.	16½	16¾	20 22	Yes
C	2400-1 Rev.▲	1¼	115	•	250	Trpl.	16¾	21½	26	Yes

"Rev." after Catalog No. indicates reversing type motor. * Jacobs Taper Spindle.
†For fast, deep hole drilling with auger bits • With No. 3 Internal Morse Taper Socket.
▲To adapt a 3/4" capacity chuck to 2400-1 Drill with No. 3 internal Morse Taper socket, specify Chuck No. 48-66-2000 and Arbor No. 48-07-0100.



B

SUPER HOLE-SHOOTERS CAPACITIES 1/2"-5/8"-3/4"

Perfectly balanced — mechanically and electrically. Built to handle a wide variety of drilling jobs. Smooth, powerful, double or triple reduction helical gearing. Spade and pipe handle removable. Furnished with heavy-duty industrial chuck.

C

1-1/4" CAPACITY SUPER HOLE-SHOOTER

MILWAUKEE'S largest and most powerful Drill. Extra long switch handle and pipe handle afford maximum leverage for drilling or reaming large holes. Triple reduction, helical gearing transmits tremendous torque. Furnished with No. 3 internal Morse Taper Socket.

Type "A" Grease

½ lb. can **Catalog No. 49-08-0500**
1 lb. can **Catalog No. 49-08-0800**

HEAVY-DUTY Milwaukee DRILL STANDS

CATALOG NO. 3540

FOR CAT. NO. 1700 and LARGER SHOWN ABOVE

FOR MILWAUKEE HOLE-SHOOTERS

Your Milwaukee Electric Drill clamps quickly into a Milwaukee Drill Stand to make a powerful and accurate drill press. It provides the leverage for steady, smooth feed. Wide opening between chuck and base accommodates bulky work. An adjustable vertical feed travel can be set for production work. Holes in base for bolting securely to bench.

SPECIFICATIONS

Catalog No.	3500	3520	3540
Height of Post	24"	29½"	36"
Max. Feed	3½"	3½"	5½"
Size of Base	8" x 8"	8" x 8"	10" x 10"
Chuck to Base—Max.	13"	16"	17½"
Chuck to Post	5¼"	6⅜"	6½"
Wgt. less Drill	21 lbs.	23 lbs.	33 lbs.
Ship. Weight	25 lbs.	25 lbs.	45 lbs.

CATALOG NO. 3520

FOR 1600 SERIES DRILLS LISTED AT TOP OF PAGE



CATALOG NO. 3500

FOR D-HANDLE DRILLS LISTED ON PAGE 5

HEAVY-DUTY Milwaukee DRILL ACCESSORIES

HIGHEST QUALITY FOR MAXIMUM EFFICIENCY

CHUCKS



JACOBS INDUSTRIAL CHUCKS Chuck Key included			CHUCK KEYS
Catalog No.	Cap.	Thread Size	Catalog No.
48-66-0260	1/4"	3/8"-24	48-66-3200
48-66-0300	1/4"	1/2"-20	48-66-3200
48-66-0500	5/16"	3/8"-24	48-66-3240
48-66-0540	5/16"	1/2"-20	48-66-3240
48-66-0800	3/8"	3/8"-24	48-66-3080
48-66-0840	3/8"	1/2"-20	48-66-3280
48-66-0880	3/8"	5/8"-16	48-66-3280
48-66-1280	1/2"	1/2"-20	48-66-3280
48-66-1440	1/2"	5/8"-16	48-66-3120
48-66-1640	5/8"	5/8"-16	48-66-3120
48-66-2040	3/4"	5/8"-16	48-66-3160
48-66-2050	3/4"	3/4"-16	48-66-3160
§ JACOBS CHUCKS for REVERSING DRILLS Chuck Key included			
48-66-0230•	1/4"	#1 Taper	48-66-3200
48-66-0240•	3/8"	#2 Taper	48-66-3080
48-66-1360	1/2"	1/2"-20	48-66-3280
48-66-1380	1/2"	5/8"-16	48-66-3280
48-66-1480	1/2"	#6 Taper	48-66-3120
48-66-1680	5/8"	#3 Taper	48-66-3120
48-66-2080	3/4"	#3 Taper	48-66-3160

§ Chucks for other drills with reversing motors . . . specify model and serial numbers.

• Chuck Removal Wedges required (Set of 2)
For 1/4" Drill — #1 Jacobs Taper
Catalog No. 49-91-0010
For 3/8" Drill — #2 Jacobs Taper
Catalog No. 49-91-0020

MORSE TAPER SOCKETS

★MORSE TAPER SOCKETS Drift Key included			DRIFT KEYS
49-66-0600	#2MT	5/8"-16	48-86-0050
49-66-0700	#3MT	5/8"-16	48-86-0070

★ See page 9 for sizes required for specific models.

EXTENSION CORDS

For all electric tools. Oil resistant, Heavy-Duty Neoprene cords with plugs molded on and with duplex connectors.

Catalog No.	Lgth.	Type	Ga.
48-76-0100	25'	SO	14
48-76-0110	50'	SO	14
48-76-0120	50'	SJO	16

See page 3 for recommended extension cord use.

CARBIDE-TIP MASONRY BITS

SPECIAL FEATURES

- **Alloy Steel Shank for Strength and Durability**
- **Shallow Precision Machined Oval Flutes Prevent Dust Packing**
- **Carbide Tip . . . The Hardest Metal Made . . . Brazed to Alloy Steel Bodies**

Drills masonry, brick, stone, plaster, slate. Wide, spiral flutes lift dust out of hole. Bit cuts at maximum efficiency without clogging. Produces clean, accurately sized holes fast. Carbide tip resists dulling. Bits may be resharpened on bench grinder using silicon carbide grinding wheel. Bits in sizes from 1" through 1 1/2" are of two piece design. Shank is 1/2" hex dia. with 1/2"-13 thread . . . nut serves as bit shoulder.

Black Oxide Finish

Dia.	Cat. No.	Shank Dia.	Overall Bit Length
1/8"	48-87-0120	1/8"	3"
5/32"	48-87-0150	5/32"	3"
11/64"	48-87-0170	11/64"	3"
3/16"	48-87-0180	3/16"	3"
7/32"	48-87-0210	1/4"	3"
1/4"	48-87-0250	1/4"	4"
9/32"	48-87-0280	1/4"	4"
5/16"	48-87-0310	1/4"	4"
3/8"	48-87-0370	1/4"	4"
7/16"	48-87-0430	1/4"	6"
1/2"	48-87-0500	3/8"	6"
9/16"	48-87-0560	1/2"	6"
5/8"	48-87-0620	1/2"	6"
11/16"	48-87-0680	1/2"	6"
3/4"	48-87-0750	1/2"	6"
7/8"	48-87-0870	1/2"	6"
1"	48-87-1000	1/2"	10"
1 1/8"	48-87-1120	1/2"	10"
1 1/4"	48-87-1250	1/2"	10"
1 1/2"	48-87-1500	1/2"	10"
EXTRA LENGTH BITS			
1/4"	48-87-0251	1/4"	12"
1/2"	48-87-0502	3/8"	18"
9/16"	48-87-0562	1/2"	18"
5/8"	48-87-0622	1/2"	18"
3/4"	48-87-0752	1/2"	18"
7/8"	48-87-0872	1/2"	18"

EXTRA LENGTH CARBIDE-TIP MASONRY BITS

Narrow Lands and Fast Spiral for Rapid Dust Removal

EXTENSION SHANKS

For Masonry Bits

1/2"-13 Thread

1/2" Hex Shank

For Two Piece Design Bits From 1" thru 1 1/2" Dia. Only

Length	Catalog No.
6"	48-28-8060
12"	48-28-8070
18"	48-28-8080
24"	48-28-8090
30"	48-28-8100
36"	48-28-8110

SCREWDRIVING ACCESSORIES

For Use With Trigger Speed Control Drills Nos. 0122-1 and 0222-1 (See Page 4)

Bit and Finder 3 1/2" long with 1/4" hex shank for slotted head screws

Screw Size	Catalog No.
6F-8R	48-30-2600
8F-10R	48-30-2625
10F-12R	48-30-2650
12F-14R	48-30-2675
14F-16R	48-30-2700

2" long Bits with 1/4" hex shanks for driving #2 and #3 Phillips screws

Size	Catalog No.
Phillips No. 2	48-30-1520
Phillips No. 3	48-30-1500

MISCELLANEOUS ACCESSORIES

LEATHER HOLSTER
FOR PISTOL DRILLS and SCREW-SHOOTERS
CATALOG NO. 49-17-0200

CARRYING CASE FOR PISTOL DRILLS and SCREW-SHOOTERS

OVERALL SIZE 13" long, 6" high, 8 1/2" wide

RUBBER-FLEX KEY HOLDERS

PLUG ADAPTER

Catalog No.	Description
48-55-0710	Carrying Case (See Above)
48-55-0110	Carrying Case For Hole Hawgs (1670-1 & 1675-1)
48-66-4040	Rubber-Flex Key Holders For Key 48-66-(3240-3080-3280)
48-66-4080	For Key 48-66-3200
48-03-0010	Plug Adapter

HEAVY-DUTY Milwaukee DRILL ACCESSORIES



SELFEED BITS

For big hole drilling in wood. For popular pipe sizes. Feed into work without pressure. 7/16" hex shanks have 3 milled flats for secure chuck grip. Side of bit tapered and beveled for easy removal from hole. Inside cutting plane shaves hole radius. Cuts clean, smooth holes. Sizes 1 3/4" and larger have reversible and replaceable double-end feed screw pilots.

Large SELFEED BITS in 3 5/8" and 4 5/8" sizes have double inside cutter blades and a larger double-end feed screw pilot. Arbors for these 2 sizes can be removed and replaced.

AUGER BITS

Sizes from 3/4" to 1 1/2" . . . All 4" twist and 6 1/2" long. 7/16" hex shanks for sure chuck grip. Precision made of special bit steel, heat treated and tempered for long life. Feed screw pilot draws bit into wood. Cutting spurs and lips stay sharp longer.

PLUMBERS' BIT KIT

A complete assortment of most commonly used MILWAUKEE Bits for BIG-HOLE drilling. Sizes include 7/8", 1 1/8", 1 1/4", 1 1/2" Auger Bits and the famous MILWAUKEE "Selfeed" Bits in 1 3/4", 2 1/8", and 2 9/16" diameters. Also 5 1/2" hex extension shank and coupling, extra double-end feed screw pilot, socket wrench and steel carrying case. Shipping Weight 8 1/2 lbs.

BIT KIT (complete) **Cat. No. 49-22-0060**
Carrying Case only **Cat. No. 48-55-0030**

SPECIFICATIONS

Catalog No.	Description	For Std. Pipe Sizes
SELFEED BITS		
48-25-1120	1 1/8" dia.	1/2"
48-25-1250	1 1/4" dia.	3/4"
48-25-1370	1 3/8" dia.	
48-25-1500	1 1/2" dia.	1"
48-25-1750	1 3/4" dia.	1"
48-25-2120	2 1/8" dia.	1 1/2"
48-25-2250	2 1/4" dia.	—
48-25-2560	2 9/16" dia.	2"
48-28-6850	Dble. Feed Screw Pilot	
49-96-0060	Socket Wrench	
LARGE SELFEED BITS		
48-25-3620	3 5/8" dia.	3" ★
48-25-4620	4 5/8" dia.	4" ★
48-07-0200	Replaceable Arbor	
48-28-6860	Dble. Feed Screw Pilot	
49-96-0070	Socket Wrench	

★ Cast Iron or Copper Pipe Size.

Catalog No.	Description	For Std. Pipe Sizes
AUGER BITS		
48-13-0750	3/4" x 4" Twist	
48-13-0870	7/8" x 4" Twist	3/8"
48-13-1000	1" x 4" Twist	
48-13-1120	1 1/8" x4" Twist	1/2"
48-13-1250	1 1/4" x 4" Twist	3/4"
48-13-1370	1 3/8" x 4" Twist	
48-13-1500	1 1/2" x 4" Twist	1"

EXTENSION SHANKS

For Selfeed Bits and Auger Bits (1" dia. and larger) with 7/16" hex shanks.

EXTENSION **COUPLING**

	Lgth.	Catalog No.
Require Coupling **48-28-0920**	5 1/2"	**48-28-3112**
	12"	**48-28-3115**
	18"	**48-28-3300**

ONE PIECE

No Coupling Required	18"	**48-28-3400**
	24"	**48-28-3500**

FLAT BORING BITS

3 Milled Flats for Secure Chuck Grip



1/4" to 1 1/2" Diameters

SPECIFICATIONS

Dia.	Catalog No.	Shank Dia.	Overall Length
1/4"	48-27-0251	3/16"	6 1/8"
5/16"	48-27-0311	3/16"	6 1/8"
3/8"	48-27-0371	1/4"	6 1/8"
7/16"	48-27-0441	1/4"	6 1/8"
1/2"	48-27-0501	1/4"	6 1/8"
9/16"	48-27-0561	1/4"	6 1/8"
5/8"	48-27-0621	1/4"	6 1/8"
11/16"	48-27-0681	1/4"	6 1/8"
3/4"	48-27-0751	1/4"	6 1/8"
13/16"	48-27-0811	1/4"	6 1/8"
7/8"	48-27-0871	1/4"	6 1/8"
15/16"	48-27-0941	1/4"	6 1/8"
1"	48-27-1001	1/4"	6 1/8"
1 1/8"	48-27-1121	1/4"	6 3/4"
1 1/4"	48-27-1251	1/4"	6 3/4"
1 3/8"	48-27-1371	1/4"	6 3/4"
1 1/2"	48-27-1501	1/4"	6 3/4"

Flat Boring Bits are precision made of high carbon steel for durability and long life. Bore clean holes fast at any angle in wood, plastic, plywood and formica. Drill point and cutting edges can be resharpened often.

FLAT BORING BIT KIT

Contains 6 popular size flat boring bits in heavy protective plastic. Assortment includes 3/8", 1/2", 5/8", 3/4", 7/8" and 1" sizes in pockets for orderly storage and easy size selection.

CATALOG NO. 49-22-0071

POWER SHIP AUGER BITS

A

13/32" SHANK 15" TWIST 18" OVERALL LENGTH

Cut overall cost per hole by using these accurately machined 13/32" shank ship auger bits. A tough fast-cutting shiphead plus precision hardened cutting edges require less frequent resharpening. For 3/8" D-Handle drills and larger, also fits hand braces.

B

1/2" SHANK 4" TWIST 6" OVERALL LENGTH

Low cost ship auger bits that can be used in 1/2" D-Handle drills and larger. Precision machined for smooth wobble free boring.

C

1/2" SHANK 15" TWIST 18" OVERALL LENGTH

For all types of construction. Accurately machined for tough deep hole boring in wood. Use with 1/2" Hole-Shooters or larger. Feed screw point, one cutting edge and side lip produce fast cutting.

	Dia.	Catalog No.
A	9/16"	48-13-0561
	5/8"	48-13-0621
	11/16"	48-13-0681
	3/4"	48-13-0751
	13/16"	48-13-0811
	7/8"	48-13-0871
	15/16"	48-13-0931
	1"	48-13-1001
B	11/16"	48-13-0683
	3/4"	48-13-0753
	13/16"	48-13-0813
	7/8"	48-13-0873
	15/16"	48-13-0933
	1"	48-13-1003
	1 1/16"	48-13-1063
	1 1/8"	48-13-1123
	1 1/4"	48-13-1253
	1 3/8"	48-13-1373
	1 1/2"	48-13-1503
C	9/16"	48-13-5560
	5/8"	48-13-5620
	11/16"	48-13-5680
	3/4"	48-13-5750
	13/16"	48-13-5810
	7/8"	48-13-5870
	15/16"	48-13-5930
	1"	48-13-6000
	1 1/16"	48-13-6010
	1 1/8"	48-13-6120
	1 1/4"	48-13-6250
	1 3/8"	48-13-6370
	1 1/2"	48-13-6500

HEAVY-DUTY Milwaukee HOLE SAWS

SHATTER-RESISTANT

MILWAUKEE Hole Saws are high production tools for sawing holes in all machineable materials. A most economical means of extending the useful range of portable drills, drill presses and lathes. High speed cutting edges welded to rigid steel bodies produce clean, accurate holes. Shatter-resistant construction makes them safe to use and provides an extra margin of durability.

9/16" to 6" Diameters

STANDARD

DEEP CUTTING

High Speed Steel Cutting Edges
6 Teeth Per Inch

DEEP CUTTING AND STANDARD TYPES

Deep cutting Hole Saws cut to 1¾" depth. Especially suited for cutting thru 2" dressed lumber.

Standard Hole Saws cut to 1¼" depth.

Arbor not included with Hole Saw

HOLE SAW ARBORS

1/4" ROUND SHANK

Catalog No. 49-56-6950

With ½"-20 thread and ¼" pilot drill. For small Hole Saws. (See Table.)

7/16" HEX. SHANK

Catalog No. 49-56-7000

With ½"-20 thread and ¼" pilot drill. For 9/16" to 1 3/16" Hole Saws. (See Table.)

QUICK CHANGE ARBORS

7/16" HEX. SHANK

Catalog No. 49-56-7055

With ⅝"-18 thread and ¼" pilot drill. For 1¼" and larger Hole Saws.

5/8" HEX. SHANK

Catalog No. 49-56-7100

With ⅝"-18 thread and ¼" pilot drill. Recommended for 4" and larger Hole Saws.

Arbors and Hole Saws are interchangeable with most other brands.

HOLE SAW KITS

STANDARD HOLE SAW KIT consists of ⅞", 1⅛", 1½", 1¾", 2", 2½" sizes; Arbors Nos. 49-56-(7000 and 7055) and steel case.
Catalog No. 49-22-4050

DEEP CUTTING HOLE SAW KIT consists of 1", 1¼", 1½", 1¾", 2¼", 3", 3⅜" sizes; Arbors Nos. 49-56-(7000 and 7055) and steel case.
Catalog No. 49-22-4060

STEEL CASE ONLY Used with either of above kits
Catalog No. 48-55-0760

ACCESSORIES

PILOT DRILLS

Catalog No. 49-56-8000

¼" High Speed Pilot Drill. For use with Hole Saw arbors.

Catalog No. 49-56-8002

¼" High Speed Pilot Drill with ¼" fluting for light gauge metals.

EXTENSION SHANKS

For 7/16" hex shank arbors . . . 1" dia. Hole Saws and larger.

COUPLING

EXTENSION

ONE PIECE

	Lgth.	Catalog No.
Require Coupling 48-28-0920	5½"	48-28-3112
	12"	48-28-3115
	18"	48-28-3300
No Coupling Required	18"	48-28-3400
	24"	48-28-3500

SPECIFICATIONS

Hole Dia. Size	Catalog No.	Use with Arbor No.	Pipe Sizes: Pipe Tap	Pipe Sizes: Pipe Entrance	For Copper Pipe Size (I.D.)
DEEP CUTTING Cut to 1¾" depth					
⅞"	49-56-0871	49-56-6950 or 49-56-7000		½"	⅝"
1"	49-56-1001				¾"
1⅛"	49-56-1121			¾"	¾"
1¼"	49-56-1251				1"
1⅜"	49-56-1371			1"	
1½"	49-56-1501				1¼"
1¾"	49-56-1751	49-56-7055 or 49-56-7100		1¼"	1½"
2"	49-56-2001			1½"	
2¼"	49-56-2251				2"
2½"	49-56-2501			2"	2"
3"	49-56-3001			2½"	2½"
3⅜"	49-56-3371				3"
4¼"	49-56-4251				4"
STANDARD Cut to 1¼" depth					
9/16"	49-56-0560	49-56-6950 or 49-56-7000			⅛"
⅝"	49-56-0620				¼"
11/16"	49-56-0680				⅜"
¾"	49-56-0750			⅜"	½"
13/16"	49-56-0810				½"
⅞"	49-56-0870		¾"	½"	⅝"
15/16"	49-56-0930				
1"	49-56-1000				¾"
1 1/16"	49-56-1060				
1⅛"	49-56-1120		1"	¾"	¾"
1 3/16"	49-56-1180				
1¼"	49-56-1250	49-56-7055 or 49-56-7100			1"
1 5/16"	49-56-1310				
1⅜"	49-56-1370			1"	
1 7/16"	49-56-1430				
1½"	49-56-1500		1¼"		1¼"
1 9/16"	49-56-1560				
1⅝"	49-56-1620				
1 11/16	49-56-1680				
1¾"	49-56-1750		1½"	1¼"	1½"
1 13/16"	49-56-1810				
1⅞"	49-56-1870				
2"	49-56-2000			1½"	
2 1/16"	49-56-2060				
2⅛"	49-56-2120				
2¼"	49-56-2250		2"		2"
2 5/16"	49-56-2310				
2⅜"	49-56-2370				
2½"	49-56-2500			2"	2"
2 9/16"	49-56-2560				
2⅝"	49-56-2620		2½"		
2¾"	49-56-2750				
2⅞"	49-56-2870				
3"	49-56-3000			2½"	2½"
3⅛"	49-56-3120				
3¼"	49-56-3250		3"		
3⅜"	49-56-3370				
3½"	49-56-3500				
3⅝"	49-56-3620			3"	
3¾"	49-56-3750		3½"		
3⅞"	49-56-3870				3½"
4"	49-56-4000				
4⅛"	49-56-4120			3½"	3½"
4¼"	49-56-4250		4"	3½"	4"
4⅜"	49-56-4370				
4½"	49-56-4500			4"	4"
4¾"	49-56-4750				
5"	49-56-5000				
5½"	49-56-5500				5"
6"	49-56-6000				

The comparative area of metal which must be cut away to make a 4½" dia. hole.

HEAVY-DUTY Milwaukee DRAIN CLEANER

WITH TRIGGER SPEED CONTROL AND REVERSING MOTOR

NEW 50 FT. DRUM CAPACITY
Holds Up to 35′ of 13/32″ Cable or 50′ of 5/16″ Inner Core Cable

Powerful unit cleans out hard-to-get-at sink and toilet installations with ease . . . eliminates removing traps or clean out plugs. Total speed control from 0 to 500 rpm lets operator start slowly to work past crossbars . . . then run at whatever speed is needed to get through goosenecks and "T's", to remove stoppage. Just squeeze the trigger for the exact speed required on any job. The further the trigger is depressed, the higher the rpm. Reversing motor enables operator to spin cable in either direction for breaking up stoppage, freeing jammed hooks. Large external drum holds up to 50 feet of inner-core drop head cable. Jacobs chuck grips cable firmly, opens easily for fast cable feed.

- **Powerful motor, specially designed for running cable**
- **Trigger Speed Control design protects cable from damage and permits safe operation from 0 to 500 R.P.M.**
- **Reversing motor makes cable extraction fast**
- **Large cable drum holds up to 50′ of inner-core drop head cable**
- **Quick, easy rodding of up to 2″ wastelines**

Catalog No. 0566-1 Kit Includes: 1/4″ x 25′ Steel Cable Cat. No. 48-53-0010, 5/16″ x 25′ Steel Cable Cat. No. 48-53-0015, 1/4″ Repair Hook Cat. No. 49-20-0020, 5/16″ Repair Hook Cat. No. 49-20-0040, Cable Guide Holder Cat. No. 49-17-0160, Cable Guide Cat. No. 49-13-0010 and Steel Carrying Case Cat. No. 48-55-6055.



Flexible steel cable follows plumbing bends and quickly removes rust, scale, grease, silt etc. No time wasted disconnecting fittings.

SPECIFICATIONS

115 Volts AC Only

Catalog No.	Speed rpm	Cable Size	Max. Cable Length	Max. Pipe Size I.D.	Length (inches)	Net Wgt. Lbs.	Shp. Wgt. Lbs.	O.S.H.A. Compliance
0566-1 Kit	0 to 500	1/4″ or 5/16″	50′	2″	17	9 1/4	36	Yes
		13/32″	35′					

STEEL CABLES

5/16″ x 25′ STEEL CABLE
Includes repair hook.
Cat. No. 48-53-0015

1/4″ x 25′ STEEL CABLE
Includes repair hook.
Cat. No. 48-53-0010

5/16″ x 30′ STEEL CABLE
Includes repair hook.
Cat. No. 48-53-0035

1/4″ x 30′ STEEL CABLE
Includes repair hook.
Cat. No. 48-53-0030

STEEL CABLE
Right-hand wound cable expands when torque is applied. Designed for feeding through crossbars, down through and around the goose neck, or traps, over to the "T" . . . down the "T", not up the vent. It eliminates removal of the trap or clean out plug.

INNER-CORE DROP HEAD CABLES

5/16″ x 25′ INNER-CORE DROP HEAD CABLE
Includes drop head, 3/4″ and 1″ cutter, Socket head screws and wrenches for changing heads.
Cat. No. 48-53-0020

5/16″ x 30′ INNER-CORE DROP HEAD CABLE
Includes drop head, 3/4″ and 1″ cutter, Socket head screws and wrenches for changing heads.
Cat. No. 48-53-0025

5/16″ x 50′ INNER CORE DROP HEAD CABLE
Includes drop head, 3/4″ and 1″ cutter, socket head screws and wrenches for changing heads.
Cat. No. 48-53-0040

13/32″ x 35′ INNER CORE DROP HEAD CABLE
Includes drop head, 1″ and 1-1/4″ cutter, socket head screws and wrenches for changing heads, extraction hook.
Cat. No. 48-53-0050

DROP HEAD PARTS KIT Cat. No. 49-22-2500
For 5/16″ Inner-Core Cable — includes Drop Head, set screw for drop head, Socket Wrench for drop head, 3/4″ cutter, 1″ cutter, set screws and Socket Wrench for cutters.

DROP HEAD PARTS KIT Cat. No. 49-22-2510
For 13/32″ Inner Core Cable — includes drop head, set screw for drop head, socket wrench for drop head, 1″ and 1-1/4″ cutter, set screws and wrench for cutters, extraction hook.

INNER-CORE DROP HEAD CABLE
Left-hand wound cable tightens against center core when torque is applied, making a solid shaft. Once through stoppage, tension on the cable is released, and it becomes flexible again.



A CABLE GUIDE
Cat. No. 49-13-0010

B CABLE GUIDE HOLDER
Cat. No. 49-17-0160

REPAIR HOOKS

For 1/4″ STEEL CABLE
Cat. No. 49-20-0020

For 5/16″ STEEL CABLE
Cat. No. 49-20-0040

REPAIR BULB

for 5/16″ Inner-Core Drop Head Cable
Cat. No. 48-50-0010

for 13/32″ Inner Core Drop Head Cable.
Cat. No. 48-50-0020

MISCELLANEOUS ACCESSORIES

JACOBS CHUCK WITH COLLET
Cat. No. 48-66-0270

Type "A" Grease
1/2 lb. can
Catalog No. 49-08-0500
1 lb. can
Catalog No. 49-08-0800

DROP HEAD ASSEMBLY

for 5/16″ Inner Core Drop Head Cable
Cat. No. 49-16-0010

for 13/32″ Inner Core Drop Head Cable.
Cat. No. 49-16-0020

CUTTERS

3/4″ CUTTER
for 5/16″ Inner Core Drop Head Cable
Cat. No. 48-38-0050

1″ CUTTER
for 5/16″ Inner Core Drop Head Cable
Cat. No. 48-38-0060

1″ CUTTER
for 13/32″ Inner Core Drop Head Cable.
Cat. No. 48-38-0070

1-1/4″ CUTTER
for 13/32″ Inner Core Drop Head Cable.
Cat. No. 48-38-0080

STEEL CARRYING CASE
Cat. No. 48-55-6055

HEAVY-DUTY Milwaukee DYMODRILL EQUIPMENT

for Diamond Core Drilling in Concrete • Tile • Masonry

Dependable, powerful, rugged tools for Contractors, Plumbers, Electricians, Erectors and Maintenance Men. The combination of MILWAUKEE VAC-U-RIG® or DYMORIG and DYMODRILLS assures easy, quiet, economical diamond core-drilling of smooth, accurate holes in reinforced concrete. Eliminates sleeving, vibration, spalling or patching. This equipment provides the most practical and efficient method of rigidly positioning DYMODRILLS for maximum on-the-job diamond-drilling performance. Readily portable, they set-up in a few minutes and are easily secured to the floor or wall for vertical or horizontal drilling. A selection of single and 2-speed DYMODRILLS is also available to meet specific diamond-drilling requirements. DYMODRILL Not Included With Rig. Order VAC-U-RIG, DYMORIG, DYMODRILL and DYMOBITS separately.

VAC-U-RIG® SHOWN WITH DYMODRILL and DYMOBIT



Net weight STAND with DYMODRILL 125 lbs.

VAC-U-RIG®

CATALOG No. 4110

115 volts AC only

For use with DYMODRILLS. Includes stand with wheels and jack screw, vacuum pump, vacuum reserve tank, 2 vacuum pads, ammeter, bubble level, base leveling screws, cradle for mounting drill motor, four spoke wheel feed control, hose and fittings. Overall height 45". Net weight 139 lbs. Shipping weight 160 lbs.

Less DYMODRILL and DYMOBIT

DYMORIG SHOWN WITH DYMODRILL and DYMOBIT

DYMORIG with DYMODRILL only 85 lbs.

DYMORIG

CATALOG No. 4100

115 volts AC only

For use with DYMODRILLS (see next page). Balanced ... easy wheel portability. Rack and pinion feed — 24" travel — Operator feels drilling action of bit — 3 spoke feed control for uniform drilling pressure — Rugged aluminum base — Rigid stability for accurate, clean holes. Two color range ammeter indicates proper pressure and drilling speed — Jack Screw at top for bracing support to ceiling — Hole in base for anchor mounting — Base Leveling Screws and Bubble Level at top of cradle provide accurate setup. Cradle and Drill can be removed to lighten for installing base and column. DYMORIG can be used with VAC-U-RIG Attachment Kit. See next page. Net Wt. 65 lbs. Shp. Wt. 74 lbs. Less DYMODRILL and DYMOBIT.

OUTSTANDING FEATURES

1. **AMMETER** Two color range indicates proper pressure and drilling speed . . . warns against motor overload.
2. **BUBBLE LEVEL** Mounted at top of cradle. Base leveling screws provide quick set-up for true drilling.
3. **ACCURATE MOUNTING** Precision machined keyway securely positions DYMODRILL on cradle of VAC-U-RIG close to drill spindle. Assures accurate drilling alignment, stability.
4. **RIGID CONSTRUCTION** Solid steel column and tubular steel stabilizers provide maximum support for unit.
5. **EASY PORTABILITY** 8" rubber wheels are mounted on welded steel base and are off-the-floor when Rig is in use.
6. **VACUUM PADS** 13" diameter pads are cast aluminum with sponge rubber inserts. Vacuum line disconnects provide quick, simple set-up.
7. **VACUUM PUMP** Heavy-duty pump develops 3000 lbs. holding force within two 13" diameter vacuum pads.
8. **VACUUM RESERVE TANK** Prevents water from entering vacuum pump. Maintains limited vacuum reserve in event of power failure.
9. **RACK and PINION FEED** 27" travel — 4 spoke wheel control for uniform pressure. Operator feels drilling action of DYMOBIT.
10. **JACK SCREW** Used with Telescoping Assembly (See page 15) when vacuum is not required. Rig can also be anchor mounted thru hole in base.

VAC-U-RIG® Less All Vacuum Components CAT. No. 4111

For use with DYMODRILLS. Includes stand with wheels, jack screw, base leveling screws, bubble level, cradle for mounting drill motor and four spoke wheel feed control. Without vacuum, stand can be mounted to floor or wall with an expansion anchor or braced from the ceiling with telescoping assembly by using the jack screw. Net Wt. 86 lbs. Shp. Wt. 104 lbs. Less DYMODRILL and DYMOBIT.

For DYMODRILL ACCESSORIES and Full Line of DYMOBITS See Following Pages 15 and 16

HEAVY-DUTY Milwaukee DYMODRILL EQUIPMENT

For VAC-U-RIG® and DYMORIG

SINGLE SPEED and 2-SPEED DYMODRILLS

DYMODRILLS are specially designed for use with MILWAUKEE diamond core drilling rigs. A single speed model is available for bit diameters most commonly used. Two speed models increase versatility for a larger range of bit capacities and have a shift lever on the motor housing to transfer drive gear from one position to another — low speed for larger bits and high speeds for smaller bits. Triple gear reduction and heavy-duty motor produce high torque and 2¼ HP at the spindle. All have heat-treated, helical-cut steel gears, ball and roller bearings, and shear pin at the spindle to protect gears and motor against overload.



SPECIFICATIONS

Spindle thread size all models 1¼"-7.

Capacity ranges listed on specific models are for maximum drilling efficiency. All models can also be used for other diameters. For 9" and 10" diameter holes, use Spacer with Key Catalog No. 49-67-0050 and low speed DYMODRILLS.

Catalog No.	Speed RPM	Volts	Suggested Drilling Capacity	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
Single Speed						
3940	500	**115 AC ONLY**	3" to 5"	20	25	Yes
Two Speed						
4030	375 750	**115 AC ONLY**	5" to 8" 2½" to 5"	24	32	Yes
4035	500 1000		3" to 5" 1¼" to 3"	24	32	Yes

Standard equipment includes built-in water swivel, 8 ft. length of ⅜" heavy-duty rubber water hose complete with fittings and water control valve, extra shear pins, also an open end wrench for removing bits.

SPACER with KEY

CATALOG No. 49-67-0050

Allows use of bits thru 10" diameter. Spacer 1" thick, fits between cradle of Rig and Drill. Four mounting screws included.

VAC-U-RIG® ATTACHMENT KITS

Complete vacuum assemblies consisting of two 13" diameter suction pads, cross-bar, vacuum pump assembly with switch, gauge, filter, vacuum reserve tank, air hose and fittings.



CATALOG No. 49-22-7050 for use only with Catalog No. 4100 DYMORIG. Converts to vacuum mounting. Net Wt. 65 lbs. Shp. Wt. 70 lbs.

CATALOG No. 49-22-7060 for use with stand only—Catalog No. 4111. Same as furnished as standard with VAC-U-RIG Catalog No. 4110. Net Wt. 59 lbs. Shp. Wt. 64 lbs.

VACUUM PUMP AC only CATALOG No. 49-50-0115

Heavy-duty 1/6 HP pump complete with vacuum gauge, air filter, switch and cord. Same as furnished with VAC-U-RIG. Net weight 25 lbs. Shipping weight 27 lbs.

VACUUM RESERVE TANK CATALOG No. 49-76-0060

Heavy-duty 3½ gallon tank with 2 male disconnects and hose assembly. Same as furnished with VAC-U-RIG. Shipping weight 9 lbs.

WATER COLLECTOR RING

CATALOG No. 48-70-0050

FOR BITS THRU 8" DIA.

For use where water flow from drilling operation must be trapped and drained. Dike-type collector ring holds water for fast disposal. Used with pump described below. Shp. Wt. 6 lbs.

WATER COLLECTOR PUMP

AC only CATALOG No. 49-50-0050

Small heavy-duty pump of balanced impeller design, driven by 115 volt enclosed motor. Pumps out excess trapped water — abrasive-proof and quiet running. Furnished with reinforced plastic flexible hose. Shp. Wt. 12 lbs.

TELESCOPING EXTENSION ASSEMBLY

CATALOG No. 48-95-1000

Braces unit between floor and ceiling for maximum rigidity. Fixed hole adjustments. Assembly adjusts to 14 foot ceilings. Fractional take up between fixed settings made with jack screw at top of DYMORIG. Shp. Wt. 33 lbs.

WATER TANK

CATALOG No. 49-76-0050

3½ gal. pressure type made of heavy gauge galvanized steel. For use where regular tap water supply is not available. Shp. Wt. 8 lbs.

MISCELLANEOUS

RUBBER WATER HOSE

CATALOG No. 49-18-0050

8' long ⅜" ID as furnished with all DYMODRILLS

3/16" SOCKET WRENCH

CATALOG No. 49-96-0085

For mounting DYMODRILLS to cradle of VAC-U-RIG.

1⅜" OPEN END WRENCH

CATALOG No 49-96-4700

for DYMODRILLS listed above.

GREASE

Type "A" for Single Speed Model

½ lb. can **CAT. No. 49-08-0500**

1 lb. can **CAT. No. 49-08-0800**

Type "C" for 2-speed Models

1 lb. can **CAT. No. 49-08-1000**



An 8" DYMOBIT cuts fast, clean and accurate using the VAC-U-RIG. Pump and Collector Ring disposes of water quickly. When drilling in corners a single pad can be used under center of base.



Drilling up close in tight corners is no problem. DYMORIG is braced to ceiling using telescoping assembly and jack screw at top of rig.

HEAVY-DUTY Milwaukee DYMOBITS and ACCESSORIES



FINEST QUALITY DIAMONDS

Only the highest quality industrial diamonds, carefully selected for uniformity and grade, are used in DYMOBITS. Special attention is given to position diamonds in the crown for a definite tracking pattern with best cutting edges exposed.

EXPANSION ADAPTERS FOR OPEN BACK DYMOBITS

Split ring expands against bit sleeve as threaded part of adapter is drawn up.

For use with bits 1¼" and larger. Self-centering, 3 piece friction drive — for easy positioning of bit sleeve and bit removal. Expansion adapters are reusable for new bits of the same size. By removing the sleeve from the adapter, an occasional lodged core can be removed from the back of the bit preventing damage to the crown.

SOLID BACK DYMOBITS

The welded adapter is an integral part of the Solid Back Bit. Precision machined and centered, the end of the adapter is threaded and milled flats are provided for easy removal of DYMOBIT from the spindle of Drill with open end wrench.

THREADED ADAPTER

CATALOG No. 48-04-0150

Reduces thread size of 1¼"-7 to ⅞"-14 or ½"-20 for DYMOBITS of 1¼", 1⅜" and 1½" diameter. Used on DYMODRILLS listed in table on page 15.

9" BIT EXTENSION

CATALOG No. 48-95-1500

For DYMOBITS of 1¾" diameter and larger. Both ends are threaded 1¼"-7. Two or more extensions can be coupled together for deeper hole drilling. Used on DYMODRILLS listed in table page 15.

10½" BIT EXTENSION

CATALOG No. 48-95-2000

Use with Threaded Adapter No. 48-04-0150 for Open Back DYMOBITS in sizes up to 1½" with ½"-20 threaded adapters, and Solid Back DYMOBITS in sizes 1¼" thru 1¾" with ⅞"-14 thread. Extension threads on ⅞"-14 spindle. Outer end is a two-stage spindle with ⅞"-14 and ½"-20 threads. Sizes 1" and smaller should not be used with this extension.

HARD AGGREGATE DIAMOND CORE BITS

DYMOBITS are designed to assure maximum cutting efficiency at minimum cost. Great concentration and orientation of the finest industrial diamonds set in a long wearing tungsten carbide matrix assures increased drilling footage even in extremely hard materials or heavily reinforced concrete. Drill bit tubes are precision machined and double cadmium plated.

4 TYPES AVAILABLE

GENERAL PURPOSE — OPEN and SOLID BACK For general core drilling in reinforced concrete, tile, masonry and marble. Diamonds are surface set in the matrix. Functionally designed waterways properly spaced in the matrix allow water to flush out cuttings, provide heat dissipation for long bit life.

RED CROWN — OPEN and SOLID BACK With diamond impregnated matrix for coring pre-stressed or reinforced concrete and other hard or highly abrasive materials. Diamond saturated matrix maintains uniform cutting efficiency for more footage, faster penetration and lower cost.

For Sizes Other Than Listed Contact Factory.

Nominal Bit Size O.D. ●	† Core Length ●	Open Back Bits Catalog No. Gen. Purpose / Red Crown	Expansion Adapter (Required) Catalog No.	★ Thread Size: Open Back Adapter	★ Thread Size: Solid Back Bit	Solid Back Bits Catalog No. Gen. Purpose / Red Crown
¼"	4"	(¼" Bit is non-coring type)				48-16-0250
5/16"	4"					48-16-0310
⅜"	4"	For DYMOBITS ¼" through 1" dia.			½"-20	48-16-0370
½"	4"	Refer to Solid Back Bits				48-16-0500
⅝"	12"	(Column at Right)				48-16-0620
¾"	12"					48-16-0750
⅞"	12"					48-16-0870
1"	12"					48-16-1000
1¼"	12"	48-16-1251	48-04-1250		⅞"-14	48-16-1252 / 48-16-1256
1⅜"	12"	48-16-1371	48-04-1370	½"-20 ▲	▲	48-16-1372
1½"	12"	48-16-1501 / 48-16-1510	48-04-1500			48-16-1502 / 48-16-1512
1¾"	12"	48-16-1751	48-04-1750	1¼"-7		48-16-1752
			48-04-1751	½"-20		
		48-16-1780	48-04-1750	1¼"-7		
			48-04-1751	½"-20		
2"	12"	48-16-2001	48-04-2000	1¼"-7		48-16-2002
			48-04-2001	½"-20		
		48-16-2010	48-04-2000	1¼"-7		48-16-2012
			48-04-2001	½"-20		
2¼"	12"	———	———	———		48-16-2253
2⅜"	12"	48-16-2371	48-04-2370	1¼"-7		48-16-2372
			48-04-2371	½"-20		
2½"	12"	48-16-2501	48-04-2500	1¼"-7		48-16-2502
			48-04-2501	½"-20		
		48-16-2510	48-04-2500	1¼"-7		48-16-2512
			48-04-2501	½"-20		
2¾"	12"	———	———	———		48-16-2752
3"	12"	48-16-3001 / 48-16-3010	48-04-3000		1¼"-7	48-16-3002 / 48-16-3012
3½"	12"	48-16-3501 / 48-16-3510	48-04-3500			48-16-3502
4"	12"	48-16-4001 / 48-16-4010	48-04-4000			48-16-4002 / 48-16-4012
4¼"	12"	48-16-4251	48-04-4250			48-16-4252
4½"	12"	48-16-4501	48-04-4500			48-16-4502
5"	12"	48-16-5001 / 48-16-5010	48-04-5000			48-16-5002 / 48-16-5012
6"	12"	48-16-6001 / 48-16-6010	48-04-6000	1¼"-7		48-16-6002 / 48-16-6012
6¼"	12"	48-16-6251	48-04-6250			48-16-6252
7"	12"	48-16-7000	48-04-7000			48-16-7001
8"	12"	48-16-8000	48-04-8000			48-16-8001
9"	12"	48-16-9000	48-04-9000			48-16-9001
10"	12"	48-16-9500	48-04-9500			48-16-9501
11"	12"					48-16-9550
12"	12"	For DYMOBITS 11" through 14" dia.				48-16-9600
13"	12"	Refer to Solid Back Bits				48-16-9650
14"	12"	(Column at Right)				48-16-9700

● Dimensions vary slightly from specified size.

† All bits ⅝" and larger will cut 12" concrete. Overall lengths vary depending on adapter type and diameter.

★ NOTE — Check thread size with spindle thread on Drill or refer to specifications for DYMODRILLS. It may be necessary to use a threaded Adapter to fit Drill spindle.

▲ When used with Drills with 1¼"-7 thread use Threaded Adapter Cat. No. 48-04-0150.

STRAP WRENCHES

To remove DYMOBIT. Available in two sizes.

CATALOG No. 49-96-8100 for bits up to 2" diameter.

CATALOG No. 49-96-8200 for bits from 2" to 8" dia.

HEAVY-DUTY Milwaukee ELECTROMAGNETIC DRILL PRESSES

¾" LATERAL MOVEMENT
20° LEFT OR RIGHT

DRILLING • TAPPING • REAMING ½", ¾", 1¼" CAPACITIES

FOR STEEL ERECTORS • BRIDGE BUILDERS • TOOL AND DIE SHOPS SHIPYARDS • MILLWRIGHTS • MAINTENANCE

• NEW adjustable unit permits ¾" lateral movement and 20° swivel, left or right. • Use on vertical, horizontal, and overhead applications. • NEW, safety color-coded control panel makes it necessary to push 2 buttons to turn off magnet. • NEW threaded receptacle from stand to drill motor prevents accidental pull out. • Stronger drill point pressures have been increased to 1300 lbs. on the small unit and to 2000 lbs. on the large and adjustable units. • NEW balanced design . . . will not tip forward when de-energized even with largest drill motor.

SINGLE SPEED OR 2-SPEED DRILLS

Single speed, MILWAUKEE-built Drills available in 1¼", ¾", and ½" capacities at speeds of 350, 400 and 450 RPM respectively. All models furnished with reversing motors . . . triple gear reduction for maximum torque . . . all ball and roller bearings. 2-Speed Drills have all the advantages of the single speed models plus greater versatility in speed and drilling power. One with speeds of 375 and 750 RPM . . . the other with speeds of 250 and 500 RPM. Low speed for large hole boring, tapping and reaming . . . high speed for small hole drilling.

NOTE: ALL SPECIFICATIONS SHOWN IN RED ARE FOR *NEW* MILWAUKEE ELECTRO-MAGNETIC DRILL STANDS AVAILABLE ONLY AFTER JULY 1, 1973.

ELECTRO-MAGNETIC DRILL STAND SPECIFICATIONS

Drill Stands and Drills are packaged and priced separately. When ordering, specify catalog numbers of both Drill Stand and Drill. Assembly of Drill to stand is easy. A single heavy-duty cord and plug supplies electrical power to stand and Drill. All Drill Presses are furnished with safety chain . . . a precaution against operator losing control of unit while positioning vertically, overhead, or from possible power failure.

11" Drill Travel on bases 4221, 4231, 4210, 4220, and 4230. 9" Drill Travel on bases 4201 and 4200.

115 VOLT UNITS AC ONLY ALL DRILLS ARE REVERSING

Stand Cat. No.	Drill Cat. No.	Capacity: Drill	Capacity: Tap†	Chuck or Taper	No Load RPM	Drill Stand Dimensions: HT.	Drill Stand Dimensions: W.	Drill Stand Dimensions: L.	▲Drill Point Pressure Lbs.	Net Wgt. Stand Only Lbs.	Comb. Net Wgt. Stand and Drill Lbs.	O.S.H.A. Compliance
4201 MED. RECT. BASE	4252-1•	½"	½"-20	Chuck	450						47	Yes
	4262-1	¾"	¾"-16	Chuck	400						60	Yes
	4282-1•	1¼"	¾"-16	No. 3MT	350	15"	4¼"	11"	1300	41	59	Yes
	4292-1*	1¼"	¾"-16	No. 3MT	750-375						63	Yes
	4297-1*	1¼"	¾"-16	No. 3MT	500-250						63	Yes
4221 LARGE RECT. BASE	4262-1	¾"	¾"-16	Chuck	400						77	Yes
	4282-1•	1¼"	¾"-16	No. 3MT	350	17¼"	5¼"	14"	2000	58	76	Yes
	4292-1*	1¼"	¾"-16	No. 3MT	750-375						80	Yes
	4297-1*	1¼"	¾"-16	No. 3MT	500-250						80	Yes
4231 LARGE ADJ. BASE	4262-1	¾"	¾"-16	Chuck	400						79	Yes
	4282-1•	1¼"	¾"-16	No. 3MT	350	17¼"	5¼"	14"	2000	60	78	Yes
	4292-1*	1¼"	¾"-16	No. 3MT	750-375						82	Yes
	4297-1*	1¼"	¾"-16	No. 3MT	500-250						82	Yes
4200 SMALL	4250-1•	½"	½"-20	Chuck	450	13¾"	4¼"	9⅛"	900	41	47	Yes
4210 MED. RECT. BASE	4260-1	¾"	¾"-16	Chuck	400	17½"	4"	13⅜"	1100	51	70	Yes
	4280-1•	1¼"		No. 3MT	350						69	Yes
	4290-1*	1¼"		No. 3MT	750-375						73	Yes
	4295-1*	1¼"		No. 3MT	500-250						73	Yes
4220 LARGE RECT. BASE	4260-1	¾"	¾"-16	Chuck	400	17⅞"	5"	13½"	1700	66	85	Yes
	4280-1•	1¼"		No. 3MT	350						84	Yes
	4290-1*	1¼"		No. 3MT	750-375						88	Yes
	4295-1*	1¼"		No. 3MT	500-250						88	Yes
4230 ROUND BASE	4260-1	¾"	¾"-16	Chuck	400	19⅜"	7⅝"	13¾"	1700	67	85	Yes
	4280-1•	1¼"		No. 3MT	350						85	Yes
	4290-1*	1¼"		No. 3MT	750-375						88	Yes
	4295-1*	1¼"		No. 3MT	500-250						88	Yes

* 2-speed drills. ▲ Maximum Pull on 1" Steel Plate, less on thinner sheets.

• Drills except Nos. 4250-1, 4252-1, 4280-1, and 4282-1 have dual mount gear case permitting reverse mounting of drill for close-quarter work.

† Maximum tapping capacity is dependent upon variable conditions prevailing, such as material, condition of tap, pitch, type cutting fluid, etc.

NOTE . . . To adapt a ¾" capacity chuck to 1¼" Drills with No. 3 internal Morse Taper Socket, specify Chuck No. 48-66-2000 and Arbor No. 48-07-0100.

CONVERSION KITS are available to convert previous drill motor models to work with the new Magnetic Bases. Conversion kits designed to adapt the new drill motor models to the old style stands are also available. See your Milwaukee Service Station for complete information.

6' LENGTH SAFETY CHAIN
Same as furnished with unit. (When ordered separately)
Catalog No. 48-58-0080

Type "A" Grease for Single Speed
½ lb. can Cat. No. 49-08-0500
1 lb. can Cat. No. 49-08-0800
Type "C" Grease for Two Speed
1 lb. can Cat. No. 49-08-1000

HEAVY-DUTY Milwaukee VACUUM CLEANERS

FOR MAXIMUM HEAVY-DUTY CLEANING APPLICATIONS

9 GALLON CAPACITY

Red Enameled Steel Wet or Dry Pick-Up

Catalog No. 8911

Powerful, two-stage bypass motor delivers 17,500 rpm with 16″ dia. red enameled 22 ga. steel tank. Ideal for fast clean-up of office carpets, quick drying of tile floors and many other heavy industrial and construction uses.

9 GALLON CAPACITY

Stainless Steel Wet or Dry Pick-Up

Catalog No. 8916

Deluxe non-corrosive 16″ dia. stainless steel tank assures maximum life. Powerful, two-stage bypass motor delivers 17,500 rpm. Ideal for jobs requiring extensive wet pick-up. Rapid-Flow Drain Valve allows complete drainage without tipping tank.

1½ BUSHEL CAPACITY

Red Enameled Steel Dry Pick-Up Only

Catalog No. 8921

High output straight-thru motor provides maximum power. Easily picks up fine sawdust, machine shop debris and sharp metal cuttings. 16″ dia. 22 ga. steel tank perfect for furnace cleaning and other uses requiring pick-up of fine dust.

NEW

15 GALLON CAPACITY

Stainless Steel Wet or Dry Pick-Up

Catalog No. 8925

A new high-power vacuum cleaner for extensive wet pickup application. 105″ of waterlift and 110 cu. ft. per min. air flow teamed with 15 gallon stainless tank. The powerful two-stage by-pass motor delivers 17,500 RPM. A Rapid Flow Drain allows complete drainage of tank without tipping.

½ BUSHEL CAPACITY

Red Enameled Steel Dry Pick-Up Only

Catalog No. 8931

Compact 14″ dia. 22 ga. steel tank with high output straight-thru motor for maximum power. Easily picks up fine sawdust, machine shop debris and sharp metal cuttings.

4½ GALLON or ¾ BUSHEL CAPACITY

Red Enameled Steel Wet or Dry Pick-Up

Catalog No. 8935

Powerful, two-stage bypass motor delivers 17,500 rpm. High capacity 14″ dia. red enameled 22 ga. tank. An ideal rental unit designed for fast clean-up of office/home carpets, quick drying of tile floors and other heavy-duty applications.

MILWAUKEE vacuum cleaners pick up debris from concrete, tile, hardwood or carpet-covered surfaces indoors or outdoors and are ideal for furnace cleaning or vacuuming water and cuttings from diamond core drilling. These vacuum cleaners are designed to service industrial, maintenance, construction and automotive users.

GENERAL SPECIFICATIONS

All models are equipped with 1½″ O.D. hose connections, cord with 3-prong grounded plug, accessory outlet receptacle on motor housing, 3 spring vinyl covered hold-down clamps and 4-wheel caddie with non-marring wheels.

SPECIFICATIONS

115 Volts AC Only

Cat. No.	For Materials	Recov. Cap.		Tank	Max. Air Flow Cu. Ft./Min.	Sealed Suction In. Water	Overall Dimensions		Net Wgt. (lbs.)	Shp. Wgt. (lbs.)	O.S.H.A. Compliance
		Gal.	Bu.				Width	Height			
8911	Wet or Dry	9	1½	Steel	92	85″	19″	32″	48	67	Yes
8916	Wet or Dry	9	1½	Stainless	92	85″	19″	32″	47	65	Yes
8921	Dry Only	—	1½	Steel	95	87″	19″	32″	42	59	Yes
8925	Wet or Dry	15	2	Stainless	110	105″	19″	36″	53	73	Yes
8931	Dry Only	—	½	Steel	95	87″	17″	25″	29	36	Yes
8935	Wet or Dry	4½	¾	Steel	92	85″	17″	28″	35	45	Yes

STANDARD EQUIPMENT

FOR MODELS 8911, 8916 AND 8925-3 paper filter bags, cloth filter, gasket and wire frame assembly, wet pick-up conversion pan, swivel connector and canvas store-all tool bag.

FOR MODEL 8921-3 paper filter bags, cloth filter, gasket, wire frame assembly and swivel connector. Canvas store-all tool bag.

FOR MODEL 8931-3 paper filter bags, cloth filter, gasket, wire frame assembly, swivel connector, and hose carrier.

FOR MODEL 8935-3 paper filter bags, wet pick-up pan, cloth filter, gasket, wire frame assembly, swivel connector, and wire hose carrier.

OUTSTANDING FEATURES

- POSITIVE WATER SHUT-OFF — On wet/dry machines protects motor from direct exposure to water.
- HEAVY-DUTY FILTER SYSTEM — For the roughest coarse materials to the finest dust.
- USE AS BLOWER — Switch hose from intake to exhaust, 90 cubic feet of air per minute can be directed for cleaning inaccessible areas.

VACUUM MOTOR DESIGN

Centrifugal blower produces high efficient vacuum and air flow. Models 8911, 8916, 8925, 8935, 8940, and 8945 have a two-stage bypass motor for wet/dry operation. It provides discharge of vacuum air from the fan case with a separate system for motor cooling. Clean air is drawn into top of motor and discharged through motor housing vents protecting motor from direct exposure to moisture.

Models 8921 and 8931 have a straight-thru motor for dry pick-up. Filters remove dirt from air before reaching the motor. Filtered air is drawn from tank and directed over electrical motor parts for cool efficient operation.

HEAVY-DUTY Milwaukee VACUUM CLEANER ACCESSORIES

FOR CURRENT MODELS ON PAGE 18
ALSO FOR PREVIOUS MODELS 8910, 8915, AND 8930

MOTOR HEAD AND DRUM ADAPTER ASSEMBLY

① MOTOR HEAD ONLY

Catalog No. 8940

The same powerful Motor Head as furnished with Models 8911 and 8916 with 30′ of cord. Requires use of 16″ dia. Conversion Pan for wet pickup. Wire Frame Filter Cage, Cloth Filter and Gasket assembly and 16″ Dacron Filter Bag required for dry pickup. Order these and all other accessories separately. Net Weight 14 lbs., Shipping Weight 16 lbs.

MOTOR HEAD ONLY **Catalog No. 8945**

New *more powerful* motor head adapts to all 16″ diameter, 9 gallon units and larger for extra-duty applications. Same as furnished with model 8925. Maximum air flow is 110 Cu. Ft./Min. with sealed suction water lift of 105″. Unit comes with a 30′ cord and requires the use of 16″ diameter conversion pan for wet pickup. Wire frame filter cage, cloth filter, and gasket assembly and 16″ dacron filter bag required for dry pickup. Order these and all accessories separately. Unit includes a swivel end connector. Catalog No. 49-90-0150. New Wgt. 15 lbs., Shipping Wgt. 17 lbs.

NEW

② DRUM ADAPTER

Catalog No. 49-90-1590

Fits your 55 Gal. drum. Gasket secures tightly to drum when vacuum is in operation. Adaptable to Motor Head 8940 and 8945 and those on Nos. 8911, 8916, 8921, and 8925. Use 16″ dia. accessories. Net Weight 10 lbs., Shipping Weight 11 lbs.

③ DOLLY

Catalog No. 49-90-1100

For 55 gal. drum. Sturdy steel construction with 4 wheels and long hinged handle. Drum easily tips off or on. Net Weight 43 lbs., Shipping Weight 45 lbs.

WIRE FRAME FILTER CAGE, CLOTH FILTER AND GASKET ASSEMBLY

Available for both 14″ and 16″ dia. tanks. The filter assembly acts as a final filter for air leaving tank. To achieve the best possible results, the cloth filter gasket and wire frame must be maintained. Any wear holes or gasket leaks will allow dust and debris to blow through exhaust ports.

Wire Frame Filter Cage 14″ Dia.
Cat. No. 49-90-0290

Wire Frame Filter Cage 16″ Dia.
Cat. No. 49-90-0270

Cloth Filter and Gasket 14″ Dia.
Cat. No. 49-90-0280

Cloth Filter and Gasket 16″ Dia.
Cat. No. 49-90-0260

DACRON FILTER BAG

Cat. No. 49-90-0320

Fits 14″ and 16″ dia. tanks. The dacron bag is suited for pick-up of medium fine dust as well as coarse sharp material. To be used without paper filter bags. Fits over cloth filter assembly.

WET PICK-UP CONVERSION PANS

Catalog No. 49-90-1620

Wet Pick-Up Conversion Pan 14″ Dia.
(Standard on Model 8935 Only)

Catalog No. 49-90-1610

Wet Pick-Up Conversion Pan 16″ Dia.
(Standard on Models 8911, 8916 and 8925)

Converts model 8911, 8916, 8925, 8940, and 8945 for wet pickup. Built-in float allows waste to reach a safe level, then stops suction, preventing motor damage. Available as a replacement unit.

DISPOSABLE PAPER FILTER BAGS

Flame-resistant paper filter bags make tank clean-out as easy as possible. Quick, easy installation gets machine going again fast.

14″ Dia. Vacuum Cleaner (5 Pack)
Cat. No. 49-90-0311

16″ Dia. Vacuum Cleaner (5 Pack)
Cat. No. 49-90-0301

16″ Dia. Vacuum Cleaner (5 Pack)
for use with 8925 ONLY.
Cat. No. 49-90-0350

MAJOR FLOOR TOOL

Major Floor Tool with two "quick turn" thumb screws for quick tool changing. Accommodates interchangeable 14″ inserts and replacements. Supplied with 49-90-0610 bumper.

Cat. No. 49-90-0550

DOUBLE BEND FLOOR ROD

Cat. No. 49-90-1000

Built-in swivel connection adapts to 1½″ ID hose, with compression fitting that accommodates all floor tools. Made of chrome-plated steel.

REPLACEMENT BUMPER FOR MAJOR FLOOR TOOL

Cat. No. 49-90-0610

BRISTLE SHOD SHOE

For Major Floor Tool. For rough floors, large wall and ceiling areas.

Cat. No. 49-90-0560

REPLACEMENT BRUSH STRIPS (2)

Cat. No. 49-90-0630

SQUEEGEE SHOE

Use with Major Floor Tool. For fast drying of washed floors.

Cat. No. 49-90-0580

REPLACEMENT SQUEEGEE BLADES (4)

Cat. No. 49-90-0640

14″ CARPET INSERT

For Major Floor Tool. Bottom plate perfectly designed for cleaning rugs, carpeting.

Cat. No. 49-90-0600

FABRIC SHOD ATTACHMENT SHOE

Use with Major Floor Tool. Suited for cleaning cement and concrete floors.

Cat. No. 49-90-0570

REPLACEMENT FABRIC STRIPS (2)

Cat. No. 49-90-0620

FELT SHOD ATTACHMENT SHOE

Use with Major Floor Tool for walls and smooth hard floors such as tile, hardwood.

Cat. No. 49-90-0590

REPLACEMENT FELT BLADES (2)

Cat. No. 49-90-0650

HEAVY-DUTY Milwaukee VACUUM CLEANER ACCESSORIES

FOR CURRENT MODELS ON PAGE 18
ALSO FOR PREVIOUS MODELS 8910, 8915, AND 8930

15" CREVICE TOOL

Cat. No. 49-90-0400

27" CREVICE TOOL

For cleaning behind radiators, other hard to reach corners and crevices.

Cat. No. 49-90-0410

RUBBER BLOWER NOZZLE

For blowing dust and dirt out of cracks and inaccessible areas. Excellent for machinery.

Cat. No. 49-90-0460

20" EXTENSION

20" extension with built-in hose end swivel. Used with utility nozzle (49-90-0740) for automotive cleaning. Also desirable when short extension is needed for dust brush attachments (49-90-0730).

Cat. No. 49-90-0510

WIDE MOUTH GULPER



Cat. No. 49-90-0540

Ideal for use on bare floors or rugs. 12" cleaning path. Compression Type, fits on Double Bend Floor Rod No. 49-90-1000.

HORSE HAIR BRUSH

Cat. No. 49-90-0750

Heavy-duty cast aluminum, wide mouth nozzle with plastic bumper. 10" cleaning path. Compression Type, fits on Double Bend Floor Rod No. 49-90-1000.

NYLON BRISTLE BRUSH

Cat. No. 49-90-0760

Heavy-duty cast aluminum, wide mouth nozzle with plastic bumper. 10" cleaning path. Compression Type, fits on Double Bend Floor Rod No. 49-90-1000.

REPLACEMENT PLASTIC BUMPER

Replacement for horse hair and nylon bristle brushes.

Cat. No. 49-90-0720

HORSE HAIR BRUSH INSERT REPLACEMENT

Cat. No. 49-90-0700

NYLON BRUSH INSERT REPLACEMENT

Cat. No. 49-90-0710

UTILITY NOZZLE

Cat. No. 49-90-0740
Taper fit utility and upholstery nozzle. Fits 1 ½" ID hose. 6" cleaning path.

CLAMP-ON NYLON BRISTLE BRUSH WITH BUMPER

Cat. No. 49-90-0480
Attach directly to utility nozzle.

REPLACEMENT NYLON BRISTLE BRUSH INSERT

Cat. No. 49-90-0680
For nylon bristle brush with bumper No. 49-90-0480.

REPLACEMENT BUMPER

Cat. No. 49-90-0690
For nylon bristle brush.

3" ROUND DUST BRUSH

Cat. No. 49-90-0730
3" round dust brush with nylon bristles and bumper. Fits 1 ½" ID hose.

REPLACEMENT BRUSH INSERT

Cat. No. 49-90-0660
Replacement for round dust brush.

REPLACEMENT BUMPER

Cat. No. 49-90-0670
For round dust brush.

WHITE CANVAS HOSE 10'

NO. 49-90-0020
Canvas covered, wire reinforced, rubber lined vacuum hose, 1 ½" ID. Two straight molded cuff ends. Order swivel-end connector separately.*

BLACK CANVAS HOSE 10'

NO. 49-90-0030
Canvas covered, wire reinforced, rubber lined vacuum hose. Strong resilient, 1 ½" ID with two straight molded cuff ends. Order swivel-end connector separately.*

WIRELESS VINYL HOSE

NO. 49-90-0060 10'
NO. 49-90-0070 25'
Crushproof multi-flex hose with no wire reinforcement. 1 ½" ID with two molded cuff ends. Order swivel-end connector separately.*

STEEL HOSE CONNECTOR

NO. 49-90-0195
Used to connect 1 ½" hoses.



HOSE CARRIER

Ideal for neat safe storage of vacuum hoses. Makes moving from one location to another easier.

FOR 14" TANKS
NO. 49-90-0170
FOR 16" TANKS
NO. 49-90-0180

BLACK NEOPRENE HOSE

NO. 49-90-0040 15'
NO. 49-90-0050 25'
Neoprene lined, oil resistant, wire reinforced, 1 ½" ID with two straight molded cuff ends. Order swivel-end connector separately.*

METAL HOSE 6'

NO. 49-90-0080

For cleaning boiler tubes and furnaces. 1 ¼" O.D. fits into standard 1 ½" ID hoses.

SWIVEL-END CONNECTOR

NO. 49-90-0150
Quick connect/disconnect feature makes attaching hoses to MILWAUKEE vacuum cleaners easy. Fits into 1 ½" ID hoses. Same as furnished with each unit.



CANVAS STORE-ALL TOOL POUCH

For Models 8911, 8916 and 8921
NO. 49-90-0250
Strong durable vinyl covered canvas pouch... makes toting extra tools easy.

*One swivel-end connector is furnished as standard equipment with vacuum cleaners 8911, 8916, 8921, 8925, 8931 and 8935 and motor heads 8940 and 8945.

HEAVY-DUTY Milwaukee 3/4" ELECTRIC HAMMER

for Contractors • Industry • Maintenance • Installation

For drilling holes in concrete and masonry for conduit, anchors and expansion shields • Chipping • Channeling • Scaling Chiseling and Tuck Pointing

Handles a wide range of Star Drills, Tooth Anchors, Chisels and Bull Point. Lightweight, perfect working balance and ruggedly built for continuous use with the right combination of power, speed and durability. Hammer blow is forward only with a patented cushioned recoil mechanism to eliminate jolting action — This mechanism has been preferred and proven for over 45 years.

Catalog No. 5361 with Glass Reinforced Nylon Handle

HARD HITTING HAMMER
3000 BLOWS PER MINUTE

Engineered for best performance, highest efficiency, dependability and long life.

Catalog No. 5360 and 5361*Electric Hammer Kit. LIMITED SET — includes 3/4" Electric Hammer, with star drill chuck, 1/2" star drill, drift pin, tool retaining spring, grease gun, grease, and steel carrying case.

Catalog No. 5380 and 5382*Electric Hammer Kit. Includes 3/4" Electric Hammer with star drill chuck, drift pin, tool retaining spring for chisels, one each bull point, cold chisel, brick cleaning chisel and mortar cutting chisel, eight assorted star drills 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", 3/4", and 7/8" sizes, grease gun, grease and steel carrying case.

SPECIFICATIONS

Catalog No.	Kit (See above)	Blows Per Min.	Volts	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
5360	Limited	3000	115	26	Yes
5361*	Limited			26	Yes
5380	Complete			30	Yes
5382*	Complete			30	Yes

*Equipped with New Glass Reinforced Nylon Handle

Efficient Operating Limit (Dia.) ..... 11/64" to 7/8"
Maximum Operating Dia. ..... 1 1/8"
Length overall (tool only) ..... 17 1/4"
Red Handle Tool Length ..... 18"

CONVERSION KIT

Catalog No. 48-62-0200 Additional accessories required to convert No. 5360 and 5361 Limited Kits to No. 5380 and 5382 Complete Kits.

Milwaukee 3/4" Electric Hammer shown removing brick on remodeling job is also ideal for setting self-drilling anchors on installation and maintenance work using Tooth Anchor Chucks.

OUTSTANDING FEATURES

RUGGED CAM ACTION

Simple, direct spring and cam action results in long life without loss of efficiency. "Ampco" aluminum bronze hammer cylinder withstands and absorbs powerful impact.





PERFECT BALANCE

Straight "In-Line" Hammer design provides perfect balance for ease in handling in any position and in close quarters. The weight is evenly distributed.

ACCESSORIES


Chucks for Star Drills Tooth Anchors

Brick Cleaning Chisel

Mortar Cutting Chisel

Retaining Spring

Star Drills

Bull Point


Chisels

Grease Gun & Grease

Catalog No.	Description
STAR DRILLS and CHUCK	
48-88-0251	1/4" x 6"
48-88-0252	1/4" x 12"
48-88-0310	5/16" x 6"
48-88-0311	5/16" x 12"
48-88-0370	3/8" x 6"
48-88-0371	3/8" x 12"
48-88-0430	7/16" x 6"
48-88-0500	1/2" x 6"
48-88-0501	1/2" x 12"
48-88-0620	5/8" x 6"
48-88-0621	5/8" x 12"
48-88-0750	3/4" x 6"
48-88-0751	3/4" x 12"
48-88-0870	7/8" x 6"
48-88-0871	7/8" x 12"
48-88-1000	1" x 6"
48-88-1001	1" x 12"
48-88-1120	1 1/8" x 6"
48-66-5010	Star Drill Chuck ★
BULL POINT	
48-62-0060	5/8" x 12"

Catalog No.	Description
CHISELS	
48-62-0070	5/8" x 7" Cold Chisel
48-62-0050	5/8" x 12" Cold Chisel
48-62-0080	Brick Cleaning Chisel
48-62-0090	Mortar Cutting Chisel
TOOTH ANCHOR CHUCKS	
48-66-5100	FOR BOLT SIZE 1/4", 5/16", 3/8", 1/2", 5/8" — O.D. OF ANCHOR 7/16", 15/32", 9/16", 11/16", 27/32"
48-66-5160	
48-66-5140	
48-66-5080	
48-66-5180	
MISCELLANEOUS	
48-55-0570	Carrying Case
49-08-0500	1/2 Lb. Can "A" Grease } FOR GEARS
49-08-0800	1 Lb. Can "A" Grease } FOR GEARS
49-08-0600	1/2 Lb. Can "B" Grease } FOR MECHANISM
49-08-0900	1 Lb. Can "B" Grease } FOR MECHANISM
49-14-0200	Grease Gun
49-68-0020	Tool Retaining Spring
48-86-0090	Drift Pin

★ Drift Pin Catalog No. 48-86-0090 included with each chuck.

HEAVY-DUTY Milwaukee HAMMER-DRILLS

Ball and Roller Bearings

SINGLE SPEED 2500 RPM

TRIGGER SPEED CONTROL 0 TO 2500 RPM

Available In Kit Form With Steel Carrying Case

Designed for Fast Percussion Drilling in Concrete or Masonry and High Speed Drilling Without Hammering in Wood or Metal.

For contractors, erectors, installation and maintenance men. Light weight, only 4½ lbs. . . . easy to handle. Powerful motor with high velocity fan cooling. Heat treated and hardened shafts. Wide, precision helical-cut gears. When hammer-drilling, light pressure against work engages mechanism. Hammer action stops when not under load . . . prevents damage when idling. All mechanism parts are case hardened for long life. Rubber dust shield protects against harmful abrasive dust. Adjustable depth gauge and removable side handle. Trigger lock-button for continuous operation.

EXCLUSIVE

Simple, slide-shift action of fluted collar for fast easy change from hammering with rotation to rotation only. Shift forward for drilling wood or metal. Retract for percussion drilling in concrete or masonry.



OUTSTANDING FEATURES

- **Powerful 4.5 amp motors with high velocity fan cooling.**
- **Drills 11/64" to 5/16" Anchor Holes in construction grade concrete with Percussion Carbide Tip Bits. 50,000 blows per minute at 2500 RPM.**
- **Drills up to ¼" in steel and ½" in wood at 2500 RPM with drilling action only using standard drill bits.**
- **Compact and lightweight. Ideal for drilling overhead.**
- **Trigger Speed Control model provides speeds of 0 to 2500 RPM for maximum control and accuracy. Prevents bit walking when starting holes in tile and ceramics at low speed. Depress trigger for higher speeds.**

1. **Rubber dust shield over chuck in front of fluted collar protects against harmful abrasive dust.**
2. **Depth gauge quickly adjusts to any drilling depth required for anchors.**
3. **Side handle for ease in handling . . . removable for close quarter work.**

SPECIFICATIONS

115 Volts

Catalog No.	Type	Blows Per Min.	No Load RPM	Length Inches	Net Wgt Lbs.	Shpg. Wgt Lbs.	O.S.H.A. Compliance
5390 Tool Only **5395** Kit	**Single Speed**	50,000	2,500	11	4½	7 15	Yes
5392 Tool Only **5397** Kit	**Trigger Speed Control**	50,000	0 to 2,500	11	4½	7 15	Yes

TOOL ONLY includes Hammer-Drill, depth gauge, removable side handle, rubber dust shield, special ⅜" industrial, geared, key-type chuck and chuck key with holder.

KIT. Same as Tool Only. Also includes 3/16" x 3", ¼" x 4", ⅜" x 4" and ½" x 6" percussion carbide-tip bits and steel carrying case.

PERCUSSION CARBIDE-TIP BITS

For Drilling Concrete and Masonry

These Carbide-Tip Bits are especially made with round shanks for use with Hammer Drills. Alloy steel shanks and bodies are heat treated for durability and long life. Highest quality carbide tips brazed to steel bodies resist dulling, stay sharp longer and can be resharpened often. Wide spiral with shallow oval flutes removes dust fast to assure maximum drilling efficiency.

SPECIFICATIONS

Bit Dia. (Inches)	Catalog No.	Shank Dia. (Inches)	Overall Length (Inches)
11/64	**48-20-6170**	11/64	3
3/16	**48-20-6180**	3/16	3
7/32	**48-20-6220**	3/16	3
1/4	**48-20-6250**	1/4	4
1/4	**48-20-6251**	1/4	6
9/32	**48-20-6280**	17/64	4
5/16	**48-20-6310**	17/64	4
5/16	**48-20-6311**	17/64	6
3/8	**48-20-6380**	5/16	4
3/8	**48-20-6381**	5/16	6
3/8	**48-20-6382**	5/16	13½
7/16	**48-20-6440**	3/8	6
15/32	**48-20-6470**	3/8	6
1/2	**48-20-6500**	3/8	6
1/2	**48-20-6501**	3/8	13½
9/16	**48-20-6560**	3/8	6

NOTE: Bits 11/64" thru 5/16" dia. are for use with Milwaukee Hammer-Drill with ⅜" chuck. Above bits and those listed below can be used with other Hammer-Drills depending upon chuck capacity. See shank dia. column.

5/8	**48-20-6620**	1/2	6
11/16	**48-20-6690**	1/2	6
3/4	**48-20-6750**	1/2	6
7/8	**48-20-6880**	1/2	6

⅜" SPECIAL CHUCK

Catalog No. 48-66-0810 Industrial, key type, 3-jaw chuck with ⅜-24 thread for use with Milwaukee Hammer-Drill. Includes Chuck Key No. 48-66-3240.

MISCELLANEOUS

Catalog No.	Description
49-62-0090	Rubber Dust Shield
48-55-0710	Steel Carrying Case
48-66-4040	Rubber-Flex Key Holder
49-08-0500	½ Lb. Can "A" Grease } For Gears
49-08-0800	1 Lb. Can "A" Grease } For Gears
49-08-0150	3 oz. Lubricant for Mechanism

HEAVY-DUTY Milwaukee 3/4" ROTARY HAMMER

NEW

for Percussion Carbide-Bit Drilling in Concrete and Masonry.

Ball and Roller Bearings

Catalog No. 5351

NEW GLASS REINFORCED NYLON D-HANDLE

2500 HEAVY HAMMER BLOWS PER MINUTE
1000 RPM NO LOAD SPEED

This powerful, lightweight Rotary Hammer is designed for fast, economical drilling—Drills 5½" per minute with ½" bit in construction grade concrete — An ideal tool for drilling anchor holes. "A" taper bits in popular sizes fit directly into nose of tool. Light pressure against work engages hammer action. Hammering with spring-loaded ram mechanism is combined with high torque rotation for best drilling efficiency. Hammer action stops when not under load, preventing damage while idling. Adjustable depth gauge assures accurate drilling depths. Auxiliary side handle is interchangeable right or left. Dust shield protects mechanism when drilling overhead. Special air intake and exhaust vents provide maximum cooling.

Catalog Nos. 5350 all Aluminum and 5351 with Glass Reinforced Nylon Handle Rotary Hammer Kits. Includes ¾" Rotary Hammer with "A" taper adapter, drift key, auxiliary side handle, depth gauge, dust shield, 3 oz. tube of lubricant for mechanism and steel carrying case.

Catalog Nos. 5355 all Aluminum and 5357 with Glass Reinforced Nylon Handle Rotary Hammer Kits. Same as above. Also includes 6 "A" taper bits ¼" x 4", ⅜" x 4½", 7/16" x 4½", ½" x 4½", 9/16" x 5", and ⅝" x 5".

SPECIFICATIONS

115 volts

Catalog No.	Maximum Capacity	Blows Per Min.	No Load RPM	Length Inches	Net Wgt. Lbs.	Shpg. Wgt. Lbs.	O.S.H.A. Compliance
5350	⅞"	2500	1000	17½	10	21	Yes
5351				18⅜		21	Yes
5355				17½		22	Yes
5357				18⅜		22	Yes

SPECIAL FEATURES

NO HOURLY OR DAILY OILING
GREASE PERIODICALLY
DEPENDING UPON AMOUNT OF USE

3-WAY ACTION

- **HAMMERING WITH ROTATION**
- **HAMMERING ACTION ONLY**
- **ROTATION ONLY**

ACCESSORIES

"A" TAPER PERCUSSION CARBIDE-TIP BITS

MILWAUKEE "A" Taper Bits have alloy steel shanks and bodies for strength and durability. Wide spiral with shallow flutes removes dust fast. Prevents packing and assures maximum drilling efficiency. Durable carbide-tip brazed to steel body . . . stays sharp longer. Use rotation with hammering action.

Bits Fit Directly Into Nose of Tool

"A" TAPER BITS

Bit Dia. (in.)	Catalog No.	Overall Length (in.)	Max. Drilling Depth (in.)
3/16	48-20-3180	4	2
¼	48-20-3250	4	2
¼	48-20-3252	6	4
5/16	48-20-3310	4½	2½
5/16	48-20-3312	6	4
⅜	48-20-3380	4½	2½
⅜	48-20-3381	9	7
⅜	48-20-3382	12	10
7/16	48-20-3440	4½	2½
15/32	48-20-3470	4½	2½
½	48-20-3499	9	7
½	48-20-3500	4½	2½
½	48-20-3501	12	10
9/16	48-20-3559	5	3
9/16	48-20-3560	9	7
⅝	48-20-3619	5	3
⅝	48-20-3620	9	7
⅝	48-20-3621	12	10
11/16	48-20-3690	5	3
¾	48-20-3790	5½	3½
¾	48-20-3795	9	7
⅞	48-20-3860	5	3

CHISEL and CHISEL ADAPTER

Use with hammering action only

Chisel Adapter

Chisel Adapter **Catalog No. 48-03-3620**
Fastens to nose of tool

Chisel
¾ x 4½ x 7

Chisel **Catalog No. 48-62-0300**
Use retaining spring 49-68-0075.

½" INDUSTRIAL CHUCK and ADAPTER

Use with Rotation only

Adapter

½" Chuck

Chuck Adapter **Catalog No. 48-03-3590**
"A" taper shank. ½"-20 threaded end.

½" Jacobs Chuck **Catalog No. 48-66-1280**
Chuck Key No. 48-66-3280 included.

TOOTH ANCHOR CHUCKS and ADAPTER



Use with hammering action only — Manual Rotation

Catalog No.	Description
48-66-6720	For Bolt Size ¼"-3/16" Anchor O.D. 7/16"
48-66-6730	For Bolt Size ⅜" Anchor O.D. 9/16"
48-03-3615	Chuck Adapter
48-86-0100	Drift Pin
49-68-0075	Retaining Spring

TOOTH ANCHOR CHUCK KIT

Catalog No. 49-22-2050 Includes all items listed in table above.



MISCELLANEOUS

Catalog No.	Description
48-03-3610 •	"A" Taper Bit Adapter
48-86-0050 •	Drift Key for above
49-96-0080 •	Socket Wrench for Depth Gauge
49-62-0080 •	Dust Shield
49-08-0150 •	3 oz. Lubricant for Mechanism
48-55-0570 •	Steel Carrying Case
49-68-0075	Retaining Spring
49-08-0500	½ lb. Can "A" Grease For Gears
49-08-0800	1 lb. Can "A" Grease For Gears

•Same as furnished with Tool.

HEAVY-DUTY Milwaukee 1-1/2" ROTARY HAMMER

Fastest Drilling Rotary Hammer On The Market

DRILL TO 2½" DIAMETER WITH PERCUSSION CORE BITS

CATALOG No. 5300

NO HOURLY OR DAILY OILING GREASE ONLY EVERY 2 TO 3 MONTHS DEPENDING UPON AMOUNT OF USE

For Percussion Carbide Bit Drilling in concrete and masonry ¼" thru 1½" dia. holes • Core Drilling 1¼", 1½", 1¾", 2" and 2½" holes • for Shell Anchors • Drills Steel to ½" diameter • Hammer Tools for chiseling, channeling, demolition work, chipping, scaling, slotting and tuck-pointing.

The MILWAUKEE 1½" Rotary Hammer is the most dependable and versatile Rotary Hammer you can buy. It is designed for rugged use and long life. Hammer mechanism is a practical combination of heavy spring and cam action. The lift cam is counter balanced to minimize tool vibration. Hammering ram is made of tool steel, precision ground and hardened. The ram is spring loaded and free floating. This mechanism will outlast any semi-pneumatic, piston type hammer. "In-Line" design of the Rotary Hammer prolongs motor and bearing life . . . Ball and roller bearings on all rotating shafts . . . Triple gear reduction . . . Heat treated gears and hardened shafts. During idling periods, shock of ram is absorbed by 6 disc springs protecting components. Armature bearings are cushioned by flat neoprene washers to prevent transmission of shock to the armature. Large fan and special vents provide maximum motor cooling.

Catalog No. 5300 Rotary Hammer includes Rotary Hammer in steel carrying case, depth gauge, pipe handle, 2 dust shields, 1 lb. can of grease and hammer tool adapter assembly.

Catalog No. 5305 Rotary Hammer Kit same as above. Also includes a scaling chisel, slotting chisel, mortar chisel, 11" bull point, 11" cold chisel, "A" taper chuck, ¼" x 4", ⅜" x 4½", 7/16" x 4½", ½" x 4½", ⅝" x 5" and ¾" x 9" "A" taper bits, and a drift pin.

SPECIFICATIONS

115 VOLTS

Catalog No.	R.P.M.			Blows Per Min.		Length	Net Weight	Shpg. Weight	O.S.H.A. Compliance
	Light Blow	Heavy Blow	Rotation Only	Light Blow	Heavy Blow				
5300 5305	700	600	850	3800	3250	18"	19¾ lbs.	45 lbs. 52 lbs.	Yes Yes

CONVERSION KIT

CATALOG No. 48-62-0205 Additional accessories to convert No. 5300 to No. 5305 as itemized above the specification table.

SPECIAL FEATURES

EXCLUSIVE 5-WAY ACTION

- **Rotation with heavy hammer blow**
- **Rotation with light hammer blow**
- **Rotation without hammering**
- **Hammering with light blow**
- **Hammering with heavy blow**



The shift lever repositions the cam which operates the hammer mechanism. Can be used freely because it does not engage or disengage gears. In No. 1 position the tool operates with rotation only. Use with industrial ½" chuck for drilling wood or metal. No. 2 position produces rotation and light hammering action. Use with percussion carbide-tip bits up to ½" diameter and larger when drilling soft materials. No. 3 position produces rotation with heavy hammering action. Use with percussion carbide-tip bits ½" and larger. For hammering action without rotation, use the tool adapter assembly. This fits into the nose of the tool to accommodate hammer tools such as chisels or bullpoints. Use the light blow (position 2) for scoring or when working in soft materials and the heavy blow (position 3) where full power is required.



SPRING-LOADED DEPTH GAUGE

Guide rod locks under spring tension to maintain accurate setting when bit reaches pre-set depth. Simple to adjust and easily removed when tool is used for other work.

ADJUSTABLE SAFETY CLUTCH

Protects operator, tool and bit. When bit jams or strikes re-bar, clutch slips — rotary action stops — prevents jolt to operator and excessive wear on bit shank or nose bushing. If clutch slips too readily, adjustment is easily made.

3-POSITION PIPE HANDLE

Offers ease in handling for use in any position. Pipe Handle can be used on either side of the motor housing or on top of switch handle.

Drilling 1" anchor holes in concrete for the installation of heavy machinery is done fast and accurate with the 5300 Rotary Hammer.

See pages 25 and 26 for Percussion Carbide-Tip Bits, Hammer Tools and other accessories for the 5300 Rotary Hammer.

HEAVY-DUTY PERCUSSION CARBIDE-TIPPED BITS

For Model 5300 Rotary Hammer

For High Speed, Low Cost Drilling in Concrete and Masonry



HIGHEST QUALITY CARBIDE TIP BRAZED TO STEEL BODY

Specially designed for continuous use with heavy blow and rotary action, MILWAUKEE Percussion Carbide-Tip Bits have heat-treated alloy steel shanks and bodies for durability and long life. Wide spiral with shallow oval flutes removes dust fast as it drills, resists packing and assures maximum drilling efficiency. Highest quality carbide tip is brazed to steel body, resists dulling, stays sharp longer and can be resharpened often.

ROTARY PERCUSSION CORE BITS



MILWAUKEE Core Bits have heat-treated steel bodies with durable carbide tips. Specially designed for fast, accurate drilling with heavy hammering and rotary action.

CORE BITS

1¼" x 6"	**Cat. No. 48-20-5250**
1½" x 6"	**48-20-5510**
1¾" x 6"	**48-20-5760**
2" x 6"	**48-20-6010**
2½" x 6"	**48-20-6050**

Above includes Core Bit and Starter Bit. Order Core Bit Adapter separately.

½" STARTER BITS

Same as furnished with Core Bits.

For 1¼"	**Cat. No. 48-20-6105**
For 1½"	**48-20-6110**
For 1¾"	**48-20-6120**
For 2"	**48-20-6130**
For 2½"	**48-20-6140**

CORE BIT ADAPTERS

Order Separately

For 1¼" Core Bit
Cat. No. 48-03-3515

For 1½", 1¾", 2" and 2½" sizes
Cat. No. 48-03-3505
Above also fit Skil 726

EXTENSIONS

For 1¼" Core Bit
12" Long **Cat. No. 48-95-6065**

For 1½", 1¾", 2" and 2½" Core Bits
7½" long **Cat. No. 48-95-6005**
12" long **Cat. No. 48-95-6055**

AVAILABLE IN TWO TYPES

GENERAL PURPOSE BITS are used for deep hole drilling. No adapter is required. One piece bits fit directly into the nose of the hammer. Sizes range from ½" to 1½" diameter. Shorter bits with "A" or "B" taper shanks are used with taper chucks. Bits with taper shanks are economical and recommended where only shallow holes are needed.

FLAT TIP BITS are used for drilling accurate holes for anchors. Available in one piece or "B" taper shanks and in diameters from 7/16" to 1⅛". Drill true holes with virtually flat bottoms for maximum seating and holding of anchors and expansion shields. Holes can be drilled to preset depth through use of depth gauge on Rotary Hammer.

GENERAL PURPOSE BITS

ONE PIECE
7/16" HEX. x 2⅛" LONG SHANK

Bit Dia. (in.)	Catalog No.	Overall Length (in.)	Max. Drilling Depth (in.)
½	**48-20-1500**	10	4¼
½	**48-20-1502**	16	10½
½	**48-20-1504**	22	16
9/16	**48-20-1560**	12	6½
5/8	**48-20-1630**	10	4½
5/8	**48-20-1632**	16	10½
5/8	**48-20-1634**	22	16
11/16	**48-20-1690**	12	6½
¾	**48-20-1750**	10	4½
¾	**48-20-1752**	16	10½
¾	**48-20-1754**	23½	18
⅞	**48-20-1880**	12	6½
⅞	**48-20-1882**	23½	18
1	**48-20-2000**	12	6½
1	**48-20-2002**	23½	18
1⅛	**48-20-2130**	12	6½
1⅛	**48-20-2132**	23½	18
1¼	**48-20-2250**	12	7
1¼	**48-20-2251**	23½	18
1⅜	**48-20-2370**	12	7
1⅜	**48-20-2372**	23½	18
1½	**48-20-2500**	15	10
1½	**48-20-2502**	23½	18

TAPER SHANK BITS
USE TAPER CHUCKS

"A" TAPER BITS
USE "A" TAPER CHUCKS

Bit Dia. (in.)	Catalog No.	Overall Length (in.)	Max. Drilling Depth (in.)
¼	**48-20-3250**	4	2
¼	**48-20-3252**	6	4
5/16	**48-20-3310**	4½	2½
5/16	**48-20-3312**	6	4
⅜	**48-20-3380**	4½	2½
⅜	**48-20-3381**	9	7
⅜	**48-20-3382**	12	10
7/16	**48-20-3440**	4½	2½
15/32	**48-20-3470**	4½	2½
½	**48-20-3499**	9	7
½	**48-20-3500**	4½	2½
½	**48-20-3501**	12	10
9/16	**48-20-3559**	5	3
9/16	**48-20-3560**	9	7
5/8	**48-20-3619**	5	3
5/8	**48-20-3620**	9	7
5/8	**48-20-3621**	12	10
11/16	**48-20-3690**	5	3
¾	**48-20-3790**	5½	3½
¾	**48-20-3795**	9	7
⅞	**48-20-3860**	5	3

FLAT TIP BITS

ONE PIECE
7/16" HEX. x 2⅛" LONG SHANK

Bit Dia. (in.)	Catalog No.	Overall Length (in.)	Max. Drilling Depth (in.)
7/16	**48-20-4440**	8	2¾
15/32	**48-20-4470**	8	2¾
½	**48-20-4500**	8	2¾
9/16	**48-20-4560**	8	2¾
5/8	**48-20-4650**	8	2¾
11/16	**48-20-4690**	8	2¾
¾	**48-20-4750**	9	4
27/32	**48-20-4840**	9	4
⅞	**48-20-4870**	9	4
1	**48-20-5000**	12	7
1⅛	**48-20-5130**	12	7

"B" TAPER BITS
USE "B" TAPER CHUCKS

Bit Dia. (in.)	Catalog No.	Overall Length (in.)	Max. Drilling Depth. (in.)
11/16	**48-20-3680**	9	6¾
¾	**48-20-3750**	9	6¾
27/32	**48-20-3840**	9	6¾
⅞	**48-20-3870**	9	6¾
1	**48-20-3100**	9	6¾

FLAT TIP "B" TAPER
USE WITH "B" TAPER CHUCKS

Bit Dia. (in.)	Catalog No.	Overall Length (in.)	Max. Drilling Depth (in.)
7/16	**48-20-7440**	5½	3¼
15/32	**48-20-7470**	8	5½
½	**48-20-7500**	8	5½
9/16	**48-20-7560**	8	5½
5/8	**48-20-7620**	8	5½
11/16	**48-20-7690**	8	5½
¾	**48-20-7750**	9	6½
27/32	**48-20-7840**	9	6½
⅞	**48-20-7870**	9	6½
1	**48-20-8000**	9	6½
1⅛	**48-20-8130**	9	6½

TAPER CHUCKS

TAPER CHUCKS FOR "A" & "B" TAPER SHANK BITS
Drift pin included with each chuck.

Taper Chuck	Model Number	Catalog Number
"A"	MILWAUKEE	**48-66-6500**
"B"	5300	**48-66-6501**
"A"	B & D	**48-66-6506**
"B"	717-718-719	**48-66-6505**
"A"	Skil 706	**48-66-6708**
"A"	Skil 726	**48-66-6500**
"B"	Skil 726	**48-66-6501**
"A"	Skil 728	**48-66-6709**
"B"	Skil 728	**48-66-6710**
"B"	Skil 736	**48-66-6507**
"A"	Skil 1706	**48-66-6708**
"A"	Hilti TE 17	**48-66-6750**
Drift Pins	when ordered separately	**48-86-0090*** **48-86-0100**

*Use with Chuck No. 48-66-6708

HEAVY-DUTY Milwaukee ROTARY HAMMER ACCESSORIES

For Model 5300 Rotary Hammer

Chucks for Tooth Anchors • Hammer Tools for Chiseling, Channeling, Demolition Work, Chipping, Scaling, Slotting and Tuckpointing • Industrial 3-Jaw Chuck for Drilling Wood and Metal • Star Drills and Star Drill Chuck

HAMMER TOOLS

Made of Highest Quality Forged Steel
Use With Tool Adapter Assembly

SCALING CHISEL

1¾" x 5½" x 10" long

For removing weld spatter or scale and cutting between drilled holes in concrete for large openings.
Catalog No. 48-62-0210

MORTAR CUTTING CHISEL

1" x 5" x 11" long

For removing old mortar for tuckpointing or caulking and seaming.
Catalog No. 48-62-0230

COLD CHISELS

¾" x 11" or 18" long

For edging, chipping or channeling.
Cat. No. 48-62-0250 11" lg.
Cat. No. 48-62-0252 18" lg.

BULL POINTS

11" or 18" long

For demolition work.
Cat. No. 48-62-0240 11" lg. Net
Cat. No. 48-62-0248 18" lg. Net

SLOTTING CHISEL

1⅛" x 5½" x 11" long

For slotting and cutting between drilled holes in concrete and masonry.
Catalog No. 48-62-0220

INDUSTRIAL CHUCK and ADAPTER

Chuck Adapter
Catalog No. 48-03-3000

½" Chuck
Catalog No. 48-66-1280

Used with rotation only. Chuck threads on chuck adapter (½"-20 thread). Capacity in steel ½". Use as regular drill for other applications. Chuck key No. 48-66-3280 included with chuck (see page 10). Order both chuck and chuck adapter.

TOOTH ANCHOR CHUCKS

For Self-Drilling Anchors

Use with "B" Taper Chucks Shown Below

Catalog No.	Description
48-66-6520	3/16"-1/4"
48-66-6540	FOR 5/16" BOLT 3/8" SIZE 1/2" 5/8"
48-66-6560	O.D. OF ANCHOR 7/16" 15/32" 9/16" 11/16" 27/32"
48-66-6580	
48-66-6600	

For final setting of anchors ½" and ⅝" use hand hammer and setting tool.



For Manual Rotation
"B" Taper Chuck Assembly Required
Catalog No. 48-03-3600
Drift Pin 48-86-0100 included

For Automatic Rotation
"B" Taper Chuck Required
Catalog No. 48-66-6501
Drift Pin 48-86-0100 included

TOOTH ANCHOR CHUCK KIT

Catalog No. 49-22-2000

Tooth Anchor Chucks for bolt sizes 3/16", ¼", ⅜", ½" and ⅝"; "B" Taper Chuck (48-66-6501) with Drift Pin (48-86-0100) and steel case.



STAR DRILLS and STAR DRILL CHUCK

For Manual Rotation with Hammering Action Only



Catalog No.	Description
48-88-0251	¼" x 6"
48-88-0252	¼" x 12"
48-88-0310	5/16" x 6"
48-88-0311	5/16" x 12"
48-88-0370	⅜" x 6"
48-88-0371	⅜" x 12"
48-88-0430	7/16" x 6"
48-88-0500	½" x 6"
48-88-0501	½" x 12"
48-88-0620	⅝" x 6"
48-88-0621	⅝" x 12"
48-88 0750	¾" x 6"
48-88-0751	¾" x 12"
48-88-0870	⅞" x 6"
48-88-0871	⅞" x 12"
48-88-1000	1" x 6"
48-88-1001	1" x 12"
48-88-1120	1⅛" x 6"
48-66-6050	Star Drill Chuck*
48-86-0090	Drift Pin

*Drift Pin Included with Chuck.

DUST SHIELD

Catalog No. 49-62-0070
Same as furnished with each tool. Keeps foreign matter from entering nose of tool. Prevents grease contamination.

TOOL ADAPTER ASSEMBLY

Catalog No. 48-03-0050
Same as furnished with each tool. Must be used with hammer tools for hammering action only.

MISCELLANEOUS

48-55-0600	Carrying Case Only (for 5300 Rotary Hammer)
48-86-0100	Drift Pin
49-08-0500	½ lb. Can "A" Grease
49-08-0800	1 lb. Can "A" Grease

HEAVY-DUTY Milwaukee ELECTRIC CHAIN SAWS

CHAIN CUTTING SPEED 2000 FT. PER MINUTE

FULL 2 HP AT THE CHAIN

16" and 20" Sizes

LIGHTWEIGHT

ALL BALL BEARINGS

NEW

Ruggedly built, fast cutting Chain Saw with functional housing proportioned for best balance. Grip handles located for easy handling in any position. Dustproof trigger switch. Tempered steel Guide Bar with uniform hardness and straight rail for friction-free chain travel. 3/8" pitch Chipper Chain for all-around cutting. Recessed chain and guide bar adjustment. Cleats provide fulcrum for feeding into work.

OUTSTANDING FEATURES

- **Most powerful Electric Chain Saw of its size.**
- **Flush cuts . . . no housing or bolt overhang.**
- **Large sawdust and chip removal port.**
- **Plunger-type chain oiler. One pint capacity.**
- **Instant start even in freezing temperatures.**
- **No fuel . . . No fire hazard.**
- **Quiet, smooth, electric motor.**

SPECIFICATIONS

Catalog No.	Bar Length	Volts	H.P. At The Chain	Cutting Speed Ft./Min.	Net Wt. Lbs.	Shp. Wt. Lbs.	O.S.H.A. Compliance
6205	16"	115	2	2000	17½	24	Yes
6206	20"				18½	26	Yes

Standard Equipment Includes Chipper Chain and Wrench.

CONVERSION KITS

Convert previous models 6200 and 6201 Chain Saws to use new guide bars and chains listed for 6205 and 6206 Chain Saws. Kits include a sprocket, guide bar and chain.

GUIDE BARS

CHAINS

SPROCKET

Catalog No.	Description
49-22-4016	16" Conversion Kit (For Cat. No. 6200)
49-22-4020	20" Conversion Kit (For Cat. No. 6201)

ACCESSORIES FOR MODELS 6205 AND 6206

GUIDE BARS

CHAINS

FILE AND HOLDER

Catalog No.	Description
48-09-5016	16" GuideBar
48-09-5020	20" Guide Bar
48-58-0016	16" Chipper Chain
48-58-0020	20" Chipper Chain
49-17-0100	File and Holder (For use with 3/8" pitch chain)
49-22-3010	Chain Replacement Kit (For use with Chipper Chain) Includes tie straps and drive link.
49-96-6200	Chain Saw Wrench
49-08-0500	½ lb. Type "A" Grease
49-08-0800	1 lb. Type "A" Grease

ACCESSORIES FOR PREVIOUS MODELS 6200 AND 6201

Catalog No.	Description
48-09-5000	16" GuideBar
48-09-5100	20" Guide Bar
48-58-0050	16" Chipper Chain
48-58-0070	20" Chipper Chain
49-17-0100	File and Holder (For use with 3/8" pitch chain)
49-22-3000	Chain Replacement Kit (For use with Chipper Chain) Includes tie straps and drive link.
49-96-6200	Chain Saw Wrench
49-08-0500	½ lb. Type "A" Grease
49-08-0800	1 lb. Type "A" Grease

HEAVY-DUTY Milwaukee PORTABLE ELECTRIC BAND SAW

NEW

CATALOG NO. 6225 LESS CASE
CATALOG NO. 6226 WITH CASE

- **Gear drive mechanism is lubricated with grease — *no oiling required!***
- **Precision Needle Bearing Blade Guides**
- **Cuts to within 1″ of floor**
- **Ideal for sawing PVC tubing**
- **High Strength frame to withstand years of service**
- **Front T-Handle for better control**
- **Heavy-Duty on/off two-speed switch**
- **Powerful Milwaukee Built Motor**
- **Uses standard 44⅞″ x ½″ x .020 band saw blades**

A new versatile 2-speed Portable Band Saw . . . low speed 200 surface feet per minute . . . high speed 250 surface feet per minute. Use it to cut large cable, pipe or round stock to 3½″ O.D., or rectangular stock up to 3½″ x 4½″. Cuts to within 1″ of floor, ceiling, or wall. It saws metal, plastic, wood . . . you name it. High and low speeds are carefully matched to Milwaukee precision saw blades for construction and production sawing jobs.

Gearing design incorporates helical gearing plus a heavy-duty worm gear, and a final chain and sprocket reduction. Hardened and precision ground steel worm meshes with alloy bronze gear for long life and smooth cool operation under all sawing applications. Gear drive mechanism is lubricated with grease — *no oiling required!*



Cuts pipe and conduit to 3½″ dia. in one pass

SPECIFICATIONS

Catalog No.	No Load Surface Ft. per Min. High	Low	Capacity Round Stock	Capacity Rectangular Stock	Length (In.)	Net Wgt. (LBS.)	Shp. Wgt. (LBS.)	O.S.H.A. Compliance
6225 Less Case	250	200	3½″	3½″ x 4½″	20″	16	23	Yes
6226 With Case							34	

Standard Equipment includes one 48-39-0360 quality 14 tooth high speed steel blade.
Steel Carrying Case (when ordered separately) Cat. No. 48-55-1090

HEAVY-DUTY MILWAUKEE BAND SAW BLADES

CARBON STEEL BLADES An inexpensive utility blade for intermittent use that will cut a wide range of material.

ALLOY STEEL BLADES Give greater blade life and sustain higher shock than carbon steel blades and cut a wider range of materials including tough alloys and structural steel.

HIGH SPEED STEEL BLADES High Speed Steel blades will outlast carbon steel and alloy steel blades for cutting most materials. Ideal for cutting carbon steel, drill rod and other solids and large diameter hard material.

6 TEETH/INCH	8 TEETH/INCH	10 TEETH/INCH
14 TEETH/INCH	18 TEETH/INCH	24 TEETH/INCH

CATALOG NUMBER	Qty. Per Pkg.	Recommended Use	Thickness of Material To Be Cut	Teeth Per Inch
		CARBON STEEL		
48-39-0050	3	High speed cutting of aluminum, brass, copper, soft bronze, magnesium, wood, mild steel; and tougher steels at slow speed	½″-3⅜″	6
48-39-0060	3	High speed cutting of aluminum, brass, copper, magnesium, mild steel; and tougher steels at slow speed	⅜″-1″	8
48-39-0070	3	High speed cutting of aluminum, angle iron, cast iron, bronze, brass, copper, galvanized pipe, mild steel; and tougher steels at slow speed	3/16″-¾″	10
48-39-0080	3	High speed cutting of aluminum, angle iron, cast iron, bronze, brass, copper, galvanized pipe, mild steel; and tougher steels and electric cable at slow speed	5/32″-½″	14
48-39-0090	3	High speed cutting of angle iron, bronze, brass, copper, galvanized pipe, thin wall tubing, mild steel; and tougher steels at slow speed	⅛″-¼″	18
48-39-0100	3		3/32″-⅛″	24
		ALLOY STEEL		
48-39-0250	1	High speed cutting of aluminum, angle iron, cast iron, bronze, brass, copper, galvanized pipe, mild steel; and tougher steel including chrome and tungsten steels at slow speed	3/16″-1″	10
48-39-0260	1	High speed cutting of aluminum, angle iron, cast iron, bronze, brass, copper, galvanized pipe, mild steel; and tougher steels including chrome, tungsten steels and electric cable at slow speed	5/32″-¾″	14
48-39-0270	1	High speed cutting of angle iron, bronze, brass, copper, galvanized pipe, thin wall tubing, mild steel; and tougher steels including chrome and tungsten steels at slow speed	⅛″-½″	18
48-39-0280	1	High speed cutting of angle iron, bronze, brass, copper, galvanized pipe, thin wall tubing, mild steel; and tougher steels at slow speed	3/32″-⅛″	24
		HIGH SPEED STEEL		
48-39-0350	1	High speed cutting of aluminum, angle iron, bronze, brass, copper, galvanized pipe, mild steel; and tougher steels including stainless, chrome, tungsten steels plus other problem material at slow speed	7/32″-⅞″	10
48-39-0360	1		3/16″-5/8″	14
48-39-0370	1		5/32″-⅜″	18

HEAVY-DUTY Milwaukee JIG-SAWS



SINGLE SPEED UNIT

Fast . . Powerful . . . Accurate

Most versatile Jig-Saw. Cuts wood, metal, plastics and composition materials. Lightweight—compact—powerful ¼ HP motor—ball and roller bearings on all rotating parts—cool running—rugged, vibration-free mechanism—perfect balance—excellent blade visibility with super sawdust blower to keep cutting lines clear. Single Speed unit with 3500 strokes per minute for general sawing.

Available
With or Without
STEEL CARRYING CASE
Cat. No. 48-55-1070

The Variable Speed Control unit permits dialing to any speed within the minimum and maximum speeds of 1400 to 3500 strokes per minute. Low speeds for increased blade life in cutting most hard materials and higher speeds for fast sawing of soft woods and composition materials. Control mechanism is full wave rectifier type with components transistorized for long life. Feedback circuit maintains speed, even under full cutting load.

VARIABLE SPEED UNIT

USE GENUINE MILWAUKEE JIG-SAW BLADES

Designed for best cutting efficiency with custom milled teeth set and hardened for maximum performance. Special tungsten carbide blades are available for cutting abrasive materials. Tang properly positions blade in the blade clamp. Universal ¼" tang fits most brands of jig saws.

CATALOG NO.	Lgth. (In.)	Teeth per Inch	Quan per Pkg.	MILWAUKEE JIG-SAW BLADES RECOMMENDED FOR CUTTING
METAL CUTTING . . . High Speed Steel Blades.				
48-42-0100	2¾	14	5	Steel to ⅛", non-ferrous metals to ¼", Plastics, Asbestos, Fiberglass, rigid conduit, hard rubber and fiber.
48-42-0101		12		Same as above. 25% thicker for most severe applications.
48-42-0120		17		Metals 18 Ga. to 10 Ga., tubing, plastics.
48-42-0140		21		Metals lighter than 18 Ga., thin wall tubing, slate, formica.
WOOD CUTTING . . . GENERAL PURPOSE . . . High Carbon Steel.				
48-42-0200	3⅛	6	5	Pocket and roughing cuts on heavier sections. Fiberboard, asbestos, asphalt.
48-42-0220		8		Same as 6 tooth but for smoother finish.
48-42-0240				Taper ground for smoothest sawing.
WOOD CUTTING . . . FLUSH CUTTING . . . High Carbon Steel.				
48-42-0300	3⅝	8	4	Same use as 6 tooth General Purpose. Saws up to a wall.
WOOD CUTTING . . . DELUXE . . . High Speed Steel.				
48-42-0400	3⅛	6	5	"Shear tooth" for fast roughing work on light and medium sections. Pocket cuts.
48-42-0420	3⅝		4	Same as above for fast roughing work on heavier sections.
WOOD CUTTING... DELUXE TAPER GROUND ...High Speed Steel.				
48-42-0500	3⅝	6	5	Fast finish work on medium sections (½"-¾") of plywood, formica, wood.
48-42-0520			4	Fast finish work on medium to heavy sections (½"-¾").
48-42-0540		10	5	Fast finish work on light sections (¼") thick of plywood, formica, wood.
48-42-0560			4	Fast finish work on light to medium sections (¼"-⅜").
48-42-0600	3⅝	6	5	Tight smooth scroll work. No distortion on curves. Saws plywood, formica, decorative veneers, plastics, etc. Thickness to ¾".
48-42-0620		10		Same as above to thicknesses of ½".
48-42-0640				Same as above. Reverse tooth for smooth finish on top surface.
KNIFE CUTTING . . . High Carbon Steel.				
48-42-0700	2½	0	5	Cuts insulating material, leather, rubber, cardboard, sponge, felt, acoustical tile.
ABRASIVE MATERIALS . . . Medium Grit Tungsten Carbide				
48-42-0800	2⅞	0	4	Plywood, hardwood veneer, fiber glass, (polyesters, epoxies, melamines, silicones), ceramic tile, cast stone, slate, clay pipe, carbon, brick, chalkboard.
48-42-0810	4	0	4	Same as above. Flush cuts to a wall.

EXCLUSIVE FEATURES

PIVOTING HEAD

Cutting head is adjustable — right or left — to full 45° angle . . . calibrated settings. Locks at required angle by tightening a single screw. Handle remains in upright position.



TURN and LOCK SHOE

Shoe quickly adjusts for straight, miter or flush cuts. Adaptable for every sawing application. Loosen and rotate shoe to required position. Holes in the shoe are placed on two locator pins on base of tool, then locked by tightening flat head screw.

SPECIFICATIONS

Catalog No.	Length of Stroke	Strokes per Minute	Overall Incl. Shoe Lgth.	W.	Ht.	Net Wgt. (Lbs.)	Shp. Wt. (Lbs.)	O.S.H.A. Compliance
SINGLE SPEED UNIT . . . 115 Volt								
6270 with case **6250** less case	¾"	3500	8"	3½"	5¼"	5	14 8	Yes
SPEED CONTROL UNIT . . . 115 Volt AC Only								
6285 with case **6280** less case	¾"	1400 to 3500	9½"	3½"	5¼"	5¼	14 8	Yes

Standard equipment includes Jig-Saw Blade Card 49-22-1160 for wood and metal — a total of 10 blades. Also included are a combination circle and rip guide, two socket wrenches, an extra blade clamp screw and one 48-66-4080 key holder.

JIG-SAW BLADE CARD

Cat. No. 49-22-1160 Same as furnished with each Jig-Saw. Consists of one each 48-42-(0100, 0120 and 0140) for metal, and 48-42-(0200, 0220, 0240, 0300, 0400, 0600 and 0640) for wood — a total of 10 blades.

WRENCH AND SCREW KITS

Cat. No. 49-22-5060 For Jig-Saws below serial no. 281-11240 (single speed) and serial no. 334-1415 (variable speed). Consists of five 49-96-0060 ⅛" Socket Wrenches for blade clamp, five 49-96-0080 3/16" Socket Wrenches for pivoting head and shoe adjustments. Also twenty blade clamp screws.

Cat. No. 49-22-5070 For Jig-Saws serial no. 281-11240 (single speed) and above and serial no. 334-1415 (variable speed) and above. Consists of five 49-96-0050 3/32" Socket Wrenches for blade clamp, five 49-96-0080 3/16" Socket Wrenches for pivoting head and shoe adjustments. Also twenty blade clamp screws.

TYPE "A" GREASE ½ lb. can **Cat. No. 49-08-0500**
1 lb. can **Cat. No. 49-08-0800**

All-Purpose Electric Hacksaws

AVAILABLE IN TWO SPEED AND VARIABLE SPEED MODELS

The first powerful, lightweight, portable electric reciprocating saw in a complete unit, the SAWZALL, with its patented mechanism, has proven its ruggedness and versatility for over fifteen years of continuous field use. For Plumbers, Heating and Air Conditioning Contractors, Electricians, Builders, Steel Fabricators, Maintenance Men and Manufacturers. Cuts any shape in wood, plaster, metal, plastics, masonite, builder's transite and other sawable materials . . . plunge cuts in wood and other resilient stock . . . no starting hole required.

NEW

DOUBLE INSULATED
TWO SPEED MODEL
CAT. NO. 6512
with case.



TWO SPEED UNIT
CAT. NO. 6510 with case.
CAT. NO. 6530 less case.
(Same as 6510 less case)



VARIABLE SPEED UNIT
CAT. NO. 6505 with case.

TWO SPEED UNIT
WITH DURABLE
GLASS REINFORCED
NYLON HANDLE
CAT. NO. 6511 with case.
CAT. NO. 6531, less case.
(Same as 6511 less case)

NEW DOUBLE INSULATED SAWZALL®

NEW Double Insulated Catalog No. 6512 Sawzall has two independent insulating barriers between electrical windings and spindle plus a durable glass reinforced nylon handle.

TWO SPEED SAWZALL®

Models available with two speeds to meet specific cutting requirements. High speed of 2400 strokes per minute for fast sawing of wood or composition materials . . . low speed of 1700 strokes per minute for maximum blade life when cutting metals. A 2-speed heavy-duty switch is conveniently located for easy switching to high or low speed as desired. Catalog No. 6511 has the same features as No. 6510 but with durable glass reinforced nylon handle.

VARIABLE SPEED SAWZALL®

Dial any speed from 1100 thru 2550 strokes per minute. Low speeds for increased blade life in cutting most hard materials and higher speeds for fast sawing of soft woods and composition materials. Control mechanism is full wave rectifier type with components transistorized for long life. Converts AC to DC giving full 115 volt sawing power on all speed ranges.



RECIPROCATING ACTION

A simple and rugged reciprocating mechanism built to stand large thrust loads in equal amount from either direction. Only three major moving parts. Heavy-duty bearings of the highest quality.

NEW SAWZALL® CUT-OFF FIXTURE

NEW

The Plumber's Second Best Friend. An inexpensive time saving accessory, designed to make square accurate cuts thru plastic pipe and other materials up to 4½" O.D. Easily accommodates irregular shapes to 3¼" x 4½".

Catalog No. 48-08-0200





OFFSET BLADE ADAPTER

Catalog No. 48-03-2000

For close quarter sawing. Extra Blade Clamp and Blade Clamp Screw included.

SPECIFICATIONS

115 volts

Catalog No.	Length of Stroke	Overall Length (Inches)	Net Wgt. (LBS.)	Ship. Wgt. (LBS.)	O.S.H.A. Compliance
Two Speed Unit — 2400 and 1700 Strokes Per Minute					
6510 with case	¾"	15⅛"	6¾	18	Yes
6530 less case				10	Yes
6531 less case*				10	Yes
6511 with case*		16"	7	18	Yes
6512 with case*†				18	Yes
Variable Speed Unit 1100 to 2550 Strokes Per Minute 115 Volt 60 Cycles AC Only					
6505 with case	¾"	15⅛"	7	18	Yes

*Equipped with glass reinforced nylon handle
†Double Insulated

Standard equipment includes Sawzall Blade Card 49-22-1120 for wood and metal— total of 11 blades. Also included are socket wrench and holder, extra blade clamp and screw.

WRENCH, SCREW AND CLAMP KIT

Catalog No. 49-22-5080 consists of 10 blade clamp screws, 2 blade clamps and 2 socket wrenches.

WRENCH AND SCREW KIT

Catalog No. 49-22-5050 consists of 25 socket wrenches and 50 blade clamp screws.

Blade Clamp Wrench	**Catalog No. 49-96-0070**
Rubber-Flex Wrench Holder	**Catalog No. 48-66-4080**
Steel Carrying Case	**Catalog No. 48-55-1560**
Type "A" Grease for Gear Case	½ lb. can **Catalog No. 49-08-0500**
	1 lb. can **Catalog No. 49-08-0800**
Type "B" Grease for Mechanism	½ lb. can **Catalog No. 49-08-0600**
	1 lb. can **Catalog No. 49-08-0900**

HEAVY-DUTY Milwaukee SAWZALL® BLADES

USE ONLY GENUINE SAWZALL® BLADES

- **Custom Milled Teeth, Set and Hardened for Maximum Performance at the Exact Speed of the Sawzall.**
- **Tang Designed to Secure Blade in Blade-Clamp at the Proper Angle for Maximum Cutting Efficiency.**



Type	Key	Catalog No.	Teeth per Inch	Lgth (In.)	Recommended for Cutting	Quan per Box
Roughing-In Blades, Wood and Plaster	A	48-00-1001 48-00-1002 48-00-1003	3	3½ 6 12	Nail free woods . . . fastest cutting . . . fully hardened to withstand roughest sawing. Teeth, fleam sharpened to shear, not tear wood fibers. Canted shank provides for faster feed, deeper cut and ideal return stroke clearance.	10 10 5
	B	48-00-1011 48-00-1012 48-00-2011	6	3½ 6 12	Nail embedded woods and composition materials . . . 12" blade affords flexibility for flush cutting.	10 10 5
		48-00-1013 48-00-1014 48-00-2012	10	3½ 6 12	For all woods . . . nail embedded woods, composition materials and light gauge non-ferrous metals.	10 10 5
		48-00-2013	18	12	Nail embedded woods . . . for opening crates, boxes, removing wood siding and shingles.	5
	C	48-00-1021 48-00-1022 48-00-1023 48-00-1024	6 6 10 10	3½ 6 3½ 6	All woods including nail-embedded woods. Hardened and tempered to resist bend or twist. Even after severe twist, blade springs right back to its original shape.	5
	D	48-00-1031 48-00-1032 48-00-1033	7	6 12 9	General roughing-in work in wood and nail embedded woods.	5
	E	48-00-1041 48-00-1042 48-00-1043	6	6 12 9	Wood cutting . . . shear tooth design . . . fleam sharpened for shearing action . . . very fast cutting, long blade life.	5 3 4
	F	48-00-1051 48-00-1052	5	3½ 6	For plaster, plaster with metal lath, plasterboard. Cuts on both forward and backward stroke.	10
	G	48-00-1061 48-00-1062	6	3½ 6	For nail-free woods, plywood, asbestos and fiberboard . . . A general purpose economy type blade.	10
		48-00-1063 48-00-1064 48-00-2064●	10	3½ 6 6	Nail embedded woods, plywood, insulating board, and asbestos. Blade edge hardened.	10
		48-00-1065 48-00-1066 48-00-2066●	18	3½ 6 6	For nail embedded woods, opening wooden crates or boxes, removing wood siding or shingles. Teeth are fully hardened.	10
		48-00-1067 48-00-1068	24	3½ 6	For light gauge non-ferrous metals.	10
Tungsten Carbide	H	48-00-1410	Scroll 0	3½	Medium grit; for brick, carbon, claypipe, chalkboard, plywood, hardwood veneer plywood.	3
	I	48-00-1400† 48-00-1420†	0	4 6	Coarse grit; for fiber glass (epoxies, polyesters, silicones, malamines). Nail embedded wood, plaster with nails, asbestos cement.	3
Specialty Blades	J	48-00-1071	Knife	4	Sponge, rubber, leather, felt and other resilient materials.	10
	K L	48-00-1081 48-00-1091	Wavy Scallop		Corrugated cardboard, laminated fiberglass, tape and sheets, paper, cork and rubber.	
Metal Scroll	M	48-00-1101 48-00-1102★ 48-00-1103★	14 18 24	2½	Scroll cutting metals. 14 tooth for ⅛" and over; 18 tooth—18 ga. to ⅛"; 24 tooth—lighter than 18 ga.	10
Roughing In	N	48-00-1131	7	4⅛	Plunge cutting wood and sawing back to a line. Hardened teeth and flexible center permits sawing in close-quarters. High resistance to bending or breaking. Ideal for roughing-in.	5
Wood Scroll	O	48-00-1121 48-00-1151	6	3⅝	Sawing intricate shapes and scroll cuts in wood and synthetic structural materials. (1121) a carbon steel economy blade (Gray) (1151) a high speed steel Deluxe blade (Black).	5
		48-00-1141	7	3⅝	Rough cutting irregular contours in wood, fiberboard, asphalt and asbestos. Spring steel blade. (Silver).	10
		48-00-1201 48-00-1202●	6	3⅝	High speed steel, hollow ground . . . De Luxe type . . . for fast, smooth finish scroll cuts in wood, plastics, formica and fiberglass. (Silver with black shank).	5
Metal Scroll	P	48-00-1161 48-00-1162	10 14	3⅝	Heavy gauge metal, hard rubber and fiber.	10
Metal Cutting	Q	48-00-2175	10	8	Cast iron, steel or copper pipe to 4" dia., and also metal decking materials.	5
		48-00-1171 48-00-1172 48-00-1179	14	2½ 4 6	Metal heavier than ⅛" thick, angles, bar stock, hard rubber and fiber.	10
		48-00-1173★ 48-00-1174★ 48-00-2170★	18	2½ 4 6	Heavy gauge metals, conduit, pipe, channels and tubing.	10
		48-00-1175★ 48-00-1176★ 48-00-2171★	24	2½ 4 6	Metals lighter than 18 gauge sheet, trim and tubing.	10
		48-00-1177 48-00-1178	32	2½ 4	Very light gauge metals . . . sheet trim and tubing.	10
	R	48-00-1181 48-00-1182	14	4 6	Heavy gauge metals, angles, bar stock ⅛" thick and above. Hard rubber. Teeth are fully hardened. Hardening of blade back limited to provide required resiliency.	10
		48-00-1183★ 48-00-1184★	18	4 6	Same characteristics as blades 1181 and 1182 except finer teeth for fast cutting of metals 18 gauge to ⅛" thick conduit, pipe, channels and tubing.	10
Pruning	S	48-00-1302	6	12	Pruning trees, smooth sawing green woods. Deep tooth design, fleam filed. Clean cuts wood fibers.	5

SOLD IN BOX LOTS ONLY — SEE QUANTITY PER BOX COLUMN

FOOTNOTE REFERENCE

- All blades have teeth set to cut on up stroke except blades 48-00-1202, 48-00-2064 and 48-00-2066. These 3 blades have teeth set to cut on down stroke and are recommended when sawing veneers or plywood to prevent splintering on the finish side.

★ Some varieties of stainless steel can be cut with these blades.

† With 2-Speed and Variable Speed SAWZALL use slower speeds.

Carbide blades cut on both the up and down strokes giving better edge finish.

ECONOMY BLADE ASSORTMENT

Catalog No. 49-22-1080

A special package value includes 45 Sawzall Blades of 18 most popular types of cutting wood or metal. Consists of five each catalog Nos. 48-00-(1063, 1064, 1174); three each 48-00-(1061, 1102, 1183); two each 48-00-(1023, 1024, 1041, 1051, 1062, 1103, 1121, 1141, 1173); one each 48-00-(1031, 1002, 1012).

SAWZALL® BLADE CARD

Catalog No. 49-22-1120 consists of one each of 48-00-(1011, 1023, 1031, 1041, 1064 and 1121) for wood, and 48-00-(1102, 1162, 1171, 1174 and 1182) for metal — a total of 11 blades.

HEAVY-DUTY Milwaukee CIRCULAR SAWS

Powerful • Rugged • Dependable
Built for Continuous Use



CONTRACTOR SAWS

11/3 HP

6½" and 7" MODELS

SPECIAL FEATURES

• Only 10½ lbs. • 2 Position Switch Control • Ball and Roller Bearings • Quick, Accurate Miter Adjustments • Cut 2" Dressed Lumber at 45° • Wide, Sturdy Wrap-Around Shoe • Carpenter Square Construction • Enclosed, Dustproof Switches • Telescoping Guard with Snap-Back Action.



PRODUCTION SAWS

13/4 HP

IN 2 POPULAR BLADE SIZES

7¼" 8¼"

SPECIAL FEATURES

• Powerful Motor Delivers 1¾ H.P. Output • Ball and Roller Bearings • Clear View Line Sighting • One Piece Wrap-Around Shoe for Rigid Support • Safe Telescoping Guard with Snap-Back Action • Carpenter Square Construction • Simple Miter and Depth Adjustments • Split Handle Design for Easy Access to Electrical Connections.

WORM DRIVE SAW

2 HP

7½"

SPECIAL FEATURES

• Wide Race and Oversized Ball Bearings • Large Machined Faces on Motor and Gear Housings Assure Solid Fit • Handles Not Part of Motor Housing • Rigid Steel Wrap-Around Shoe • Fast, Positive Miter and Depth Adjustments • Oil Plug at Side of Gear Case for Easy Fill • Up to 1" Lumber Can Be Used on Either Side of Shoe When Ripping Large Panels.

CONTRACTOR SAWS

The best lightweight Saws ever built for the contractor. Handle easily in any position with ideal visibility for fast, accurate sawing. Helical-cut hardened steel gears for smooth operation. Balanced handle control with top trigger switch for fast cut-off work and back trigger for longer reach.

115 volts **SPECIFICATIONS** 5/8" Arbor

Blade Size	Catalog No.	No load Speed (RPM)	Depth of Cut at 90°	Max. Depth of Cut at 45°	Net Wgt. (lbs.)	O.S.H.A. Compliance
6½"	**6292** with case **6293** less case	5600	0 to 2⅛"	1¾"	10½	Yes
7"	**6330** with case **6331** less case	5400	¼ to 2⅜"	1⅞"	10½	Yes

Shp. Wt. with case 25 lbs., less case 16 lbs.
Standard Equipment Includes Combination Saw Blade, Rip Guide and 1 ea. 9/16" & 1⅜" Wrenches.

Exclusive

Contractor Saws and Production Saws have a spring-loaded clutch drive to protect gears against backlash and wear. More than doubles gear life.

PRODUCTION SAWS

Designed for reliable year after year performance in heavy construction and industrial maintenance . . . widely used for sawing heavy hardwood planking and frames for concrete construction. Helical-cut, hardened steel gears for smooth running. Contour handle for balance and ease in handling. Large grease chamber provides maximum lubrication.

115 volts **SPECIFICATIONS** 5/8" Arbor

Blade Size	Catalog No.	No load Speed (RPM)	Depth of Cut at 90°	Max. Depth of Cut at 45°	Net Wgt. (lbs.)	O.S.H.A. Compliance
7¼"	**6340** with case **6360** less case	5800	0 to 2 17/32"	2 1/32"	14¾	Yes
8¼"	**6380** with case **6400** less case	5100	¾" to 3 1/32"	2⅜"	15	Yes

Shp. Wt. with case 34 lbs., less case 22 lbs.
Standard Equipment Includes Combination Saw Blade, Rip Guide and 1 ea. 9/16" & 1⅜" Wrenches.

WORM DRIVE SAW

Motor and worm drive gearing develop 2 H.P. at the blade. Designed for ease of handling with ideal balance. Retractable guard operates efficiently under any condition. Exhaust air directed over gear case keeps saw cool and line of sight clear. Saw equipped with diamond shaped arbor. Adapters available for blades with 5/8" arbor hole.

115 volts **SPECIFICATIONS** Diamond Arbor

Blade Size	Catalog No.	No load Speed (RPM)	Depth of Cut at 90°	Max. Depth of Cut at 45°	Net Wgt. (lbs.)	O.S.H.A. Compliance
7½"	**6370** less case **6371** with case	4400	0 to 2 15/32"	2 1/16"	15¾	Yes

Shp. Wt. with case 34 lbs., less case 22 lbs.
Standard Equipment Includes Combination Blade, 9/16" Blade Wrench, Rip Guide and Lubricant.

Exclusive

Hardened and precision ground steel worm meshes with alloy bronze gear for long life and smooth operation under all sawing conditions.

HEAVY-DUTY Milwaukee CIRCULAR SAW ACCESSORIES

Highest Quality for Best Performance

MILWAUKEE saw blades are made of chrome nickel steel — precision ground, tempered, set and filed. Each blade is perfectly balanced and tensioned for fast, smooth, accurate sawing. Carbide-tipped blades are chrome plated — cut fast and smooth, stay sharp up to 50% longer than steel-tipped blades. Ideal for cutting wood, Transite, Masonite, asbestos, Formica, composition siding and roofing. Abrasive cutting wheels for stone or concrete and metal are safety nylon reinforced — bonded of uniform grit and break resistant.



Blades 1 thru 6 have ⅝" arbor hole with knockout for diamond arbor.

1. COMBINATION . . . for general sawing. Rip or crosscut without changing blade.

2. CROSSCUT - FLOORING . . . cut hardwoods, flooring and crating fast. Close-set teeth produce smooth finish and hold edge longer when encountering nails.

3. RIP - CUT . . . for high speed production sawing. Hook shaped teeth have alternate set filed square across to cut and not split fibers.

4. PLANER . . . hollow ground to produce fine finish or smooth end grain. Minimizes planing and sanding.

5. PLYWOOD . . . for plywood, wallboard, masonite, light gauge non-ferrous metals, thin plastics. Fine teeth prevent tearing; hold sawdust to minimum.

6. NON - FERROUS . . . hollow ground for cutting metals such as aluminum, magnesium, copper and brass.

Blades 7 and 8 have either a ⅝" or diamond arbor hole. See table for arbor hole.

7. CARBIDE - TIPPED . . . for wood, Transite, Masonite, asbestos, Formica, composition siding, roofing. Chrome plated. Stay sharp up to 50% longer than steel-tipped blades.

8. ABRASIVE CUTTING WHEELS . . . for stone, concrete and metal. Safety reinforced nylon . . . bonded of uniform grit and break resistant.



BLADE ADAPTERS

Spindle flanges to convert arbors for blades with diamond shaped hole or for ⅝" hole.

To convert diamond arbor to 5/8" arbor for Worm Drive Saw. (Steel blades only)

Inner Adapter Catalog No.	Outer Adapter Catalog No.
48-03-2400	48-03-2450

(both required)

To convert 5/8" arbor to diamond arbor on other Saws.

Only Inner Adapter required

Catalog No. 48-03-2500

RIP FENCES

Catalog No.	For Saws
49-02-0050	Contractor and Production
49-02-0070	Worm Drive

STEEL CARRYING CASES

When ordered separately

Catalog No. 48-55-1050
For Nos. 6320, 6360, 6400

Catalog No. 48-55-1081
For Nos. 6293, 6331.

Catalog No. 48-55-1100
For No. 6370

SPECIFICATIONS

Blade Catalog No.	Blade Diam. (In.)	Number of Teeth
COMBINATION BLADES		
48-40-1653	6½	16
48-40-1655	6½	44
48-40-1722	7	18
48-40-1740	7¼	40
48-40-1752	7¼	18
48-40-1760	7½	20
48-40-1763	7½	40
48-40-1822	8¼	20
48-40-1825	8¼	44
CROSS CUT-FLOORING BLADES		
48-40-5655	6½	64
48-40-5725	7	70
48-40-5755	7¼	70
48-40-5765	7½	70
48-40-5825	8¼	80
RIP-CUT BLADES		
48-40-8654	6½	36
48-40-8724	7	30
48-40-8754	7¼	30
48-40-8764	7½	30
48-40-8824	8¼	30
PLANER BLADES*		
48-40-7656	6½	50
48-40-7661	7	55
PLYWOOD BLADES*		
48-40-4655	6½	150
48-40-4658	7	200
NON-FERROUS METAL CUTTING*		
48-40-6658	6½	80
48-40-6661	7	70

*For 6½" thru 8¼" Saws.

CARBIDE TIPPED BLADES

Catalog No.	Blade Dia. (Ins.)	Number of Teeth	Arbor Hole
48-40-3650	6½	12	⅝"
48-40-3700	7	12	⅝"
48-40-3750	7½	12	Diamond
48-40-3820	8¼	14	⅝"

ABRASIVE CUTTING WHEELS ⅛" THICK

Wheel Catalog No.	Diam. (Ins.)	Arbor Hole
For Stone or Concrete*		
49-92-3220	6	⅝"
49-92-4310	7	⅝"
49-92-4370	7¼	Diamond
49-92-5000	8	⅝"
For Metal*		
49-92-3020	6	⅝"
49-92-4300	7	⅝"
49-92-4380	7¼	Diamond
49-92-5010	8	⅝"

*For 6½" thru 8¼" Saws.

MISCELLANEOUS

Catalog No.	Description
49-48-0050	Protractor
49-96-6200	9/16" Utility Wrench
49-96-6400	13/16" Open End Wrench
49-08-0500	½ lb. Can "A" Grease
49-08-0800	1 lb. Can "A" Grease
OIL FOR WORM DRIVE SAW	
49-32-0050	½ pt. Oil
49-32-0060	1 pt. Oil
49-32-0070	½ gal. Oil

HEAVY-DUTY Milwaukee ORBITAL SANDER

for Furniture Manufacturers • Woodworkers
Carpenters • Cabinet Makers • Boat Builders

ONLY
5 LBS.

DIRECT DRIVE
NO GEARS OR BELTS

Available
With or Without
STEEL CARRYING CASE
Cat. No. 48-55-0850

SPECIFICATIONS

115 volts

Catalog No.	Orbits Per Min.	Dia. of Orbit	Over-all Size			Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
			Length	Width	Height			
WITH FELT PAD								
6000 Less Case **6001 With Case**	10,000	1/8"	10 1/4"	3 9/16"	5 3/4"	5	9 13	Yes
WITH RUBBER PAD								
6002 Less Case **6003 With Case**	10,000	1/8"	10 1/4"	3 9/16"	5 3/4"	5	9 13	Yes

Standard Equipment Includes a Package of 10 Assorted Sheets of Sandpaper. Catalog No. 49-37-0010.

HIGH SPEED . . . 10,000 ORBITS PER MINUTE

For fast, high production, satin-smooth finishing of wood, metal or plastics. Sands thin veneers without scoring, burning or tracking — no swirl marks. Lightweight for ease in handling overhead, vertically, on edges, in corners, contours or on offset surfaces. Compact design only 5 3/4" high with no protruding parts to interfere with working surface. Powerful oversize Milwaukee Built Motor. Multiple blade fan draws air around every part for cooler operation. Mechanism counter-balanced to prevent vibration. Heavy-duty 2-pole, thumb-slide switch. Three grease sealed, precision ball bearings — No further lubrication required.

ACCESSORIES

SANDPAPER

Aluminum-Oxide Open Coat Production Paper.
Size 3 2/3" x 9", 1/3 of Standard 9" x 11" Sheet.

Catalog No.	Grit	Grade	Sheets Per Pkg.
49-37-0050	50	Coarse	10
49-37-0080	80	Medium	10
49-37-0120	120	Fine	10
•49-37-0010 (Assortment)	50 80 120	Coarse Medium Fine	10 Assorted

•Same as Furnished With Each Orbital Sander.

HEAVY-DUTY Milwaukee POLISHERS

7" and 9" Diameters for Production Work

Ball and Roller Bearings

With *Exclusive*
SPRING LOADED CLUTCH DRIVE

Assures smooth running — greatly increases gear life — prevents harmful backlash.

Designed for continuous heavy-duty use. Rugged, Powerful — Perfectly balanced.



7" Dia. Cat. No. 5450 Lightweight polisher, 1750 RPM used with standard liquid polishes.

7" Dia. Cat. No. 5530 Lightweight polisher, 2800 RPM for exclusive use with high speed liquid machine polishes.

9" Dia. Cat. No. 5590 More powerful polisher, 1450 RPM. Handles the larger diameter pads and bonnets. Especially recommended for rubbing and compounding.

SPECIFICATIONS

Catalog No.	Disc Dia.	Volts	Speed No Load (RPM)	Lgth. (In.) †	Net Wgt. (Lbs)	Shp. Wgt. (Lbs)	O.S.H.A. Compliance
5450	7"	115	1750	14 1/2	9 1/4	16	Yes
5530	7"	115	2800	14 1/2	9 1/4	16	Yes
5590	9"	115	1450	15 1/4	12 3/4	20	Yes

† Over-all length of tool only—not including pad.

Furnished with each polisher is a rubber backing pad, disc nut, polishing pad and one quart of BluShel Polish.

BONNET CLEANING TOOL

Cat. No. 49-80-0050 Quickly fluffs, cleans, buffing pads and bonnets while discs are rotating. Removes glazed surface and loosens packed wool to prolong life. Shp. Wt. 1 lb.

Moulded Rubber Backing Pad

Lambswool Pad



Polishing Pad

Lambswool Bonnet

Catalog No.	Description
49-36-2500	7" dia. Moulded Rubber Pad
49-36-2200	8 1/2" dia. Moulded Rubber Pad
49-40-0160	Disc nut
49-36-1400	7 1/2" dia. Polishing Pad
49-36-1600	9" dia. Polishing Pad
49-36-0500	7" dia. Lambswool Pad
49-36-0700	9" dia. Lambswool Pad
48-48-0500	7" dia. Lambswool Bonnet
48-48-1000	9" dia. Lambswool Bonnet

Type "C" Grease 1 lb. can Catalog No. 49-08-1000

BluShel CAR POLISH

Cleans, polishes, and seals automotive finishes. Leaves a dry, brilliant finish. It is free of harmful chemicals.



Catalog No.	Description	Shp. Wgt. Lbs.
49-43-0050	1 Qt.	3
49-43-0051	12 Qt. Case	33
49-43-0060	1 Gal.	10
49-43-0061	6 Gal. Case	60

HEAVY-DUTY Milwaukee ROUTERS AND ACCESSORIES

ALL BALL BEARINGS

1 HP 8 AMPS

Catalog No. 5620

1½ HP 10 AMPS

Catalog No. 5660

MOST POWERFUL 1 and 1½ HORSEPOWER ROUTERS ON THE MARKET

MILWAUKEE Routers are engineered to meet the woodworking industry's exacting standards. They have the highest amp ratings of any routers in their class. Built for heavy-duty, continuous high production use, these tools make joinery, beading, grooving, routing, fluting and other operations simple, fast and accurate. Erickson double-angle collets are used exclusively to assure maximum bit grip and precision accuracy under toughest operating conditions. A full line of accessories and router bits are available for all types of applications.

SPECIFICATIONS

115 Volts

Catalog No.	HP	No Load Speed RPM	Collet Capacity	Sub-Base Diameter	Overall Height	Net Wgt. (lbs.)	Shp. Wgt. (lbs.)	O.S.H.A. Compliance
5620	1	23,000	¼"-⅜"	6"	8"	8	10	Yes
5660	1½	23,000	¼"-⅜"-½"	6"	8"	8½	11	Yes

STANDARD EQUIPMENT

1 HP ROUTER model 5620 includes a ¼" collet (cat. no. 48-66-0930), 2 open end wrenches (⅞" open end cat. no. 49-96-4070) and router base (cat. no. 48-10-0060).

1½ HP ROUTER model 5660 includes a ¼" collet (cat. no. 48-66-0945) and ½" collet (cat. no. 48-66-0955). 2 open end wrenches (⅞" open end, cat. no. 49-96-4475 and a 1⅛" open end cat. no. 49-96-4505) and router base (cat. no. 48-10-0060).

MOTORS ONLY

Motor for 1 HP unit
Catalog No. 5610

Motor for 1½ HP unit
Catalog No. 5650

Motors include 2 wrenches, ¼" collet (with 5610) or ¼" and ½" collets (with 5650), adjusting ring and power cord.

BASE ONLY

Bases for 1 and 1½ HP unit
Catalog No. 48-10-0060

Base includes 2 handles, sub base and wing lock nut.

ERICKSON COLLETS FOR MILWAUKEE ROUTERS

For 1 HP models 5620 and 5610
¼" Collet **Catalog No. 48-66-0930**
⅜" Collet **Catalog No. 48-66-0940**

For 1½ HP models 5660 and 5650
¼" Collet **Catalog No. 48-66-0945**
⅜" Collet **Catalog No. 48-66-0950**
½" Collet **Catalog No. 48-66-0955**

GENERAL TEMPLATE GUIDES AND HINGE BUTT GUIDE

For 1 HP and 1½ HP Routers (Includes 2 screws)



Template	Dimensions A	B	C	Catalog No.
General	5/16	1/4	3/16	**49-54-0500**
General	3/16	3/8	5/16	**49-54-0510**
General	5/16	7/16	3/8	**49-54-0520**
General	3/16	5/8	9/16	**49-54-0530**
Hinge Butt	7/16	5/8	9/16	**49-54-0550**

OPEN END WRENCHES

⅞" Wrench **Catalog No. 49-96-4070**
1⅛" Wrench **Catalog No. 49-96-4080**
(See Standard Equipment)

STEEL CARRYING CASE FOR MILWAUKEE ROUTERS

Catalog No. 48-55-0810

OUTSTANDING FEATURES

- MILWAUKEE-BUILT MOTORS The highest amp ratings of any routers in their class. They have the reserve horsepower for extra heavy-duty jobs.
- FUNCTIONAL TRIGGER-HANDLE GROUPING Textured handles, for maximum comfort and no slip gripping, permit on-off switch operation without releasing the handle.
- ACCURATE, SIMPLE DEPTH ADJUSTMENT Adjusting ring, marked in 1/64" graduations, permits friction-free operation with locking device to maintain depth-of-cut.
- OUT-OF-WAY ELECTRIC CORD Prevents cord from falling into line of cut and will not obscure vision.
- FLAT TOP FOR STEADY POSITIONING For changing bits, removing base or measuring bit for depth of cut.
- HEAVY DUTY SUB BASE With large openings for maximum visibility.



ROUTER GUIDE

Catalog No. 49-54-0200

For straight or circular cuts. Guide includes trammel point assembly for cutting circles.

VENEER TRIM KIT

Catalog No. 49-54-0300



For cutting hard plastic laminates. Comes complete with base, mounting screws, combination straight and bevel trim bit and extra nylon guide.

DOOR & JAMB BUTT TEMPLATE KIT

Catalog No. 49-54-0100

Includes carrying case, template, link rail assemblies, template nails and end gauges. Will mortise any 6'6", 6'8" or 7' door and any hinge size 2½" to 5½". Kit includes detailed instructions for proper use. Additional template nails (12 per package) are available (cat. no. 49-54-0600). Order hinge butt template guide (cat. no. 49-54-0550) separately.

CARRYING CASE ONLY

Catalog No. 48-55-0800

HEAVY-DUTY Milwaukee ROUTER BITS

HIGHEST QUALITY FOR BEST PERFORMANCE AND LONG LIFE

MILWAUKEE ROUTER BITS are a select line, made from high-speed steel, carbide tipped and solid carbide steel. Each bit has been carefully evaluated and approved for use with the new routers. Double-ground edges, consistent matching contours, high speed geometry and critical hardness control all add up to maximum accuracy and economy.



COMBINATION STRAIGHT AND 22° BEVEL TRIM BIT

Combines 22° bevel trim and flush trim cuts in one bit.

CARBIDE TIPPED

CATALOG NUMBER	A Degrees	D In.
48-23-6715	22°	1/4



7½° BEVEL TRIMMER

With pilot. For finish trim edge on plastic laminate doors, tables and furniture.

SOLID CARBIDE

CATALOG NUMBER	A Degrees	C In.	D In.
48-23-5195	7-1/2	1-5/8	1/4



FLUSH TRIM BIT

With pilot. Produces square, flush edge on plastic laminates.

SOLID CARBIDE

CATALOG NUMBER	A In.	C In.	D In.
48-23-5235	1/4	1-5/8	1/4



PROVINCIAL DESIGN VEINER BITS

Most practical for veining designs on panels, cabinet doors and furniture.

SOLID CARBIDE

CATALOG NUMBER	A In.	C In.	D In.
48-23-5295	1/8	1-1/2	1/4
48-23-5300	3/16	1-1/2	1/4



HELIX LAMINATE TRIMMERS

Designed to force the laminate against backing for chip free cuts — eliminates surface flake out. Replaceable ball bearing pilot.

CARBIDE TIPPED

CATALOG NUMBER	TYPE OF CUT	A In.	B In.	C In.	D In.
48-23-6700	Flush	3/4*	5/8	1	1/4
48-23-6710	15°	3/4*	3/8	1	1/4

*Replaceable Bearing 49-54-1050.



TWO WING SLOTTING CUTTERS

Used for slotting plywoods and core boards for "T" moldings.

CARBIDE TIPPED

CATALOG NUMBER	A In.	B In.	C In.
48-23-8000	1/16	1-7/8	5/16
48-23-8010	5/64	1-7/8	5/16
48-23-8020	3/32	1-7/8	5/16
48-23-8030	1/4	1-7/8	5/16



*Stiffening Collars included with Slotting Cutters — two each for 1/16", 5/64" and 3/32" and one for 1/4"

NOTE

USE ABOVE WITH SLOTTING CUTTER ARBOR Catalog No. 48-23-8050

Includes 1/4" shank Slotting Cutter Arbor, Nut, Washer and Bearing
Replacement Arbor Bearing No. 49-54-1080



COMBINATION PILOT PANEL BITS WITH DRILL POINTS — SINGLE FLUTE

For trimming veneer and for template panel routing.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.	E In.
48-23-1010	1/4	3/4	1-5/16	1/4	2-5/8
48-23-1015	3/8	7/8	1-5/16	3/8	3

CARBIDE TIPPED

48-23-6000	1/4	7/8	1	1/4	2-1/2
48-23-6020	3/8	1	1-1/8	3/8	3



DOWN SPIRAL PILOT PANEL BITS WITH DRILL POINTS

For cutting aluminum sheet, plywood, wall panels, insulation sheeting and other synthetic materials.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-1020	1/4	3/4	3-1/16	1/4
48-23-1025	3/8	1	3-1/2	3/8
48-23-1030	1/2	1-3/4	4-1/4	1/2



RIGHT HAND SPIRAL BIT

For trimming aluminum and non-ferrous metals.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-1500	1/4	3/4	1-1/4	1/4



PILOT PANEL BIT — SINGLE FLUTE

For trimming veneer and for template panel routing.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-1000	1/4	3/4	1-5/16	1/4

STRAIGHT BITS — TWO FLUTES

For all general purpose routing (rabbeting, grooving, dadoing, etc.). Smooth finish cuts. Use long shank bits where nature of cut requires longer shank extension.



HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-0050	1/4	5/8	1	1/4
48-23-0055	1/4	1-1/8	1-3/16	1/4
48-23-0060	5/16	3/4	1	1/4
48-23-0065	5/16	1-1/8	1-3/16	1/4
48-23-0070	3/8	11/16	1	1/4
48-23-0110	3/8	1-1/8	1-1/4	3/8
48-23-0125	3/8	1-1/8	1-7/16	1/2
48-23-0075	7/16	11/16	1	1/4
48-23-0080	1/2	3/4	1	1/4
48-23-0130	1/2	1-1/8	1-7/16	1/2
48-23-0140	1/2	2	2	1/2
48-23-0085	9/16	5/8	1	1/4
48-23-0090	5/8	5/8	1	1/4
48-23-0145	5/8	1-1/8	1-7/16	1/2
48-23-0095	11/16	5/8	1	1/4
48-23-0100	3/4	5/8	1	1/4
48-23-0150	3/4	1-1/8	1-7/16	1/2
48-23-0155	13/16	1-1/8	1-7/16	1/2
48-23-0160	7/8	1-1/8	1-7/16	1/2
48-23-0170	1	1-1/8	1-7/16	1/2

CARBIDE TIPPED

48-23-5055	1/4	3/4	1	1/4
48-23-5056	1/4	1	1	1/4
48-23-5105	1/4	3/4	1	3/8
48-23-5065	5/16	1	1-1/16	1/4
48-23-5070	3/8	1	1-1/16	1/4
48-23-5110	3/8	1-1/4	1	3/8
48-23-5126	3/8	1	1-1/4	1/2
48-23-5080	1/2	1	1-1/16	1/4
48-23-5115	1/2	1	1	3/8
48-23-5141	1/2	1-1/4	1-1/4	1/2
48-23-5142	1/2	2	1-3/4	1/2
48-23-5090	5/8	3/4	1-1/16	1/4
48-23-5100	3/4	3/4	1-1/16	1/4
48-23-5150	3/4	3/4	1-1/4	1/2

STRAIGHT BITS — SINGLE FLUTE

For all general purpose routing (rabbeting, grooving, dadoing, etc.). Fast rough cuts. Use long shank bits where nature of cut requires longer shank extension.



HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-0010	1/16	3/16	1	1/4
48-23-0015	1/8	5/16	1	1/4
48-23-0035	1/8	5/8	1-3/16	1/4
48-23-0020	5/32	3/8	1	1/4
48-23-0025	3/16	7/16	1	1/4
48-23-0040	3/16	3/4	1-3/16	1/4
48-23-0030	7/32	7/16	1	1/4
48-23-0045	1/4	1	1-3/16	1/4
48-23-0046	3/8	1-1/8	1-3/16	3/8

CARBIDE TIPPED

48-23-5025	3/16	3/8	1-1/16	1/4



STAGGER TOOTH STRAIGHT BIT

Excellent for cut outs. This design gives the bit two flute balance with single flute cutting speed.

CARBIDE TIPPED

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-5143	1/2	2	1-1/2	1/2



HINGE MORTISING BITS

Fast cutting bit for making mortises when cut is started from edge of work.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-1100	3/8	7/16	1-1/8	1/4
48-23-1110	7/16	3/8	1-1/8	1/4
48-23-1120	1/2	13/32	1-1/8	1/4
CARBIDE TIPPED				
48-23-6100	1/2	5/16	1-7/32	1/4



CORE BOX BITS — TWO FLUTES

Especially effective in fluting flat surfaces (mantels and facades).

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-0200	1/4	1/4	1	1/4
48-23-0205	5/16	1/4	1	1/4
48-23-0210	3/8	1/4	1	1/4
48-23-0215	7/16	1/4	1	1/4
48-23-0220	1/2	11/32	1	1/4
48-23-0225	9/16	3/8	1	1/4
48-23-0230	5/8	3/8	1	1/4
48-23-0235	11/16	7/16	1	1/4
48-23-0240	3/4	15/32	1	1/4



DOVETAIL BITS

For making dovetail.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-1300	9/32	3/8	1-1/4	1/4
48-23-1310	9/16	17/32	1-3/32	1/4



RABBETING BITS

With pilot. For making rabbeting cuts without use of router guide. Carbide tip bit has replaceable ball bearing pilot.

HIGH SPEED STEEL

CATALOG NUMBER	RABBET DEPTH In	A In.	B In.	C In.	D In.	E In.
48-23-1400	1/4	11/16	7/16	1	1/4	3/16
48-23-1410	3/8	15/16	1/2	1	1/4	3/16
CARBIDE TIPPED						
48-23-6400	3/8	1-1/4	1/2	1-1/2	1/4	*

*REPLACEMENT BALL BEARING 49-54-1060... By substituting Bearing 49-54-1070, rabbet depth can be increased to 1/2".



V-GROOVING BITS

Excellent for lettering and sign work.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-0600	3/8	9/1/6	1	1/4
48-23-0610	7/8	1-1/4	1	1/4



CHAMFERING BITS — TWO FLUTES

With pilot. For decorative edging and making concealed joints. Carbide tip bit has replaceable ball bearing pilot.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	C In.	D In.	E In.
48-23-1200	1/2	1	1/4	3/16
CARBIDE TIPPED				
48-23-6200	5/8	1	1/4	*

*Replaceable Bearing 49-54-1090.



CORNER ROUNDING BITS

With pilot. For decorative edging and for drop leaf table joints. Carbide tip bits have replaceable ball bearing pilot.

HIGH SPEED STEEL

CATALOG NUMBER	A In. Radius	C In.	D In.	E In.
48-23-0400	3/16	1	1/4	3/16
48-23-0410	1/4	1	1/4	3/16
48-23-0420	5/16	1	1/4	3/16
48-23-0430	3/8	1	1/4	3/16
48-23-0440	1/2	1	1/4	3/16
CARBIDE TIPPED				
48-23-5410	1/4	1	1/4	*
48-23-5430	3/8	1	1/4	*

*Replaceable Bearing 49-54-1060... Converts to Beading Bit by substituting Bearing No. 49-54-1070.



COVE BITS — TWO FLUTES

With pilot. For decorative edging and for drop leaf table joints.

HIGH SPEED STEEL

CATALOG NUMBER	A In. (Radius)	B In.	C In.	D In.	E In.
48-23-0300	3/16	3/8	1	1/4	3/16
48-23-0310	1/4	1/2	1	1/4	3/16
48-23-0320	3/8	5/8	1	1/4	3/16
48-23-0330	1/2	3/4	1	1/4	3/16



BEADING BITS — TWO FLUTES

With pilot. For decorative furniture. Pilot guides router along edge of work. Carbide tip bits have replaceable ball bearing pilot.

HIGH SPEED STEEL

CATALOG NUMBER	A Radius	B In.	C In.	D In.	E In.
48-23-0500	1/16	3/16	1	1/4	3/16
48-23-0510	1/8	3/8	1	1/4	3/16
48-23-0520	1/4	1/2	1	1/4	3/16
48-23-0530	3/8	3/4	1	1/4	3/16
CARBIDE TIPPED					
48-23-5520	1/4	1/2	1	1/4	*
48-23-5530	3/8	5/8	1	1/4	*

*Replaceable Bearing 49-54-1070... Converts to Corner Rounding Bit by substituting Bearing 49-54-1060.



ROMAN OGEE BITS

With pilot. For decorative furniture. Pilot guides router along edge of work.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.	E In.	F In.
48-23-0800	5/32	1/2	1	1/4	3/16	15/16
48-23-0810	1/4	3/4	1	1/4	3/16	1-3/16



VEINING BITS — SINGLE FLUTE

For decorative line work on any flat surface.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.
48-23-0700	1/8	5/16	1	1/4
48-23-0710	3/16	7/16	1	1/4
48-23-0720	7/32	7/16	1	1/4



OGEE BITS

For decorative cuts. Clamp straight edge or template on the work and use as a guide for the outside edge of router base.

HIGH SPEED STEEL

CATALOG NUMBER	A In.	B In.	C In.	D In.	E In.	F In.
48-23-0900	3/16	5/8	1	1/4	3/16	13/16
48-23-0910	9/32	29/32	1	1/4	3/16	1-3/16

HEAVY-DUTY Milwaukee SPECIAL SCREW-SHOOTERS

FOR DRIVING SELF-DRILLING, SELF-TAPPING TEKS® FASTENERS.

TEKS® registered trade mark of Illinois Tool Works Inc

WITH POSITIVE DRIVE CLUTCH

CATALOG NO. 6798-1 REVERSING

With Non-Marring Locators
And Trigger Speed Control 0-2500 RPM

Positive Drive Clutch model is specifically engineered for fast, precision driving of self-drilling, self-tapping fasteners in steel, brass, bronze, aluminum and stainless. Also for fastening wood or other compressible materials to metal. Positive clutch engages when pressure is applied. Driving action stops and clutch disengages when pressure is released or when locator contacts work surface. Clutch jaws are milled at precise angles, assuring positive driving action. Depth control is adjustable in increments of 1/64" from outside of tool.

CAPACITY

¼" in 3/16" Cold Rolled Steel or No. 12 in ½" Cold Rolled Steel.

- **Powerful 4.5 amp motor**
- **Conveniently located Reversing Switch**
- **New, simple one hand depth adjustment**

SPECIFICATIONS — 115 Volts 60 Cycle AC Only

Catalog No.	RPM No Load	Bit Shank Size	Spindle Offset	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
6798-1 Rev.	0 to 2500	¼" Hex	¾"	9½	3¾	7	Yes

"Rev." after Catalog No. indicates reversing type motor. Equipped with lockable trigger switch.

WITH ADJUSTABLE TORQUE CLUTCH

CATALOG NO. 6783-1 REVERSING

With Exclusive Bit Guides
And Trigger Speed Control 0-2500 RPM

Milwaukee's Adjustable Torque Clutch model is a completely *new concept* for driving self-drilling, self-tapping fasteners. A simple "pull and turn" torque adjusting ring is the only adjustment required for fast accurate screwdriving. Clutch disengages and driving action stops when pre-set torque is reached. Another big plus feature is the powerful 4.5 amp motor.

CAPACITY

¼" in 3/16" Cold Rolled Steel or No. 12 in ½" Cold Rolled Steel.

- **New, powerful 4.5 amp motor**
- **Conveniently located Reversing Switch**
- **New Adjustable Clutch Mechanism**
- **New, exclusive Bit Guide System**
- **High Torque and RPM**

SPECIFICATIONS — 115 Volts 60 Cycle AC Only

Catalog No.	RPM No Load	Bit Shank Size	Spindle Offset	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
6783-1 Rev.	0 to 2500	¼" Hex	¾"	10¼	4½	8	Yes

"Rev." after Catalog No. indicates reversing type motor. Equipped with lockable trigger switch.



SIMPLIFIED ADJUSTABLE TORQUE RELEASE CLUTCH

Torque output is easily changed externally by turning adjusting ring. Locking collar positively holds setting.

Type "A" Grease
½ lb. can **Cat. No. 49-08-0500**
1 lb. can **Cat. No. 49-08-0800**

For Steel Carrying Case See page 10

BIT HOUSING & LOCATORS FOR 6798-1 POSITIVE DRIVE

HEX HEAD SCREWS — USING SOCKET & DRIVER



Hex. Size	Bit Housing	Locator Assembly	Socket Driver	Magnetic Socket	Non-Mag. Socket
¼"	Cat. No. 48-32-2500	49-26-0250	¼" Sq. x 2" Long 48-32-2050	49-66-3000	49-66-3001
5/16"		49-26-0312		49-66-3010	49-66-3011
3/8"		49-26-0375		49-66-3020	49-66-3021
7/16"		49-26-0600		49-66-3030	

HEX HEAD SCREWS — USING ONE PIECE EXTENSIONS



Hex. Size	Bit Housing	Locator Assembly	Socket Ext.-Magnetic	Socket Ext.-Non-Mag.
¼"	Cat. No. 48-32-2500	49-26-0250	49-66-3006	49-66-3005
5/16"		49-26-0312	49-66-3016	49-66-3015
3/8"		49-26-0375	49-66-3026	49-66-3025

PHILLIPS, POSIDRIV® AND ROBERTSON SCREWS



Type of Set-Up	Bit Housing	Locator Assembly	Bit Holder	Insert Bits
Magnetic	Cat. No. 48-32-2500	49-26-1000	48-32-3025	Select Bits with Key Letters S, T, or X
Non-Mag.		49-26-0250	49-32-3050	

NOTE: For Slotted Frearson, and Clutch Head Screws, use accessories as shown for Model 6543-1, Page 39. See Page 40 for special Mobile Home Kit.

Supplied With Tool. 5/16" Hex Magnetic Socket, ¼" Sq. x 2" Socket Driver and ¼", 5/16", 3/8" and 7/16" Locators. See Page 41, for complete bit and socket illustrations and specs.

BIT GUIDES FOR 6783-1 ADJUSTABLE TORQUE

HEX HEAD SCREWS — USING SOCKET & DRIVER



Hex. Size	Bit Guide	Socket Driver	Magnetic Socket	Non-Mag. Socket
¼"	48-32-0250	¼ Sq. x 2" Long 48-32-2050	49-66-3000	49-66-3001
5/16"	48-32-0312		49-66-3010	49-66-3011
3/8"	48-32-0375		49-66-3020	49-66-3021

HEX HEAD SCREWS — USING ONE PIECE EXTENSIONS

Hex. Size	Bit Guide	Magnetic Extension	Non-Mag. Extension
¼"	48-32-0250	49-66-3006	49-66-3005
5/16"	48-32-0312	49-66-3016	49-66-3015
3/8"	48-32-0375	49-66-3026	49-66-3025

PHILLIPS, POSIDRIV®, FREARSON, ROBERTSON, CLUTCH HEAD AND HEX SOCKET SCREWS



Type of Set-Up	Bit Guide	Bit Holder	Insert Bits
Magnetic	48-32-0608	48-32-3025	Select any Insert Bit
Non-Magnetic	48-32-0250	48-32-3050	

NOTE: For Slotted Screws and Hex Nuts, use accessories as shown for Model 6583-1, Page 39.

Supplied With Tool. 5/16" Hex Magnetic Socket, ¼" Sq. x 2" long Socket Driver and ¼", 5/16", and 3/8" Bit Guides. See Page 41 for complete bit and socket illustrations and specs.

WOOD SCREWS

WITH POSITIVE DRIVE CLUTCH

CATALOG NO. 6543-1 REVERSING
With Trigger Speed Control

Positive Clutch Drive Unit is compact, lightweight and powerful for use in wood and other resilient materials where there is a varied resistance in density and hardness. Clutch engages when pressure is applied and stops when pressure is released. Torque is maintained while pressure is applied. New exclusive Snap-in bit guide design provides maximum support, greatly reducing bit wobble.

CAPACITY

Soft wood with pilot hole — to 5/16" Lag.
Soft wood without pilot hole — to #16
Hard wood with pilot hole — to #16
Hard wood without pilot hole — to #12

- **Powerful 4.5 amp motor**

SPECIFICATIONS 115 Volts 60 Cycle AC Only

Catalog No.	RPM No Load	Bit Shank Size	Spindle Offset	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
6543-1 Rev.	0 to 1000	1/4" Hex	3/4"	9 3/4	4 1/2	7	Yes

"Rev." after Catalog No. indicates reversing type motor. Equipped with lockable trigger switch.

MACHINE AND SHEET METAL SCREWS AND NUTS

WITH ADJUSTABLE TORQUE CLUTCH

CATALOG NO. 6583-1 REVERSING
With Trigger Speed Control

Milwaukee Adjustable clutch mechanism offers optimum torque control by a simple "pull and turn" adjusting ring. Ideally suited for driving machine and sheet metal screws and nuts. Once adjusted, uniform torque is maintained when driving screws or nuts of the same size in materials of uniform density. Clutch automatically disengages when screw or nut is set. Powerful 4.5 amp motor with 0 to 1000 rpm speed control offers continuous control from start to finish.

CAPACITY

Tapping screws — to 1/4" in 3/16" mild steel
Machine screws and nuts —to 1/4"

- **New Adjustable Clutch Mechanism**
- **Smoother, quieter Helical Gear Train**
- **Improved Fan and Baffle System**
- **High Torque 4.5 amp motor**

SPECIFICATIONS 115 Volts 60 Cycle AC Only

Catalog No.	RPM No Load	Bit Shank Size	Spindle Offset	Lgth. (In.)	Net (Lbs.) Wgt.	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
6583-1 Rev.	0 to 1000	1/4" Hex	3/4"	10 1/4	5	7 1/2	Yes

"Rev." after Catalog No. indicates reversing type motor. Equipped with lockable trigger switch.

TRIGGER SPEED CONTROL REVERSING SWITCH

Complete operating speed control in forward and reverse is provided for models 6543-1, 6583-1, 6783-1 and 6798-1 by this solid state speed control reversing switch. Increasing or decreasing pressure on the trigger controls the amount of drilling or reversing speed from zero to maximum RPM. Reversing lever, located directly above trigger, is provided with a mechanical interlock to prevent accidental reversing when motor is running.

Type "A" Grease
1/2 lb. can **Cat. No. 49-08-0500**
1 lb. can **Cat. No. 49-08-0800**

For Steel Carrying Case See page 10

BIT GUIDE HOUSING & BIT GUIDES FOR 6543-1 POSITIVE DRIVE

SLOTTED SCREWS



Screw Size	Bit Guide Housing	Bit Guide	Bit and Finder Combination
6F-8R	Cat. No. 48-32-1000	48-32-0608	48-30-2600
8F-10R		48-32-0810	48-30-2625
10F-12R		48-32-1012	48-30-2650
12F-14R		48-32-1214	48-30-2675
14F-16R		48-32-1416	48-30-2700

NOTE:
F = Flat Head
R = Round Head

PHILLIPS, POSIDRIV®, FREARSON, ROBERTSON, CLUTCH HEAD AND HEX SOCKET SCREWS



Type of Set-Up	Bit Guide Housing	Bit Guide	Bit Holder	Insert Bits
Magnetic	Cat. No. 48-32-1000	48-32-0608	48-32-3025	Select any Insert Bit
Non-Mag.		48-32-0250	48-32-3050	

HEX HEAD SCREWS



Hex. Size	Bit Guide Housing	Bit Guide	Socket Driver	Magnetic Socket	Non-Mag. Socket
1/4"	Cat. No. 48-32-1000	48-32-0250	1/4 Sq. x 2" Long	49-66-3000	49-66-3001
5/16"		48-32-0312		49-66-3010	49-66-3011
3/8"		48-32-0375	48-32-2050	49-66-3020	49-66-3021

NOTE: For Hex Nuts or Hex Head Screws, using one piece extensions, use accessories as shown for Model 6583-1 (below), plus Bit Guide Housing, Cat. No. 48-32-1000.

Supplied With Tool. Non-Magnetic Bit Holder and 1/4" Bit Guide. All bits must be purchased separately. See Page 41 for complete bit and socket illustrations and specs.

BIT GUIDES FOR 6583-1 ADJUSTABLE TORQUE

SLOTTED SCREWS

Screw Size	Bit Guide	Bit and Finder Combination
6F-8R	48-32-0608	48-30-2600
8F-10R	48-32-0810	48-30-2625
10F-12R	48-32-1012	48-30-2650
12F-14R	48-32-1214	48-30-2675
14F-16R	48-32-1416	48-30-2700



NOTE:
F = Flat Head
R = Round Head

PHILLIPS, POSIDRIV®, FREARSON, ROBERTSON, CLUTCH HEAD AND HEX SOCKET SCREWS



Type of Set-Up	Bit Guide	Bit Holder	Insert Bits
Magnetic	48-32-0608	48-32-3025	Select any Insert Bit
Non-Magnetic	48-32-0250	48-32-3050	

HEX NUTS (SOCKETS HAVE BOLT CLEARANCE)



Hex. Size	Bit Guide	Socket Driver	Magnetic 2" Lg. Nut Socket
1/4"	48-32-0312	1/4" Sq. x 2" Lg. 48-32-2050	49-66-3002
5/16"	48-32-0810		49-66-3012
3/8"	48-32-1012		49-66-3022

NOTE: For Hex Head Screws, use accessories as shown for Model 6783-1, Page 38.

Supplied With Tool. Non-Magnetic Bit Holder and 1/4" Bit Guide. All bits must be purchased separately. See Page 41 for complete bit and socket illustrations and specs.

HEAVY-DUTY Milwaukee DRYWALL SCREW-SHOOTERS

BOTH WITH

- **Positive Drive Clutch**
- **4.5 Amp Motors**
- **Non-marring Locators**

CATALOG NO. 6747-1 REVERSING

High Speed
CATALOG NO. 6751-1 REVERSING

Minimum Offset for Close Quarter Work
Simple, Positive, Depth Adjustment

For driving screws flush or "dimple sinking" when installing panels on metal or wood studs. Drives to exact depth without marring or damaging panels — makes cementing and final finishing easier. Magnetic bit holder holds drywall screws to insert bit. Reversing switch allows easy removal of screws. Positive lock adjustment provides a wide range of depth settings. New, simplified, one hand adjustment. Push Locking Collar forward and rotate it to right or left. Each ¼ turn equals 1/64" change in depth. New light-weight nose assembly is permanently lubricated and will not rust or corrode.

ACCESSORIES

2 PC. MAGNETIC BIT HOLDER
Cat. No. 48-32-3030
NOSE END ONLY FOR ABOVE
Cat. No. 48-32-3035

¼" HEX PHILLIPS INSERT BITS
#1 Cat. No. 48-32-1030
#2 Cat. No. 48-32-1050

¼" HEX INSERT SOCKETS
Magnetic
Cat. No. 49-66-0800
Non-Magnetic
Cat. No. 49-66-0750

¼" HEX MAGNETIC BIT HOLDER
Cat. No. 48-32-3025

LOCATOR TIP
Cat. No. 49-78-0100
Replacement insert for Drywall Locator
Cat. No. 49-26-1000
For use on extremely abrasive material or metal lath. Easily removable for non-marring applications.

BIT HOUSING
Catalog No. 48-32-2500



LOCATOR SLEEVE FOR MAGNETIC BIT HOLDER
Cat. No. 49-26-1000

CONVERSION KIT Catalog No. 49-22-1520 Non marring nose assembly fits previous Milwaukee Drywall Screwdrivers. Consists of Bit Housing No. 48-32-2500 and Locator Sleeve No. 49-26-1000.

SPECIFICATIONS

115 Volt 60 Cycle AC Only

Catalog No.	RPM No Load	Bit Shank Size	Spindle Offset	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
6747-1 Rev.	2500	¼" Hex.	¾"	10¼	4	7	Yes
6751-1 Rev.	4000						Yes

"Rev." after Catalog No. indicates reversing type motor. Both models are equipped with lockable trigger switches.

Supplied With Both Tools. #2 Phillips Bit, Magnetic Bit Holder and Magnetic Bit Holder Locator.

NOTE: 25 ft. cord available for all MILWAUKEE Screw-Shooters. See your local MILWAUKEE Branch office or Service Station.

For Steel Carrying Case See page 10

Type "A" Grease ½ lb. can Catalog No. 48-08-0500
1 lb. can Catalog No. 48-08-0800

HEAVY-DUTY Milwaukee NO-HUB SCREW-SHOOTER

NEW

Trigger-Speed Control-Reversing Catalog No. 6584-1

- **Factory pre-set clutch assures 60" lbs. of torque for fool-proof tightening**
- **Nose piece is easy to remove for getting into tight work.**
- **Trigger speed control reversing switch.**

FAST INSTALLATION OF NO-HUB COUPLINGS

New No-Hub Driver tightens no-hub couplings *10 times faster* than hand wrench methods . . . plus gives you these extra benefits: Greater torque accuracy. Trigger-speed control with reversing. Powerful 4.5 amp motor. Pre-Set clutch. Heavy-duty ball and roller bearing construction for long trouble-free service. Suitable for many other driver applications.

SPECIFICATIONS

115 Volt 60 Cycle AC Only

Catalog No.	RPM No Load	Bit Shank Size	Spindle Offset	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
6584-1 Rev.	0 to 1000	¼" Hex.	¾"	10½	5	7½	Yes

Equipped with lockable trigger switch.

Supplied With Tool. 5/16" Hex Non-Magnetic Socket Extension and 5/16" Bit Guide.

ACCESSORIES

Type "A" Grease
½ LB. CAN **Catalog No. 49-08-0500**
1 LB. CAN **Catalog No. 49-08-0800**

For Steel Carrying Case See page 10



LEATHER HOLSTER
FOR PISTOL DRILLS and SCREWDRIVERS
Fits belts to 3" wide.
CAT. NO. 49-17-0200

NEW

MOBILE HOME KIT **Cat. No. 49-22-1530**

Kit consists of Bit Guide Housing, 5/32" x 2¾" Clutch Head Bit and Clutch Head Finder Assembly.

BIT GUIDE HOUSING
Cat. No. 48-32-1000



5/32" x 2¾" CLUTCH HEAD BIT
Cat. No. 48-30-1145



CLUTCH HEAD FINDER ASSEMBLY
Cat. No. 48-30-2500

Fits the following list of MILWAUKEE Screw-Shooters for use with clutch head screws:

Model 6747-1*	2500 RPM	Positive Drive
6798-1	0-2500 RPM	Positive Drive
6543-1	0-1000 RPM	Positive Drive
6751-1	4000 RPM	Positive Drive

*Recommended

Kit also fits Adjustable Torque Models 6583-1 and 6783-1 and discontinued Positive Drive Models 6745-1, 6746-1 and 6796-1.

HEAVY-DUTY Milwaukee SCREW-SHOOTER ACCESSORIES

SCREW-SHOOTER NOSE PIECE ASSEMBLIES

A — BIT GUIDE HOUSING

B — SHORT BIT GUIDE

C — LONG BIT GUIDE

Milwaukee's Exclusive Bit Guides Provide Wobble-Free Screwdriving



D — BIT HOUSING



E — LOCATOR



F — MAGNETIC BIT HOLDER LOCATOR

Milwaukee Locators Provide Wobble-Free Screwdriving — Plus Depth Adjustments

Key	Description	Catalog No.	For Use With Driver			
A	Bit Guide Housing	48-32-1000	6543-1	6747-1	6751-1	6798-1
B1	1/4" Bit Guide	48-32-0250	ALL MODELS			
B2	5/16" Bit Guide	48-32-0312				
B3	3/8" Bit Guide	48-32-0375	ALL EXCEPT 6751-1			
C1	6F-8R Bit Guide	48-32-0608	ALL MODELS			
C2	8F-10R Bit Guide	48-32-0810	ALL EXCEPT 6751-1			
C3	10F-12R Bit Guide	48-32-1012				
C4	12F-14R Bit Guide	48-32-1214				
C5	14F-16R Bit Guide	48-32-1416				
D	Bit Housing	48-32-2500	6543-1	6747-1	6751-1	6798-1
E1	1/4" Locator	49-26-0250	6543-1	6747-1	6751-1	6798-1
E2	5/16" Locator	49-26-0312	6543-1	6747-1	6751-1	6798-1
E3	3/8" Locator	49-26-0375	6543-1	6747-1		6798-1
E4	7/16" Locator	49-26-0600	6543-1	6747-1		6798-1
F	Mag. Bit Holder Loc.	49-26-1000	6543-1	6747-1	6751-1	6798-1

SCREWDRIVING ACCESSORIES



When Ordering, Use Catalog Numbers

BIT HOLDERS • SOCKETS • EXTENSIONS • BITS and FINDERS

Key	Description	Size	Catalog No.	For Use With
G	Magnetic Bit Holder		48-32-3025	F or C1
H	2-Pc. Mag. Bit Holder		48-32-3030	F or C1
I	Bit Holder Nose End (for H)		48-32-3035	H
J	Non-Mag. Bit Holder		48-32-3050	E1 or B1
K	1/4" Sq. x 2" Socket Driver		48-32-2050	L-M-N
L1	Hex. Sockets Only Non-Magnetic	1/4"	49-66-3001	K & E1 or B1
L2		5/16"	49-66-3011	K & E2 or B2
L3		3/8"	49-66-3021	K & E3 or B3
M1	Hex Sockets Only Magnetic	1/4"	49-66-3000	K & E1 or B1
M2		5/16"	49-66-3010	K & E2 or B2
M3		3/8"	49-66-3020	K & E3 or B3
M4		7/16"	49-66-3030	K & E4
N1	2" Lg. Hex Nut Magnetic Sockets With Bolt Clearance	1/4"	49-66-3002	K & B2
N2		5/16"	49-66-3012	K & C2
N3		3/8"	49-66-3022	K & C3
O1	1 Pc. Hex Socket Extension Non-Magnetic	1/4"	49-66-3005	E1 or B1
O2		5/16"	49-66-3015	E2 or B2
O3		3/8"	49-66-3025	E3 or B3
P1	1 Pc. Hex Socket Extension Magnetic	1/4"	49-66-3006	E1 or B1
P2		5/16"	49-66-3016	E2 or B2
P3		3/8"	49-66-3026	E2 or B3
Q1	Bit and Finder Combinations (Slotted Screws) 3 1/2" long	6F-8R	48-30-2600	C1
Q2		8F-10R	48-30-2625	C2
Q3		10F-12R	48-30-2650	C3
Q4		12F-14R	48-30-2675	C4
Q5		14F-16R	48-30-2700	C5
R1	Replacement Bits for Bit and Finder Combinations 3 1/2" long	6F-8R	48-30-0750	Q1
R2		8F-10R	48-30-0770	Q2
R3		10F-12R	48-30-0790	Q3
R4		12F-14R	48-30-0800	Q4
R5		14F-16R	48-30-0805	Q5

When Ordering, Use Catalog Numbers

INSERT BITS

Key	Description	Size	Catalog No.	For Use With
S1	Phillips 1" long	#1	48-32-1030	G, H or J
S2		#2	48-32-1050	
S3		#3	48-32-1070	
T1	Posidriv® 1" long	#1	48-32-1120	
T2		#2	48-32-1125	
T3		#3	48-32-1130	
U1	Frearson (Reed & Prince) 1 1/8" long	#1	48-32-1110	
U2		#2	48-32-1115	
V1	Clutch Head Insert Bits 1 1/4" long	3/32"	48-32-1135	
V2		1/8"	48-32-1140	
V3		5/32"*	48-32-1145	
V4		3/16"	48-32-1150	
V5		1/4"	48-32-1155	
W1	Hex Socket Insert Bits 1" long	5/64"	48-32-1160	
W2		3/32"	48-32-1165	
W3		7/64"	48-32-1170	
W4		1/8"	48-32-1175	
W5		9/64"	48-32-1180	
W6	Hex Socket Insert Bits 1 15/16" long	5/32"	48-32-1185	
W7		3/16"	48-32-1190	
W8		7/32"	48-32-1195	
W9		1/4"	48-32-1200	
X1	Square Drive (Robertson) 1" long	#1	48-32-1205	
X2		#2	48-32-1210	
X3		#3	48-32-1215	
Y1	Slotted Screw Insert Bits 1 1/2" long	6F-8R	48-32-0050	It is Recommended Slotted Screws Be Driven With Q1 thru Q5
Y2		8F-10R	48-32-0060	
Y3		10F-12R	48-32-0070	
Y4		12F-14R	48-32-0080	
Y5		14F-16R	48-32-0090	

*See page 40 for 5/32" Clutch Head Mobile Home Kit.

ACCESSORIES FOR PREVIOUS MILWAUKEE 1/4" HEX SHANK DRIVERS

1 15/16" Long Bits For Slotted Head Screws

BIT

FINDER

Screw Size	Bit Only Catalog No.	Finder Catalog No.
6F-8R	48-30-0500	48-30-2025
8F-10R	48-30-0505	48-30-2050
10F-12R	48-30-0510	48-30-2075
12F-14R	48-30-0515	48-30-2100

2" Long Phillips Bits

PHILLIPS BIT

#2 Catalog No. 48-30-1520
#3 Catalog No. 48-30-1500

HEAVY-DUTY Milwaukee IMPACT WRENCHES

Rugged Design • No Kickback or Twist • Runs Continuously with Constant Torque

Catalog No. 9051
½" SQUARE DRIVE
with Ball Detent

Square Drive — ½". The finest, most powerful impact wrench of its size for setting, running or removing bolts, nuts, studs and screws . . . also taps, threads, rethreads, drills and reams. Highest quality components include unit thrust bearings for spring and impact mechanism, chrome alloy steel balls and multiple planet gear system. Anvil, hammer and planetary gear cage are forged from selected alloy steel and heat treated for heavy-duty service. Forward and reverse rotation is achieved by turning rear end-cap. Brushes shift automatically for best commutation and efficiency.

IMPACT WRENCH KIT
Catalog No. 9056

Convenient ½" Impact Wrench Kit is complete with compact carrying case and an assortment of ½" hex drive sockets. Catalog No. 9056 ½" Impact Wrench Kit includes: 9051 Impact Wrench, 49-66-3080 ½" Hex Socket, 49-66-3090 9/16" Hex Socket, 49-66-3100 5/8" Hex Socket, 49-66-3110 11/16" Hex Socket, 49-66-3120 ¾" Hex Socket, 49-66-3130 13/16" Hex Socket, 48-55-2580 Steel Carrying Case.

Catalog No. 9070
¾" SQUARE DRIVE
with Pin and
Ring Retainer

Square Drive — ¾" Perfect balance for fatigue-free use and plenty of power make this tool ideal for steel erection, equipment maintenance and other heavy-duty industrial applications. This tool has the same basic high quality impact mechanism as the Cat. No. 9051 plus an increased torque range.

Catalog No. 9060
5/8" QUICK CHANGE CHUCK

Quick-Change 5/8" hex recess chuck. Perfect for installing utility pole hardware, attaching guy wire clamps and pole steps. Use wood augers with integral 5/8" hex shanks from 7/16" thru 1 1/16". Easy to operate end-cap for reversing rotation allows safe bit removal. Also valuable for general construction, marine installations, boat building and pre-fab construction. Quick-Change chuck makes changing of augers and sockets possible on job site without additional tools.

HEAVY-DUTY ½" SQUARE DRIVE IMPACT HEX SOCKETS

Single broached, standard length, Specially made for Impact Wrench.

Size	Catalog No.
7/16"	49-66-3070
1/2"	49-66-3080
9/16"	49-66-3090
5/8"	49-66-3100
11/16"	49-66-3110
3/4"	49-66-3120
13/16"	49-66-3130
7/8"	49-66-3140

IMPACT WRENCH SPECIFICATIONS

Catalog No.	Impacts Per Min.	No Load RPM	Torque Range	Volts	Length	Net Wt.	Shpg. Wt.	O.S.H.A. Compliance
9051	1900	1900	95—130	115	10¼	6¼	9¼	Yes
9056 KIT	1900	1900	95—130	115	10¼	13	16	Yes
9060	1725	1700	175—250	115	11⅞	10	13	Yes
9070	1725	1700	175—250	115	11⅞	10	13	Yes

½" SQUARE DRIVE IMPACT WRENCH ACCESSORIES

UNIVERSAL JOINT
No. 48-03-0500
Fits ½" Square Drive and used with Hex Sockets to reach difficult places at various angles . . . also allows clearance around obstructions.

TOOL HANGER
No. 49-17-0220
Adapts to Impact Wrench models 9051, 9060 and 9070

EXTENSION BAR
No. 48-95-5000
Adapts to ½" Square Drive. Provides 5" additional length where required for use with sockets or other accessories.

KEYLESS CHUCK
No. 48-66-0010
Adapts to ½" Square Drive with capacity for accessories with 1/8" to ½" diameter shanks.

QUICK CHANGE CHUCK
No. 48-66-0060
With 7/16" Hex Socket for Screw Driver Bits and hole saws or other accessories with 7/16" Hex Shanks. See page 12 for hole saws.

COLLET CHUCK
No. 48-66-0050
For round shank tools, drills and reamers 3/16" to 3/8" diameter . . . also taps and E-Z outs No. 10 to ½". Two wrenches are included.

OPEN END WRENCH No. 49-96-4680
Included and used with Collet Chuck No. 48-66-0050

CARRYING CASE FOR 9051 ONLY
No. 48-55-2580

SPECIAL LUBRICANT No. 49-08-0100
For mechanism — 3½ oz. tube.

HEAVY-DUTY Milwaukee DIE GRINDER and STRAIGHT GRINDER

ALL BALL BEARINGS

Die Finishing and Polishing
Removal of Thin Layers of Material
Production Grinding of Small Parts

Durable, Easy to Operate
Ball Bearings Lubricated for Life
Extended Spindle Grips Close to Stones
Powerful Ventilating Fan Keeps Motor Cool

CATALOG NO. 5191
DIE GRINDER

Milwaukee's Die Grinder is designed for the tool and die trade, pattern and model making and other trades requiring precision heavy-duty applications. Internal grinding, deburring and filing are some of the more specific uses. Standard equipment includes a ¼" collet. A ⅛" collet is available as an accessory. The 34,000 RPM no load speed can be used with high strength non-reinforced organic wheels to 1" diameter and with reinforced wheels to 1½" diameter.

CATALOG NO. 5265
STRAIGHT GRINDER

General Purpose Grinding

- **For Use With:**
- **Abrasive Wheels**
- **Rotary Files**
- **Carbide Burrs**

The Milwaukee Straight Grinder's rugged construction coupled with rigid spindle support is ideal for cleaning and deburring castings, finishing welds and heavy-duty filing. Standard equipment includes a ¼" collet. An accessory ⅛" collet is available. The 21,000 RPM no load speed provides ample power and torque for use with non-reinforced organic wheels to 1⅝" diameter and reinforced wheels to 2" diameter. Featured are the automatic shut-off brushes. When brushes reach ¼" the tool will stop, protecting the commutator from damage.

SPECIFICATIONS

Catalog Number	Collet Diameter	Max. Grinding Wheel Dia.		No Load RPM	Volts	Length	Net Weight Lbs.	Shipping Weight Lbs.	O.S.H.A. Compliance
		Non-Reinforced Organic	Reinforced						
5191	⅛†-¼ ▲	1"	1½"	34,000	115	13½"	4	6	Yes
5265	⅛†-¼ ▲	1⅝"	2"	21,000	115	18⅜"	6¾	9	Yes

†Available as accessory only ▲Standard equipment

ACCESSORIES

Catalog Number	Description
48-66-0910*	¼ Collet
49-96-4112*	Collet Wrench
49-96-4115*	Spindle Wrench
48-66-0900	⅛ Collet

*Included as standard equipment

NOTE

These Grinders are not supplied with grinding wheels. Before using any grinding wheel be sure speed shown for that wheel is greater than the no load speed of the tool. Tables of maximum operating speeds for mounted wheels are included in the instructions packed with each new grinder.

HEAVY-DUTY Milwaukee TAPPER

For Thru-Holes and Blind Holes • Balanced For Easy Handling • Floating Chuck
Quick Tap Changing • Faster Than Hand Tapping • Automatic Reversing & Depth Gauge

CATALOG NO. 8600

A portable heavy-duty tapper designed for craftsmen, machine builders and the sheet metal trades. Well balanced for easy handling and offering a floating chuck that prevents tap breakage. Automatic reversing, backs tap out of hole at high speed when operator pulls backward . . . no reversing switch needed. Built to handle #8 thru 5/16" taps in cold rolled steel and a variety of non-ferrous materials.

SPECIFICATIONS

Catalog Number	Capacity In Mild Steel	RPM		Volts	Length	Net Weight Lbs.	Shipping Weight Lbs.	O.S.H.A. Compliance
		Clockwise	Counter-Clockwise					
8600	5/16"	360	650	115	13⅝"	5¼	7	Yes

ACCESSORIES

Catalog Number	Description
48-66-1500▲	Tapper Chuck Assembly
48-86-0110▲	Drift Pin
48-66-6740▲	Chuck Key
49-11-0070▲	Depth Gauge

▲Included as standard equipment

MISCELLANEOUS

Type "A" Grease ½ lb. can **Catalog No. 49-08-0500**
1 lb. can **Catalog No. 49-08-0800**

HEAVY-DUTY Milwaukee SANDER-GRINDERS

OUTSTANDING FEATURES

- **BALL BEARING MOUNTED ROTOR ASSEMBLY** Is dynamically balanced and vibration free.
- **EXTERNAL BRUSH HOLDERS** Permit inspection and replacement of brushes without disassembling grinder.
- **BUTTON-TYPE SPINDLE LOCK** For easy removal of discs or other accessories. No special tools required.
- **HEAVY-DUTY URETHANE TOOL REST** Absorbs shock . . . prevents damage to housings.
- **REMOVABLE SIDE HANDLE** For use on either side of grinder.
- **LARGE FAN AND EXHAUST PORTS** Direct air over disc, dissipates heat and keeps work area free of dust and grit.

For Heavy-Duty Automotive and Industrial Use In 7" or 9" Sizes

Ball and Roller Bearings

. . . With *EXCLUSIVE*

SPRING LOADED CLUTCH DRIVE

Assures smoother running and prevents harmful backlash shock of heavy or unbalanced grinding wheels to driving mechanism. Greatly increases gear life.





6000 RPM 7" DIAMETER TOOL ONLY

High Speed CATALOG NO. 6085

High Speed 6000 RPM Sander-Grinder, powered by a new MILWAUKEE 2 hp motor. Built for continuous duty in automotive, industrial, welding, and concrete surfacing applications. Unit is supplied less disc assembly and sanding discs. Can be used with disc assemblies and accessories on page 45.

Catalog No.	Speed RPM	Disc Dia. (In.)	Volts	HP	Spindle Thread Size	Length (Less Disc) (Inches)	Net Wgt. (Lbs.)	Ship. Wgt. (Lbs.)	O.S.H.A. Compliance
6085•	6000	7	115	2	5/8"-11	15½	12¼	17	Yes*

• Less disc assembly and hub
* When used as a grinder, guard must be used for O.S.H.A. compliance

5000 RPM 7" DIAMETER

CATALOG NO. 6020

Widely used in auto body shops, garages, by sheet metal fabricators and on farms for sharpening plows and disc harrows. Can be converted from sanding to grinding or wire brushing. Furnished with 7" standard phenolic resin backing disc assembly and disc retaining nut. One each sample 36 and 60 grit 7" diameter sanding disc included.



5000 RPM 9" DIAMETER TOOL ONLY

CATALOG NO. 6080

The same powerful sander-grinder as Catalog No. 6060 less disc assembly, and sanding discs. For use with cup wire brushes and flared cup grinding wheels — available as accessories.

5000 RPM 9" DIAMETER

CATALOG NO. 6060

Specially built for continuous duty service in heaviest type of work. High speed and high torque give best performance under maximum load. Furnished with 9" standard phenolic resin backing disc assembly and disc retaining nut. One each 36 and 60 grit 9" diameter sample sanding disc included.



5000 RPM 9" DIAMETER

CATALOG NO. 6100

Designed expecially for the welder or for concrete surfacing. With the same power and characteristics as Catalog No. 6060 but with 9" x ¼" Flat Rough Reinforced Grinding Disc in place of backing disc assembly and sanding discs. Steel guard No. 49-12-0090 also furnished.

SPECIFICATIONS

Catalog No.	Speed RPM	Disc Dia. (In.)	Volts	HP	Spindle Thread Size	Length (Less Disc) (Inches)	Net Wgt. (Lbs.)	Ship. Wgt. (Lbs.)	O.S.H.A. Compliance
6020	5000	7	115	1½	5/8"-11	15½	13	18	Yes*
6060		9					13¼	18	Yes*
6080•		9					12¼	17	Yes*
6100		9					15¼	20	Yes

• Less disc assembly and hub
* When used as a grinder, guard must be used for O.S.H.A. compliance

HEAVY-DUTY Milwaukee SANDER-GRINDER ACCESSORIES

REINFORCED GRINDING DISCS
CUP GRINDING WHEELS • WIRE CUP BRUSHES
ABRASIVE SANDING DISCS



SPECIFICATIONS

	Description			Catalog No.	Max. Speed
	FLAT REINFORCED GRINDING DISCS				
	ALUMINUM OXIDE DISCS FOR METAL				
A	ROUGH	With 5/8"-11 Threaded Hub	7" x 1/4"	49-93-3110	7750
			9" x 1/4"	49-93-3230	6000
	FINISH		7" x 1/4"	49-93-3170	7750
			9" x 1/4"	49-93-3290	6000
	SILICON CARBIDE DISCS FOR STONE OR CONCRETE				
	5/8"-11	Threaded Hub	7" x 1/4"	49-93-3130	7750
			9" x 1/4"	49-93-3250	6000
B	GUARD		Fits 7"	49-12-0080	—
			Fits 9"	49-12-0090	—
	CURVED REINFORCED GRINDING DISCS				
C	ROUGH	With 5/8"-11 Threaded Hub	7" x 1/4"	49-93-3120	8500
			9" x 1/4"	49-93-3240	6000
	FINISH		7" x 1/4"	49-93-3180	8500
			9" x 1/4"	49-93-3300	6000
D	GUARD		Fits 7"	49-12-0100	—
			Fits 9"	49-12-0110	—
	FLARED CUP GRINDING WHEELS				
E	4" DIA. FOR 7"	5/8"-11 Thread		49-93-5140	9000
	5" DIA. FOR 9"	5/8"-11 Thread		49-93-5220	7200
F	GUARD	For 4" Flared Cup		49-12-0060	—
		For 5" Flared Cup		49-12-0070	—
	ARMOR-CUP GRINDING WHEELS				
	ALUMINUM OXIDE ARMOR-CUP FOR METAL				
G	4" DIA. FOR 7"	5/8"-11 Thread		49-93-5250	9000
	5" DIA. FOR 9"	5/8"-11 Thread		49-93-5270	7200
	SILICON CARBIDE ARMOR-CUP FOR STONE OR CONCRETE				
	4" DIA. FOR 7"	5/8"-11 Thread		49-93-5260	9000
	5" DIA. FOR 9"	5/8"-11 Thread		49-93-5280	7200
H	GUARD	For 4" Flared Cup		49-12-0060	—
		For 5" Flared Cup		49-12-0070	—
	WIRE CUP BRUSHES				
I	4" DIA. FOR 7"				
	30 ga. crimped wire	5/8"-11 Thread		48-52-1300	7000
	24 ga. knot wire	5/8"-11 Thread		48-52-1350	6000
	6" DIA. FOR 9"				
	24 ga. crimped wire	5/8"-11 Thread		48-52-1600	6000
	30 ga. knot wire	5/8"-11 Thread		48-52-1650	6000
	ABRASIVE SANDING DISCS				
J	FOR 7" DIA.	16 Grit	PACKED AND SOLD ONLY IN BOXES OF 10	48-80-2000	7000
		24 Grit		48-80-2050	7000
		36 Grit		48-80-2100	7000
		60 Grit		48-80-2200	7000
		80 Grit		48-80-2250	7000
	FOR 9" DIA.	16 Grit		48-80-2500	7000
		24 Grit		48-80-2550	7000
		36 Grit		48-80-2600	7000
		60 Grit		48-80-2700	7000
		80 Grit		48-80-2750	7000

Strong and tough with high safety factor to permit high speed operation. Nylon reinforced to resist breakage from twisting, starting torque or lateral pressure. All types require Guard "B".

Nylon reinforced curved grinding discs for grinding welds. Contour shape permits easier accessibility to work surfaces. Same high safety factor as flat reinforced grinding discs. All types require Guard "D".

Aluminum oxide for all general purpose metal grinding. Resinoid bonded. These wheels are fitted with 5/8"-11 threaded bushing molded integrally for ready mounting.

Resinoid bonded. Special fine grit outer rim wears slowly . . . prevents rounded edges for high performance without distortion. Eliminates waste by maintaining a flat grinding surface even under the toughest conditions . . . provides longer usable cup life. 5/8"-11 threaded bushing integrally molded for easy mounting.

Finest quality crimped and knot wire brushes to give long service life on the toughest cleaning jobs. Ideally suited for cleaning castings, structural steel, sheet metal, stone and concrete.

Specially selected extra hard aluminum oxide grits are applied with plastic adhesive to rigid fibre backing for long life . . . will not crack, curl or tear. Special spiral design speeds grinding, cools as it grinds. They are waterproof and can be dipped in gasoline and scrubbed for re-use.

BACKING DISC ASSEMBLIES

Light, perfectly balanced assemblies provide flexibility for curves and contours. Abrasive discs can be trimmed down to the next smaller diameter to be used with smaller backing discs, affording greater economy.

STANDARD PHENOLIC DISC ASSEMBLIES

Same as furnished with Nos. 6020 and 6060



Description	Dia.	Catalog No.	Max. Speed
*COMPLETE ASSEMBLY	7"	49-36-6000	7000
	9"	49-36-6050	7000
DISC ONLY	7"	48-80-6000	7000
	9"	48-80-6050	7000
RUBBER PAD	—	49-36-3500	7000
DISC NUT	—	49-40-0350	—

*All Disc Assemblies include Disc Nut

NOTE
The maximum safe operating speed shown on the grinding wheels must be greater than the no load speed of the tool.

DISC SAVER PHENOLIC DISC ASSEMBLIES



Description	Dia.	Catalog No.	Max. Speed
*COMPLETE ASSEMBLY	7"	49-36-3600	7000
	9"	49-36-3650	7000
DISC ONLY	7"	48-80-6010	7000
	9"	48-80-6060	7000
RUBBER PAD	—	49-36-3550	7000
DISC NUT	—	49-40-0350	—

*All Disc Assemblies include Disc Nut

MISCELLANEOUS

DISC NUT
Cat. No. 49-40-0120
For Disc Wheel Hub Adapter and discontinued Nested Spring Steel Disc Assemblies.

1 LB. TYPE C GREASE
Cat. No. 49-08-1000

HUB ADAPTER DISC WHEEL
Cat. No. 48-03-1000
For use with depressed center hub wheels with 7/8" diameter hole. Order disc nut 49-40-0120 separately.

HEAVY-DUTY Milwaukee PORTABLE GRINDERS

ALL BALL BEARINGS

CATALOG No. 5220

Outstanding Features



1. Lightweight Aluminum Alloy Housings
2. Heavy-Duty MILWAUKEE-BUILT MOTOR
3. Adjustable, Shatterproof Steel Guard
4. Fully Enclosed Dustproof Switch
5. Helical-Cut Alloy Steel Gears and Shafts
6. Double Row Oversize Ball Bearings

MILWAUKEE Heavy-Duty Portable Grinders are engineered to give rugged, dependable, trouble-free performance. Here, in this steel fabricating shop, the operator is grinding off welds using 6" model 5240. Ideal balance of the unit makes it easy to handle and reduces fatigue through long periods of use.

NOTE
The maximum safe operating speed shown on grinding wheels and tuck point abrasive wheels must be greater than the no load speed of the tool.

POWERFUL, HIGH TORQUE GRINDERS

For use in welding shops and heavy industry — prepares surfaces for welding, smooths welds, removes burrs, snags and grinds castings — also for wire brushing, buffing and general grinding. Ruggedly built for continuous service — lightweight and balanced to permit long periods of use. Oversize double row ball bearings provide rigid support for grinding wheel. High velocity air flow keeps motor cool and free of dust and grit. Equipped with adjustable steel wheel guard and coarse grinding wheel. Hinged face plate on guard for quick wheel replacement.

SPECIFICATIONS

Catalog No.	Wheel Size	Hole Dia.	Speed No Load (RPM)	Volts	Lgth. (In.)	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)	O.S.H.A. Compliance
5200	4" x 1"	½"	6000	115	21⅝	13½	19	Yes
5220	5" x 1"	⅝"	4000	115	21¾	15	19	Yes
5240	6" x 1"	⅝"	4000	115	22	16½	22	Yes

REPLACEMENT GUARD ASSEMBLIES

4" WHEEL GUARD ASSEMBLY
For Model 5200 Grinder
Cat. No. 49-12-0130

5" WHEEL GUARD ASSEMBLY
For Model 5220 Grinder
Cat. No. 49-12-0140

6" WHEEL GUARD ASSEMBLY
For Model 5240 Grinder
Cat. No. 49-12-0150



COARSE GRIT GRINDING WHEELS

Catalog No.	Size (In.)	Hole Dia.	Max. Wheel Speed
49-92-1140	4 x 1	½	9000
49-92-2240	5 x 1	⅝	9000
49-92-3260	6 x 1	⅝	6000

KNOT WIRE BRUSHES

Made of select steel wire. For cleaning steel surfaces and castings, removing rust, scale, file marks.

Catalog No.	Dia. (In.)	Hole Dia.	Wire Size	Max. Wheel Speed
48-52-2210	4	½"	.014	8000
48-52-2310	5	⅝"	.014	8000
48-52-2510	6	½"-⅝"	.014	8000

CLOTH BUFFING WHEELS

For polishing and buffing metal surfaces. Coated with abrasive, can be used for smooth finish grinding or rough polishing.

Catalog No.	Dia. (In.)	Hole Dia.
49-93-0060	4	½"
49-93-0070	5	⅝"
49-93-0090	6	⅝"

1 lb. can Type C Grease.
Cat. No. 49-08-1000

HEAVY-DUTY Milwaukee TUCK POINT GRINDER

8" Diameter Wheel



CATALOG No. 5260

Outstanding physical features for the Tuck Point Grinder are the same as noted above for Portable Grinders.

ALL BALL BEARINGS

Powerful, high speed, easy handling grinder for fast clean removal of old or loose mortar. Furnished with 8" x ⅛" abrasive wheel and steel wheel guard for safe operation. All ball bearings — double row ball bearings in forward handle housing provide rigid support for grinding wheel. Comfortable grip.

SPECIFICATIONS

Catalog No.	Wheel Size	Hole Dia.	Speed No Load (RPM)	Volts	Lgth. (ins.)	Net Wgt. lbs.	Shp. Wgt. lbs.	O.S.H.A. Compliance
5260	8" x ⅛"	⅝"	4000	115	21	15¼	19	Yes

TUCK POINT ABRASIVE WHEELS

Maximum Wheel Speeds 7200 RPM

Cat. No. 49-92-5020 8" x ⅛" x ⅝" hole.
Cat. No. 49-92-5040 8" x 3/16" x ⅝" hole.
Cat. No. 49-92-5060 8" x ¼" x ⅝" hole.

1 LB. TYPE C GREASE
Cat. No. 49-08-1000

Kits and abrasive wheels are adaptable to Portable Grinders Nos. 5220 and 5240.

TUCK POINT GUARD ASSEMBLY
Cat. No. 49-12-0120 Consists of Guard and Spacer.

TUCK POINT GRINDER ACCESSORY KITS

Cat. No. 49-22-6050 Includes wheel guard, spacer unit and 8" x ⅛" x ⅝" hole abrasive wheel.

Cat. No. 49-22-6060 Same as above kit except with 8" x 3/16" x ⅝" hole abrasive wheel.

HEAVY-DUTY Milwaukee BENCH GRINDERS

AVAILABLE IN 5 SIZES
1/4 • 1/3 • 1/2 • 3/4 • 1 HORSE POWER

6 • 7 • 8 and 10 Inch Wheel Sizes

Plastic Eye Shields (Cat. No. 49-62-0100) are furnished as standard equipment. Glass Eye Shields and Illuminated Eye Shields are offered as optional accessories. Shields *must* be used when operating grinders.

¼ H.P. GRINDER
Shown with Optional
Glass Eye Shields
Catalog No. 49-62-0060



⅓ H.P. GRINDER
Shown with Optional
Glass Eye Shields
Catalog No. 49-62-0060



¾ H.P. GRINDER
Shown with Optional
Illuminated Eye Shields
Catalog No. 49-62-0050

½ H.P. GRINDER
Mounted on Grinder Pedestal
Shown with Optional
Glass Eye Shields
Catalog No. 49-62-0060



1 H.P. GRINDER
Shown with Optional
Illuminated Eye Shields
Catalog No. 49-62-0050

PLASTIC EYE SHIELDS

Catalog No. 49-62-0100. (pair) These protective eye shields are furnished as standard equipment on all MILWAUKEE Bench Grinders. Easily replaced when pitted. Supplied as a pair. Complete with attaching hardware for any MILWAUKEE Bench Grinder. Shp. Wt. 1 lb. per pair.

ILLUMINATED EYE SHIELD

Catalog No. 49-62-0050. (as shown above on 1 H.P. Grinder) Metal frame holds 2 pieces of 4" x 6" glass . . . top is safety glass . . . underneath, window glass . . . easily replaced when pitted. Double socket with two bulbs eliminates shadow. Rigid support prevents swiveling. Available for ½, ¾, and 1 H.P. bench grinders only. If pair required specify 2 units. Shp. Wt. 4 lbs. each.

GLASS EYE SHIELD

Catalog No. 49-62-0060. (as shown above on ½ H.P. Grinder) Frame holds 3" x 5" Shatterproof glass. Mounting bracket included. Adaptable to all models. Specify 2 units if pair desired. Shp. Wt. 2 lbs. each.

GRINDER PEDESTAL

Catalog No. 49-39-0050. (as shown above) Heavy gray iron castings with tubular steel column. Removable water pot. Adaptable to all models. Height 34". Shp. Wt. 54 lbs.

INDUCTION MOTOR UNITS

Precision built, quiet, smooth running and designed for continuous production in factories, machine and welding shops, tool rooms, maintenance departments and garages. Heavy-duty motors — alternating current only — dynamically balanced, with every safeguard against overload. Completely sealed against dirt and grit. Lifetime lubricated ball bearings.

SPECIFICATIONS

Standard equipment includes two balanced, aluminum oxide wheels — one fine and one coarse grit — adjustable tool rests, spark deflectors and plastic eye shields. Pedestal and glass or illuminated eye shields are listed below and are available as accessories. Wheels other than those supplied as standard equipment must be ordered separately.

HP	Catalog No.	Voltages AC 60 cycle	Phase	Speed RPM	Wheel Size	Hole Dia.	Space Between Wheels	Net Wgt. (Lbs.)	Shp. Wgt. (Lbs.)
¼	**4900**	115	1	3450	6"x⅝"†	½"	11½"	22	24
⅓	**4920**	115	1	3450	6"x¾"	½"	13½"	27	29
½	**4980**	115	1	3450	7"x1"	⅝"	14⅛"	37	40
¾	**5040**	115/230	1	3450	8"x1"	⅝"	16⅜"	57	60
1	**5080**	115/230	1	1725	10"x1"	¾"	17⅛"	82	85

†Replacement wheels are ¾"

SPECIAL FEATURE

BELL TYPE CONSTRUCTION

Clearance in front of motor housing is important when grinding longer pieces.

WHEELS FOR BENCH GRINDERS

NOTE: The maximum safe operating speed shown on the grinding wheels must be greater than the no load speed of the tool. Aluminum Oxide Grinding Wheels are available in coarse, medium and fine grit for all types of grinding. Knot Wire Brushes for removing rust, scale and file marks — made of select steel wires. Brushes have a face width of ¾". Cloth Buffing Wheels for buffing metal surfaces — made of multiple layers of select buffing cloth — securely sewed — can be dipped in an emery grit after coating with glue for finish grinding or rough polishing.

GRINDING WHEELS

	Catalog No.	Size (In.)	Hole Dia.	Max. Wheel Speed
MEDIUM GRIT	**49-92-3140**	6 x ¾	½	6000
	49-92-4200	7 x 1	⅝	5200
	49-92-5300	8 x 1	⅝	4600
	49-92-7200	10 x 1	¾	3750
COARSE GRIT	**49-92-3160**	6 x ¾	½	6000
	49-92-4220	7 x 1	⅝	5200
	49-92-5320	8 x 1	⅝	4600
	49-92-7220	10 x 1	¾	3750
FINE GRIT	**49-92-3180**	6 x ¾	½	6000
	49-92-4240	7 x 1	⅝	5200
	49-92-5340	8 x 1	⅝	4600
	49-92-7240	10 x 1	¾	3750

KNOT WIRE BRUSHES

Catalog No.	Dia. (In.)	Hole (Dia.)	Wire Size	Max. Wheel Speed
48-52-2510	6	½"-⅝"	.014	8000
48-52-2610	7	⅝"	.014	5000
48-52-4810	10	¾"	.014	4500

CLOTH BUFFING WHEELS

Catalog No.	Dia. (In.)	Hole Dia.
49-93-0080	6	½"
49-93-0100	7	⅝"
49-93-0110	10	¾"

HEAVY-DUTY Milwaukee METAL CUTTING SHEARS

Ball and Roller Bearings

MILWAUKEE Shears are designed for heavy-duty continuous production use and are engineered for highest efficiency, best cutting versatility and ease in handling. Lightweight, compact and perfectly balanced, these Shears produce maximum constant output power. Tool steel ram holds cutter blade in perfect alignment for fast, accurate cutting. With large bearing surfaces, the ram maintains proper blade clearance for clean cuts and minimum distortion. All Shears are ruggedly built with heat treated gears, hardened shafts, ball and roller bearings, and sturdy aluminum alloy housings.

CUT ALL TYPES OF SHEET METAL
COLD ROLLED STEEL • STAINLESS • NON-FERROUS

Ideal For
Heating & Air Conditioning Fabrication
Metal Building Construction
Sheet Metal Fabrication
Industrial Maintenance
Aviation Industry

AVAILABLE IN 4 POPULAR SIZES

OUTSTANDING FEATURES

- High Speed, Accurate Cutting Mechanism
- Simple Blade Adjustments — No Shims
- Blade Design Eliminates Jamming
- Leaves Edges Smooth — Free of Burrs
- No Adjustments for Straight Cuts or Curves
- Cuts Close Curves Either Right or Left
- Clear, Unobstructed Visibility

Tool steel shear blades are easily adjustable. Sheared metal rides smoothly over steel yoke providing high trim cutting efficiency.

16 GAUGE
CATALOG No. 6800

14 GAUGE
CATALOG No. 6810

12 GAUGE
TRIM SHEAR
CATALOG No. 6820

10 GAUGE
TRIM SHEAR
CATALOG No. 6830

SPECIFICATIONS

Catalog No.	Capacity		Cutting Speed Ft./Min.	Minimum Radius	Volts	Net Wt. Lbs.	Shp. Wt. Lbs.	O.S.H.A. Compliance
	Steel	Stainless						
6800	16 Ga.	17 Ga.	17	½"	115	5¼	8	Yes
6810	14 Ga.	16 Ga.	10	¾"	115	5	7	Yes
6820	12 Ga.	14 Ga.	8	¾"	115	8½	11	Yes
6830	10 Ga.	12 Ga.	5	1"	115	10	13	Yes

STANDARD EQUIPMENT
Also Available as Accessories

Catalog No.	Description	For Catalog Nos.			
49-11-0050	Feeler Gauges	6800	6810	6820	6830
49-80-0010	Blade Adj. Screw Tool		6810	6820	6830
49-11-0065	Cutting Angle Gauge		6810	6820	6830
49-96-0060	⅛" Hex Socket Wrench	6800			
49-96-0065	9/64" Hex Socket Wrench	6800			
49-96-0310	Hex Socket Wrench Set		6810	6820	
49-96-0320	Hex Socket Wrench Set				6830
48-44-0070	Shear Blade Set	6800			
48-44-0080	Shear Blade Set		6810	6820	
48-44-0090	Shear Blade Set				6830
49-13-0020	Scrap Guide			6820	

MISCELLANEOUS ACCESSORIES

Catalog No.	Description	For Catalog Nos.			
49-08-0500	½ lb. Can "A" Grease		6810	6820	6830
49-08-0800	1 lb. Can "A" Grease		6810	6820	6830
49-08-1000	1 lb. Can "C" Grease	6800			
49-14-0300	Grease Gun		6810	6820	6830

HEAVY-DUTY Milwaukee NIBBLER

Ball and Roller Bearings

FOR FAST ECONOMICAL CUTTING IN STEEL, STAINLESS STEEL, ALUMINUM AND PLASTIC

SHEET METAL WORK • INDUSTRIAL MAINTENANCE • HEATING AND AIR CONDITIONING FABRICATION • METAL BUILDING CONSTRUCTION • AVIATION INDUSTRY

13 GAUGE CATALOG NO. 5410

Ideal for maintenance, production and other continuous heavy-duty precision applications. The dependable MILWAUKEE Nibbler can be used in cold rolled steel to 13 gauge and stainless steel to 14 gauge. In addition, the unit can be used for aluminum and plastic with accessory carrier rod. Simple to adjust punch and die accommodates a variety of gauges and offers maximum accuracy. As tool is guided along the cutting line, small crescent shaped pieces of material are punched out . . . leaving a clean undistorted surface. In addition, ¼" cutting radius makes intricate patterns easy to follow. Open front plus adjustable nose piece makes cutting at the stock pile possible, avoiding unnecessary material handling.

OUTSTANDING FEATURES

- BURR & DISTORTION-FREE CUTS
- LIGHT FEED PRESSURE REQUIRED
- SHORT TURNING RADIUS
- START CUTS IN MIDDLE OF SHEET
- TOOL STEEL PUNCH AND DIE
- CONVENIENT SWITCH LOCATION

Milwaukee Nibblers are easy to guide along templates and scribed lines and require only light pressure. Just a single adjustment for material thickness is necessary.



SPECIFICATIONS

Catalog Number	Capacity		Cutting Speed Ft./Min.	Minimum Radius	Volts	Net Weight lbs.	Shipping Weight lbs.	O.S.H.A. Compliance
	Steel	Stainless						
5410	13 Ga.	14 Ga.	3	¼"	115	9¼	13	Yes

STANDARD EQUIPMENT

Also Available as Replacement Accessories

Catalog Number	Description
49-52-0250	Carrier Rod▲
48-44-0250	Nibbler Punch
48-79-0020	Die
49-96-4720	Open End Wrench
49-96-0300	Hex. Socket Wrench Set
49-96-6500	Nibbler Punch Wrench

▲For use with steel and stainless steel

ADDITIONAL ACCESSORIES

Catalog Number	Description
49-08-0500	½ lb. can "A" Grease
49-08-0800	1 lb. can "A" Grease
49-14-0300	Grease Gun
49-52-0260	Carrier Rod■

■For use with Aluminum and Plastic

HEAVY-DUTY Milwaukee "PITTSBURGH LOCK" HAMMER

Ball and Roller Bearings

Fast • Powerful • Rugged • Efficient

CATALOG NO. 5400

CAPACITY

30 to 22 Gauge Sheet Metal

For Sheet Metal, Heating and Air Conditioning Contractors—closes seams neatly at a rate up to 20 feet per minute. Powerful 115 volt motor—smooth running and easy to use—weight rests on work. Position of handle affords positive control and balance—Auxiliary knob handle for two hand operation on heavy gauge metals. Guides easily along seam on straight runs or curves. Ruggedly designed for high volume, heavy-duty production use—in the shop or on the job.





Specially designed hammer mechanism of hardened tool steel. Closes seams flush and secure. Shoe guide assures proper positioning. Closing duct seams neat and quick is easy for the operator.

SPECIFICATIONS

Catalog Number	Capacity	Ft./Min.	Volts	Net Weight	Shipping Weight	O.S.H.A. Compliance
5400	30 to 22 Ga.	20' Max.	115	10	14	Yes

MISCELLANEOUS

Type "A" Grease ½ lb. can **Catalog No. 49-08-0500**
1 lb. can **Catalog No. 49-08-0800**

HEAVY-DUTY Milwaukee ALTERNATORS

MILWAUKEE Alternators are the most dependable source of portable electric power. Advanced design revolving field alternators offer superior electrical performance with less weight, less maintenance and less cost. Full power output is obtained from stationary coils through solid connections eliminating arcing and sparking. Brushes in alternator ride on smooth slip rings and carry only low control current with practically no brush wear. Nationally recognized engines are used and local service is always available.

RELIABLE, LOW COST PORTABLE POWER

Large fuel tank capacities.

Long life 1800 RPM industry accepted 12 H.P. **Air Cooled** four cycle engines feature stellite valves and rotators.

Large triple chamber stainless steel muffler.

ADVANCED DESIGN: Revolving field alternator construction eliminates AC slip rings and DC commulators.



Full capacity: 115 volts and 230 volts — a voltage selector provides instant full capacity at 115 volts.

Multiple choice receptacle panel: To fit your electrical requirements plus two 15 amp fuses in the panel.

Solid State Voltage Control: Rigid temperature compensation holds voltage within ±5% over load range.

Vibrator Isolators: Serves as a stabilizer for both engine and alternator.

HOW TO SELECT YOUR MILWAUKEE ALTERNATOR

MILWAUKEE Alternators are built for continuous-duty operation at rated capacity. To determine which Alternator best fits your needs, total the watt ratings (volts x amps = watts) of all equipment (excluding electric motors) to be operated at the same time. The watt rating of the Alternator should at least equal this total. When operating electric motors, add the "starting watts required" shown in the chart at right to insure good starting and to reduce disturbances to other loads. When analyzing the motor loads and required starting watts, determine which loads can be staggered. In most cases, it is impractical to have an alternator large enough to handle total connected load.

Motor H.P. Rating	Approx. Running Watts	Approximate Starting Watts Required			
		Universal Motors	Repulsion Induction Motors	Capacitor Motors	Split Phase Motors
1/6	275	400	600	850	1200
1/4	400	500	850	1050	1700
1/3	450	600	975	1350	1950
1/2	600	750	1300	1800	2600
3/4	850	1000	1900	2600	†
1	1000	1250	2300	3000	†
1 1/2	1600	1750	3200	4200	†
2	2000	2350	3900	5100	†
3	3000	†	5200	6800	†

† Motors of higher horsepower are not generally used.

HEAVY-DUTY Milwaukee ALTERNATORS



1750 WATT 5 H.P. 3600 RPM



2500 WATT 6 H.P. 3600 RPM



3000 WATT 12 H.P. LONG LIFE 1800 RPM

3500 WATT 8 H.P. 3600 RPM



7000 WATT 16 H.P. 3600 RPM



5000 WATT 12 H.P. 3600 RPM

SPECIFICATIONS

Catalog No.	Watts	HP	★ Engine 1-cyl.	Start	Fuel Tank (gal.)	Volts AC	Total Amps. Output 115/230	Output Receptacles			Overall Dimensions in Inches			Net Wt. (lbs.)	Shp. Wt. (lbs.)	O.S.H.A. Compliance
								115V 2 Pole NEMA #5-15R	115V Twist Lock NEMA #L5-30R	230V Twist Lock (1)	L.	W.	H.			
4452	1750	5	Tec	Recoil	1/2	115	15.2	2	—	—	24	20	20	108	121	Yes
4552●	2500	6	Tec	Recoil	1	115/230	21.7/10.9	2	1	L6-20R	24	20	18	116	129	Yes
4612	3000	12	Wis	Rope	1	115/230	27/13.5	2	1	L6-20R	29	20	20	180	200	Yes
4642●	3500	8	Tec	Recoil	1	115/230	30.4/17.2	2	1	L6-20R	29	20	19	165	180	Yes
4777	5000	12	Wis	Rope	2 3/4	115/230	43.4/21.7	2	2	L6-30R	29	20	20	180	208	Yes
4792	7000	16	Tec	Elect.†	2 3/4	115/230	60.8/32.5	2	2	L6-30R	29	20	24	235	260	Yes

★ All units equipped with manual choke, except Cat. No. 4792 (7000 watt)
† Battery not included ● Full Capacity — 115 volt selector switch

ALTERNATOR DOLLY

Catalog No. 48-83-0110

FOR 3000, 3500, 5000, and 7000 WATT UNITS

Consists of push handle, rest and wheel assemblies. 12" dia., pneumatic, heavy-duty tires. Wheels have roller bearings. Net Wt., 30 lbs., Shpg. Wt. 34 lbs.

QUICK REFERENCE LIST

GENUINE MILWAUKEE REPLACEMENT PARTS

For customer convenience, MILWAUKEE provides this list of replacement parts to simplify ordering components for current models listed in this catalog. Genuine MILWAUKEE parts for these and previous models are available from your nearest Authorized Service Station, Branch or Factory as listed on the inside back cover. These parts are exact duplicates of those used in MILWAUKEE ELECTRIC TOOLS and are your assurance of maximum tool life and trouble-free operation. A complete schematic diagram indicating all parts may be obtained by ordering the service bulletin number shown. However, major repairs should be referred to factory trained personnel. At no time should substitute parts be used. Always furnish catalog number and serial number of the tool when ordering parts.

● Cat. No.	Service Bulletin No.	Serial No. Start	Armature No.	Field No.	Carbon Brush No.	Cord No.	Brush Cap No.	Switch No.
0101	54-06-0205	376-33402	16-22-1280	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0102-1	54-06-0352	428-26932	16-22-1280	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0792
0120	54-06-0404	90-54543	16-22-1120	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0121	54-06-0504	377-4618	16-22-1251	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0122-1	54-06-0652	429-7274	16-22-1251	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0792
0125	54-06-0701	322-3404	16-20-1010	18-20-1000	22-18-0310	22-64-0310	23-44-0020	23-66-0280
0140	54-06-0804	91-7034	16-22-1120	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0141	54-06-0820	479-1001	16-22-1251	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0160	54-06-1004	93-3024	16-22-1120	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0161	54-06-1020	480-1001	16-22-1251	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0180	54-06-1204	93-8701	16-22-1120	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0181	54-06-1304	393-2118	16-22-1251	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0190	54-06-1402	304-10099	16-22-1120	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0191	54-06-1504	394-2394	16-22-1251	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0200	54-05-1604	89-9081	16-22-1110	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0220	54-06-2004	88-65425	16-22-1110	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0280
0221	54-06-2104	378-11201	16-22-1241	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0515
0222-1	54-06-2302	430-44235	16-22-1241	18-22-1121	22-18-0360	22-64-0665	23-44-0020	23-66-0792
0225	54-06-2401	316-3052	16-20-1000	18-20-1000	22-18-0310	22-64-0310	23-44-0020	23-66-0280
0565-1	54-05-0111	467-1876	16-22-1221	18-22-1060	22-18-0360	22-64-0665	23-44-0020	23-66-0797
0566-1	54-05-0125	496-1001	16-22-1221	18-22-1060	22-18-0360	22-64-0665	23-44-0020	23-66-0797
0800	54-08-0203	10-6215	16-42-1040	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
0801	54-08-0220	485-1001	16-42-1400	18-42-1200	22-16-0250	22-64-0385	23-44-0120	23-66-0505
0805	54-08-0250	484-1001	16-42-1400	18-42-1200	22-16-0250	22-64-0625	23-44-0120	23-66-0505
0850	54-08-0402	12-3593	16-42-1040	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
0870	54-08-0603	13-8903	16-42-1040	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
0871	54-08-0610	486-1001	16-42-1400	18-42-1200	22-16-0250	22-64-0385	23-44-0120	23-66-0505
0875	54-08-0630	487-1001	16-42-1400	18-42-1200	22-16-0250	22-64-0625	23-44-0120	23-66-0505
0890	54-08-0652	50-9145	16-42-1040	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
1000	54-08-1052	17-85272	16-42-1040	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
1000-1	54-08-1076	126-32055	16-42-1040	18-42-1141	22-18-0100	22-64-0380	23-44-0060	23-66-0487
1001	54-08-1100	490-1001	16-42-1415	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0505
1001-1	54-08-1140	491-1001	16-42-1415	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0751
1100	54-08-2103	14-73340	16-42-1210	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
1100-1	54-08-2126	133-37742	16-42-1210	18-42-1141	22-18-0100	22-64-0380	23-44-0060	23-66-0487
1101	54-08-1160	492-1001	16-42-1410	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0505
1101-1	54-08-1180	493-1001	16-42-1410	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0751
1105-1	54-08-2250	458-1001	16-42-1410	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0751
1106-1	54-08-2020	482-1001	16-42-1410	18-42-1040	22-16-0250	22-64-0625	23-44-0120	23-66-0751
1120	54-08-2141	306-3001	16-40-1030	18-40-1000	22-18-0280◈	22-64-0310	23-44-0020	23-66-0230
1200	54-08-2203	54-14985	16-42-1210	18-42-1040	22-18-0100	22-64-0170	23-44-0060	23-66-0230
1200-1	54-08-2226	134-15815	16-42-1210	18-42-1141	22-18-0100	22-64-0380	23-44-0060	23-66-0487
1201	54-08-2040	494-1001	16-42-1410	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0505
1201-1	54-08-2060	495-1001	16-42-1410	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0751
1250-1	54-08-1080	459-1001	16-42-1400	18-42-1200	22-16-0250	22-64-0385	23-44-0120	23-66-0751
1251-1	54-08-1120	481-1001	16-42-1400	18-42-1200	22-16-0250	22-64-0625	23-44-0120	23-66-0751
1600	54-10-0503	108-37796	16-62-1000	18-62-1000	22-18-0170	22-64-0170	23-44-0065	23-66-0190
1600-1	54-10-0525	109-17265	16-62-1140	18-62-1110	22-18-0170	22-64-0170	23-44-0065	23-66-0190▲
1620-1	54-10-0543	343-4041	16-62-1140	18-62-1110	22-18-0170	22-64-0170	23-44-0065	23-66-0190▲
1650	54-10-2004	117-24987	16-62-1010	18-62-1000	22-18-0170	22-64-0170	23-44-0065	23-66-0190
1650-1	54-10-2026	142-16466	16-62-1150	18-62-1110	22-18-0170	22-64-0170	23-44-0065	23-66-0190▲
1670-1	54-10-4025	472-1001	16-62-1165	18-62-1120	22-18-0450	22-64-0120	23-44-0130	23-66-0751
1675-1	54-10-4003	413-27500	16-62-1165	18-62-1120	22-18-0450	22-64-0120	23-44-0130	23-66-0751
1700	54-12-1024	62-12779	16-82-1420	18-82-1110	22-18-0115	22-64-0080	23-55-0081	23-66-0190
1700-1	54-12-1042	131-1136	16-82-1421	18-82-1110	22-18-0115	22-64-0080	23-44-0081	23-66-0190□
1750	54-12-2023	63-4350	16-82-1430	18-82-1110	22-18-0115	22-64-0080	23-44-0081	23-66-0190
1750-1	54-12-2033	130-1782	16-82-1810	18-82-1070	22-18-0115	22-64-0080	23-44-0081	23-66-0190□
1850	54-12-3021	66-4910	16-82-1430	18-82-1110	22-18-0115	22-64-0080	23-44-0081	23-66-0190
1850-1	54-12-3032	128-3012	16-82-1810	18-82-1070	22-18-0115	22-64-0080	23-44-0081	23-66-0190□
2400-1	54-12-6051	171-2086	16-82-1231	18-82-1070	22-18-0055	22-64-0075	23-44-0030	23-66-0190□

● For Drill Chucks and Chuck Keys, see page 10.

◈ Upper Brush Only. For Lower Brush, order 22-18-0290.

▲ For Reversing Toggle Switch, order 23-66-0198.

□ For Reversing Toggle Switch, order 23-66-0340.

Continued

QUICK REFERENCE LIST

GENUINE MILWAUKEE REPLACEMENT PARTS

● Cat. No.	Service Bulletin No.	Serial No. Start	Armature No.	Field No.	Carbon Brush No.	Cord No.	Brush Cap No.	Switch No.
3940	54-16-2041	161-2023	16-82-1220	18-82-1070	22-18-0055	22-64-0065	23-44-0030	–
4030	54-16-3020	345-1001	16-82-1770	18-82-1070	22-18-0055	22-64-0065	23-44-0030	–
4035	54-16-3040	346-1001	16-82-1770	18-82-1070	22-18-0055	22-64-0065	23-44-0030	–
4250-1●	54-14-1002	298-2304	16-42-1210	18-42-1040	22-18-0100	22-64-0060	23-44-0060	–
4252-1●	54-14-1100	501-1001	16-42-1210	18-42-1040	22-18-0100	22-64-0750	23-44-0060	–
4260-1●	54-14-2002	299-1705	16-82-1231	18-82-1070	22-18-0055	22-64-0530	23-44-0030	–
4262-1●	54-14-2100	502-1001	16-82-1231	18-82-1070	22-18-0055	22-64-0740	23-44-0030	–
4280-1	54-14-3001	301-1534	16-82-1231	18-82-1070	22-18-0055	22-64-0530	23-44-0030	–
4282-1	54-14-3100	503-1001	16-82-1231	18-82-1070	22-18-0055	22-64-0740	23-44-0030	–
4290-1	54-14-4000	347-1001	16-82-1781	18-82-1070	22-18-0055	22-64-0530	23-44-0030	–
4292-1	54-14-4200	504-1001	16-82-1781	18-82-1070	22-18-0055	22-64-0740	23-44-0030	–
4295-1	54-14-4100	348-1001	16-82-1781	18-82-1070	22-18-0055	22-64-0530	23-44-0030	–
4297-1	54-14-4300	505-1001	16-82-1781	18-82-1070	22-18-0055	22-64-0740	23-44-0030	–
5191	54-22-5010	441-1001	16-12-0010	18-12-0010	22-18-0480	22-64-0710	–	23-66-0895
5200	54-22-2038	74-3698	16-82-1660	18-82-1110	22-18-0260	22-64-0090	23-44-0065	23-66-0250
5220	54-22-3107	75-6706	16-82-1450	18-82-1110	22-18-0260	22-64-0090	23-44-0065	23-66-0250
5240	54-22-4107	76-5856	16-82-1450	18-82-1110	22-18-0260	22-64-0090	23-44-0065	23-66-0250
5265	54-22-5000	448-1001	16-22-1300	18-22-1180	22-18-0485	22-64-0705	31-12-0090	23-66-0900
5300	54-24-3506	342-21060	16-62-1130	18-62-1100	22-18-0330	22-64-0410	23-44-0100	23-66-0490
5330	54-24-1200	477-1001	16-82-1830	18-82-1220	22-18-0145	22-64-0075	23-44-0140	23-66-0490
5350	54-24-3004	389-9885	16-42-1360	18-42-1200	22-18-0100	22-64-0180	23-44-0060	23-66-0580
5351	54-24-3020	488-1001	16-42-1430	18-42-1200	22-16-0250	22-64-0385	23-44-0120	23-66-0505
5361	54-24-3040	489-1001	16-42-1420	18-42-1040	22-16-0250	22-64-0385	23-44-0120	23-66-0505
5390	54-24-1505	422-29023	16-22-1290	18-22-1160	22-18-0410	22-64-0665	23-44-0060	23-66-0515
5392	54-24-1551	456-5078	16-22-1290	18-22-1160	22-18-0410	22-64-0665	23-44-0060	23-66-0925
5400	54-24-7006	107-11150	16-22-1000	18-22-1030	22-18-0090	22-64-0170	23-44-0020	23-66-0160
5410	54-27-0100	447-1001	16-22-1310	18-22-1190	22-18-0485	22-64-0715	31-12-0090	23-66-0900
5450	54-32-1008	100-22449	16-62-1045	18-62-1035	22-18-0330	22-64-0090	23-44-0100	23-66-0160
5530	54-32-1103	140-4028	16-62-1035	18-62-1035	22-18-0330	22-64-0090	23-44-0100	23-66-0160
5590	54-32-1218	47-9416	16-82-1180	18-82-1110	22-18-0260	22-64-0090	23-44-0065	23-66-0250
5610	54-37-0101	451-1221	16-62-1180	18-62-1101	22-18-0440	22-64-0380	23-44-0130	23-66-0860
5620	54-37-0101	451-1221	16-62-1180	18-62-1100	22-18-0440	22-64-0120	23-44-0130	23-66-0860
5650	54-37-0202	452-2367	16-62-1170	18-62-1170	22-18-0440	22-64-0380	23-44-0130	23-66-0860
5660	54-37-0202	452-2367	16-62-1170	18-62-1170	22-18-0440	22-64-0120	23-44-0130	23-66-0860
6000	54-38-1002	285-4288	16-42-1310	18-42-1130	22-18-0090	22-64-0220	23-44-0060	23-66-0380
6020	54-38-2019	49-51010	16-82-1711	18-82-1180	22-18-0125	22-64-0090	23-44-0035	23-66-0250
6060	54-38-3109	48-106488	16-82-1711	18-82-1180	22-18-0125	22-64-0090	23-44-0035	23-66-0250
6085	54-38-3201	461-1151	16-82-1715	18-82-1185	22-18-0125	22-64-0730	23-44-0035	23-66-0250
6200	54-40-2503	151-12774	16-82-1280	18-82-1085	22-18-0055	22-64-0095	23-44-0030	23-66-0300
6205	54-40-2525	478-1001	16-82-1280	18-82-1085	22-18-0055	22-64-0095	23-44-0030	23-66-0300
6206	54-40-2525	478-1001	16-82-1280	18-82-1085	22-18-0055	22-64-0095	23-44-0030	23-66-0300
6225	54-40-1200	457-1001	16-62-1190	18-62-1180	22-18-0450	22-64-0115	23-44-0130	23-66-0483
6250	54-40-3003	281-26772	16-22-1190	18-22-1121	22-18-0270	22-64-0220	23-44-0020	23-66-0310
6280	54-40-3103	334-5182	16-22-1190	18-22-1121	22-18-0270	22-64-0220	23-44-0020	23-66-0310
6293	54-40-1814	309-6160	16-62-1050	18-62-1050	22-18-0300	22-64-0340	–	23-66-0430
6320	54-40-1502	176-6394	16-82-1290	18-82-1085	22-18-0095	22-64-0080	23-44-0050	23-66-0500
6331	54-40-1842	349-7670	16-62-1100	18-62-1050	22-18-0300	22-64-0340	–	23-66-0430
6360	54-40-1512	177-8633	16-82-1300	18-82-1085	22-18-0095	22-64-0080	23-44-0050	23-66-0500
6370	54-40-2003	368-6101	16-82-1801	18-82-1201	22-18-0095	22-64-0430	23-44-0050	23-66-0500
6400	54-40-1522	178-8327	16-82-1310	18-82-1085	22-18-0095	22-64-0080	23-44-0050	23-66-0500
6505*	54-40-4102	335-4212	16-42-1340	18-42-1180	22-18-0100	22-64-0170	23-44-0060	23-66-0230
6510*	54-40-4206	284-247445	16-42-1170	18-42-1120	22-18-0100	22-64-0380	23-44-0060	23-66-0480
6511*	54-40-4250	460-1001	16-42-1420	18-42-1220	22-16-0250	22-64-0385	23-44-0120	23-66-0484
6512*	54-40-4140	483-1001	16-42-1420	18-42-1040	22-16-0250	22-64-0625	23-44-0120	23-66-0751
6543-1	54-42-0301	469-1652	16-22-1295	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0792
6583-1	54-42-0401	470-1851	16-22-1295	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0792
6584-1	54-42-0250	497-1001	16-22-1295	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0792
6747-1	54-42-5151	453-21978	16-22-1295	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0815
6751-1	54-42-0201	468-4591	16-22-1290	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0815
6783-1	54-42-0351	471-1911	16-22-1295	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0792
6798-1	54-42-5501	450-6758	16-22-1295	18-22-1160	22-18-0360	22-64-0665	23-44-0020	23-66-0792
6800	54-44-0100	220-1001	16-22-1106	18-22-1030	22-18-0090	22-64-0220	23-44-0060	23-66-0310
6810	54-44-0200	444-1001	16-12-0010	18-12-0010	22-18-0480	22-64-0710	–	23-66-0895
6820	54-44-0300	445-1001	16-22-1310	18-22-1190	22-18-0485	22-64-0715	31-12-0090	23-66-0900
6830	54-44-0400	446-1001	16-22-1310	18-22-1190	22-18-0485	22-64-0715	31-12-0090	23-66-0900
8600	54-47-0100	440-1001	16-12-0020	18-12-0020	22-18-0490	22-64-0725	–	23-66-0905
9051	54-26-1300	466-1001	16-42-1355	18-42-1195	22-16-0260	22-64-0425	–	23-66-0575
9060	54-26-1400	463-1001	16-42-1365	18-42-1205	22-16-0265	22-64-0425	–	23-66-0585
9070	54-26-1500	462-1001	16-42-1365	18-42-1205	22-16-0265	22-64-0425	–	23-66-0585

★ For Sawzall Blade Clamp, order 42-68-0073 - - - Blade Clamp Screw, 06-75-2400 - - - Socket Wrench, 49-96-0070.

● For Drill Chucks and Chuck Keys, see page 10.



Milwaukee Factory SERVICE CENTERS

A Nationwide Network of MILWAUKEE Service Centers ready to serve you, and your immediate tool needs.



A nation-wide network of Factory Service Centers and Authorized Service Stations has been established to assure prompt, efficient service. These organizations, staffed with factory trained personnel, are your source for service or MILWAUKEE ELECTRIC TOOL warranty repairs. They carry an adequate stock to supply genuine replacement parts.

FACTORY SERVICE
4320 North 124th St.
Wauwatosa, Wis. 53225
Phone (414) 781-3600

ATLANTA
1434 Tullie Road, N.E.
Atlanta, Georgia 30329
Phone 404 636-4377

BOSTON
143 California St.
Newton, Mass. 02158
Phone 617 244-4483

CHICAGO
7315 N. Monticello Ave.
Skokie, Ill. 60076
Phone 312 539-9173

CLEVELAND
7600 Wall Street
Cleveland, Ohio 44125
Phone 216 524-8040

DALLAS
7205 Envoy Court
Dallas, Texas 75247
Phone 214 637-4820

DENVER
2620 W. 2nd Avenue
Denver, Colorado 80219
Phone 303 922-1163

DETROIT
999 Troy Court
Troy, Mich. 48084
Phone 313 585-8252

LOS ANGELES
2561 W. Olympic Blvd.
Los Angeles, Calif. 90006
Phone 213 382-3000
and 213 382-2361

or

1130 N. Magnolia St.
Anaheim, Calif. 92801
Phone 714 827-3970

MIAMI
8101 N.W. 33rd St.
Miami, Florida 33122
Phone 305 592-0442

MINNEAPOLIS
2200 W. 94th Street
Bloomington, Minn. 55431
Phone 612 884-7258

NEW YORK
35-01 — 24th St.
Long Island City, N.Y. 11106
Phone 212 361-0330
N.J. 201 622-7752

PHILADELPHIA
388 Reed Road
P.O. Box 224
Broomall, Pa. 19008
Phone 215 544-5544
Phila. 215 528-6771

SAN FRANCISCO
329 Littlefield Ave.
So. San Francisco, Calif. 94080
Phone 415 583-8484
S.F. 415 761-2851

SEATTLE
503 S. Michigan St.
P.O. Box 80346
Seattle, Washington 98108
Phone 206 762-8430

AUTHORIZED SERVICE STATIONS

ALABAMA
Power Tool Services, Inc.
1113 4th Avenue South
Birmingham, Alabama 35233

ALASKA
Aero Services Co.
203 Post Road
P.O. Box 1554
Anchorage, Alaska 99501

Aero Services Co. of Fairbanks
P.O. Box 2191
Fairbanks, Alaska 99701

ARIZONA
Glenn's Tool Service
4036 N. 13th Way E.
Phoenix, Arizona 85014

Electric Motor Company
1028 E. Broadway
Tucson, Arizona 85719

ARKANSAS
Henninger, Inc.
1206 S. Main St.
Little Rock, Ark. 72202

CALIFORNIA
Blackstone Electric Motor Shop
1251 Blackstone Avenue
Fresno, California 93703

Sacramento Industrial Electric Co.
6325 Elvas Avenue
Sacramento, California 95819

Precision Mechanical
260 Commercial Street
San Jose, California 95112

CONNECTICUT
Portable Power Tool Repair Co.
447 Arch Street, Rear
New Britain, Connecticut 06051

FLORIDA
Turner Electric Works
1020 E. 8th St., P.O. Box 4247
Jacksonville, Florida 32201

Florida Electric Motor Service
1128 Atlanta Avenue
Orlando, Florida 32806

Electrical Repair Co.
1228 East Cass Street
Tampa, Florida 33602

HAWAII
Central Service & Sales, Inc.
687 Auahi Street
Honolulu, Hawaii 96813

IDAHO
K. C. Supply Co.
814 N. Manville Street
Boise, Idaho 83704

INDIANA
Electric Tool & Motor Service, Inc.
1001 North Illinois
Indianapolis, Indiana 46204

IOWA
Jim's Appliance Service
901 Ninth St., S.W.
Cedar Rapids, Iowa 52404

Five Cities Tool Service, Inc.
743 Schmidt Road
Davenport, Iowa 52802

Electrical Engineering & Equip. Co.
1808 Delaware Street
Des Moines, Iowa 50317

KANSAS
Mears Electric Co., Inc.
925 E. Murdock
Wichita, Kansas 67202

KENTUCKY
City Electric Motor Shop
492 East High Street
Lexington, Kentucky 40508

Electric Tool Service Corp.
757 Logan Street
Louisville, Kentucky 40204

LOUISIANA
Beerman Precision Machine Wks., Inc.
2021 Thalia Street—P.O. Box 53432
New Orleans, Louisiana 70150

MARYLAND
Roland Electrical Company
330 West 23rd Street
Baltimore, Maryland 21211

Turner Electric Company
201 Ethan Allen Avenue
Takoma Park, Maryland 20012

MISSISSIPPI
Flannigan Electric Co. Inc.
328 Oakdale Street
Jackson, Mississippi 39204

MISSOURI
Heath Sales & Services, Inc.
518-20 East 16th Street
Kansas City, Missouri 64108

P. M. Electric Company, Inc.
5280 Fyler Avenue
St. Louis, Missouri 63139

MONTANA
Mosch Electric Motors
326 - 3rd Avenue South
Great Falls, Montana 59401

NEBRASKA
Flohr Electric Service, Inc.
2516 Cuming Street
Omaha, Nebraska 68131

NEVADA
Stewart's Electric Motors, Inc.
2113 Western Avenue
Las Vegas, Nevada 89102

NEW MEXICO
Electric Service, Inc.
1007 Bridge Boulevard, S.W.
Albuquerque, New Mexico 87105

NEW YORK
Richter Electric Motor Repair
1559 Niagara Street
Buffalo, New York 14213

Berger Electric Corp.
295 Mt. Read Blvd.
P.O. Box 1907
Rochester, New York 14603

Barrett Electric Service Inc.
112 Henry Street
Schenectady, New York 12304

Ramsing Electric Service Co.
125 Charles Avenue (Syracuse)
Solvay, New York 13209

NORTH CAROLINA
Portable Tool Service
724 N. Brevard Street
Charlotte, North Carolina 28202

OHIO
Cincinnati Electrical Repair Co.
2023 Elm Street
Cincinnati, Ohio 45210

B. R. Shoemaker & Son
950 Oakland Park Avenue
Columbus, Ohio 43224

M & R Electric Motor Service, Inc.
1516 East Fifth Street
Dayton, Ohio 45403

OKLAHOMA
Hydraulic Equipment Company
515 South Broadway
Oklahoma City, Oklahoma 73125

Hammond Electric Co.
1510 East Third Street
Tulsa, Oklahoma 74120

OREGON
Keith's Electric Motor Service
678 Olive Street
Eugene, Oregon 97401

Walker Electric Works
206 Northwest 10th Ave.
Portland, Oregon 97209

PENNSYLVANIA
Snyder Electric Company
1500 Chateau Street
Pittsburgh, Pennsylvania 15233

PUERTO RICO
Cabrera Electronic Shop
Andalucia Esq. Algeria 1001
Rio Piedras, Puerto Rico 00920

RHODE ISLAND
Babine Electric Service Inc.
315 Jefferson Blvd.
Warwick, Rhode Island 02888

SOUTH CAROLINA
Mann Electric Repair Co.
2909 Main St.
Columbia, South Carolina 29201

Delta Ind. Electric Co., Inc.
1906 Meeting Street
P.O. Box 622
Charleston, South Carolina 29402

TENNESSEE
Electric Service Company
3914 McCalla Avenue
Knoxville, Tennessee 37914

Southern Electric Co.
812 Porter Street
Memphis, Tennessee 38126

Allied Electric Motor Co., Inc.
939 - 4th Avenue, South
Nashville, Tennessee 37210

Dixie Industrial Service, Inc.
2108 E. Main St.
Chattanooga, Tenn. 37404

TEXAS
G. E. Jones Electric Co., Inc.
212 No. Polk
Amarillo, Texas 79107

I-T-S Rentals Inc.
3003 Leeland
Houston, Texas 77003

UTAH
Diamond Electric Motor Service
1465 South Second West Street
Salt Lake City, Utah 84104

VIRGINIA
Bryan Electric Company
424 West 25th St.
Norfolk, Virginia 23517

Roy's Electric Motor Service, Inc.
3201 Norfolk Street
Richmond, Virginia 23230

Lloyd Electric Company, Inc.
521 West Salem Ave.
Roanoke, Virginia 24016

WASHINGTON
K & N Electric Motors, Inc.
1311 No. Washington Street
Spokane, Washington 99201

Cooper Electric Motor Service Co.
205 South 4th Avenue
Yakima, Washington 98902



MILWAUKEE ELECTRIC TOOL CORPORATION FACTORY AND HOME OFFICE

13135 W. LISBON RD. • BROOKFIELD, WI 53005 • PHONE: AREA CODE (414) 781-3600

CANADIAN SUBSIDIARY

MILWAUKEE ELECTRIC TOOL (CANADA) LTD., 383 MIDWEST RD., SCARBOROUGH, ONTARIO M1P3A6





Milwaukee

MILWAUKEE ELECTRIC
TOOL CORPORATION
13135 WEST LISBON RD.
BROOKFIELD, WI 53005

LITHO IN U.S.A.